




Republic
DOORS AND FRAMES

Price book

Effective February 27, 2026



Customer Care

Our Customer Care Representatives are available for questions or assistance.

877-671-7011

Customer Service

📞 Press 1
✉️ Republic.Support@allegion.com

Technical Support

Republic is backed by a knowledgeable Product Support team that can be reached at:

📞 **877-671-7011**

Follow the prompts to select Product Support, then Doors and Frames, then Republic.

The team may also be contacted at:

✉️ Doors_Frames_TechProdSupport@allegion.com

List Price Estimating

Republic Factories and Service Centers
✉️ Republic.Estimating@allegion.com

www.republicdoor.com

Administrative offices

Allegion administrative office
11819 N. Pennsylvania St.
Carmel, IN 46032
allegion.com/us

Request for quote

Carolinas

(North Carolina, South Carolina, Virginia)
Carolinas.Quotes@allegion.com

Central

(Illinois, Iowa, Kansas, Missouri, Nebraska)
Central.Quotes@allegion.com

Chicago

(Northern Illinois, Wisconsin)
Chicago.Quotes@allegion.com

Florida

Florida.Quotes@allegion.com

Metro New York

(Metro New York, Northern New Jersey)
Metro.Quotes@allegion.com

Michigan

Michigan.Quotes@allegion.com

Mid Atlantic North

(New York, Western Pennsylvania)
Mid.Atlantic.North.Quotes@allegion.com

Mid Atlantic South

(Delaware, Eastern Pennsylvania, Maryland, Northern Virginia, Southern New Jersey, Washington DC)
Mid.Atlantic.South.Quotes@allegion.com

Midwest

(Indiana, Kentucky, Ohio, West Virginia)
Midwest.Quotes@allegion.com

Mountain States

(Colorado, Idaho, Montana, Nevada, Utah, Wyoming)
Mtn.States.Quotes@allegion.com

New England

(Connecticut, Maine, Massachusetts, New Hampshire, Rhode Island, Vermont)
[NewEngland.Quotes@allegion.com](mailto>NewEngland.Quotes@allegion.com)

North Central

(Minnesota, North Dakota, South Dakota)
NorthCentral.Quotes@allegion.com

Northern California

NoCal.Quotes@allegion.com

Northwest

(Alaska, Oregon, Washington)
Northwest.Quotes@allegion.com

South

(Alabama, Georgia, Louisiana, Mississippi, Tennessee)
South.Quotes@allegion.com

Southern California


(Southern California, Hawaii)
SoCal.Quotes@allegion.com

Southwest

(Arizona, New Mexico)
Southwest.Quotes@allegion.com

Texas

(Arkansas, Texas, Oklahoma)
Texas.Quotes@allegion.com



Contents

Doing business with Allegion	4
General	7
Conditions of sale.....	7
Abbreviations.....	9
Weights.....	11
Doors	17
DP Series.....	17
Honeycomb.....	19
Insulated.....	22
Steel stiffened.....	25
Embossed.....	28
Frames	33
Universal ME Series	33
Drywall MH Series	37
Double egress ME Series	41
Double egress MH Series.....	45

Specialty	49
Lead lined doors and frames.....	49
Bullet resistant doors and frames.....	53
Paladin™ Series doors and frames.....	57
Hurricane/Wind resistant.....	58
Sound transmission control (STC)	62
Sticks	71
SE Series	71
Borrowed lites.....	74
Cut-N-Notch and Panels.....	77
Engineering	83
Valu-Pac	87
Door parts	91
Frame parts	97

Policies and documents

The purchase of Allegion products is governed by the Allegion Authorized Seller Program. For program terms and conditions, and other program details, please visit: www.allegion.com/AuthorizedSeller.

For Warranty information, visit us.allegion.com/warranty or contact Customer Service at 877-671-7011.

Sustainability

Allegion can provide sustainability documentation for select products, ensuring transparency and adherence to environmental standards and building certification programs such as LEED and Living Building Challenge. This documentation includes detailed information on the sustainable practices and materials used, helping you make informed decisions that align with your sustainability goals.

To view the full list of products with declarations, please visit: <https://us.allegion.com/en/resources/sustainability.html>



Online ordering is available through Overtur™ Estimate and Order (OEO)

OEO offers much more than placing online orders including:

- Provides net price for direct customers and list price for indirect customers, integrator partners and end-users
- Online Ordering for direct customers
- Automated price updates
- Ability to export price lists and cross-reference guides in Excel
- Republic Stock Doors, Frames and Modifications are available at this time
- Request a quote or quote revision from an estimate

How to get it:

1. Login or register at <http://360portal.allegion.com>
2. Find the Estimate and Order Icon and follow the instructions to request access
3. The Online Ordering team will begin working on your access with your Allegion Sales Representative

Traditional ordering methods:

Email: Republic.Order.Entry@allegion.com

When using traditional ordering methods, list the product attributes in the order outlined in this price book, which follow the ACN format guidelines.

Training and Troubleshooting

QR Scan the QR Code to access our resource center or visit <https://support.oeo.allegion.com/hc/en-us>

Questions or issues should be reported to Online.Ordering.Support@allegion.com for escalation

HOLLOW METAL ORDER STANDARDS

The following are defaults or standards to be aware of when placing manual orders to Republic and Steelcraft. The intent is to reduce the number of clarification needs for industry common product standards. Many of these are already defaults but important to document.

General Door & Frame Standards

1. Cold Rolled Steel (CRS) unless otherwise stated.
2. For continuous hinges there will not be any additional reinforcement unless otherwise stated or requested.
3. We will default to 4-1/2" universal hinges unless specified or required for performance or certification needs.
4. The quantity of hinges will follow each brand's location and quantity standards outlined in Tech Manual unless otherwise specified.
5. The Door thickness standard of 1-3/4" thick and frames rabbet to accommodate a 1-3/4" thick door is standard unless otherwise specified.
6. Shop drawings and hardware schedules are not considered a purchase order.
7. Please ensure door and frame orders are configured to work together. While we may try, we are not responsible to cross-reference orders, or jobs, to ensure fit and function.

Frames

1. Standard frames, 16 and 14 gauge will be knock down unless indicated otherwise.
 - Steelcraft 12 gauge frames will be square cut as standard
 - Republic 12 gauge frames will be square cut as standard
2. If welding is noted, frames will be face welded unless stated otherwise to be full profile or continuously welded.
3. The frames standard profile of 2" face and unequal rabbet will be the default unless otherwise indicated in that order line.
4. Jamb Anchors:
 - Steelcraft will default to loose wire anchors unless otherwise noted
 - Republic all jamb anchors must be ordered and indicated separately and are shipped loose unless welded is indicated
5. Glazing Bead default size will be the following unless otherwise specified:
 - Steelcraft will be 5/8" x 5/8"
 - Republic will be 3/4" x 5/8"
6. Fire labels will be mylar as default unless "metal" or an hourly rating is specified:
 - Steelcraft will be Intertek (ITS)
 - Republic is UL

Doors

1. Door core will be honeycomb core unless otherwise indicated.
2. The provided door edge seam will be our standard visible edge seam unless otherwise indicated, required for certifications, or part of our standard design.
 - Example: Steelcraft A14 door is standard filled edge and PW-Series is standard welded edge.
3. The default door style will be flush unless otherwise indicated.
4. The door undercut will default to 3/4" unless otherwise specified except for the following:
 - Hurricane product at Steelcraft and Republic will default to 3/8"
 - Sound (STC) doors at Republic are 3/8" for STC Eco (up to STC 47) and 1/4" for STC 48 and greater
 - Tornado Doors, PW-Series, are 3/4", but please note that typical undercut must provide 1/4" max between bottom of door and top of finished floor / threshold
5. Panic devices will be located per template location unless otherwise specified. This includes doors with light kits located below the exit device cross bar.
 - Mortise panic devices will be located to match each brand's standard strike location unless otherwise noted.
6. Pairs of doors with vertical rod devices:
 - Steelcraft will default to a wide inactive leaf unless otherwise specified
7. Republic, for all paired openings the frame header is undersized 1/16"

this page intentionally blank

CONDITIONS OF SALE

1. CONFORMANCE TO REGULATIONS - Manufacture, shipment and delivery are subject to any prohibition, restriction, priority, allocation regulation or condition imposed by or on behalf of the United States of America which may prevent or interfere with fulfillment of this order.
2. SELLER'S ACCEPTANCE - Until accepted in writing on this form by Republic Doors & Frames ("Seller"), Buyer's order shall constitute an offer to purchase; when so accepted by Seller, this form shall constitute the entire contract between the parties [and Seller shall not be bound by any terms, conditions, representations, or warranties, express or implied, except as state herein]. It is understood by the parties, and Buyer hereby agrees, that no term or condition contained in any order submitted by Buyer which is inconsistent with, additional to or different from the terms and conditions stated herein shall be binding on Seller unless Specifically agreed to by Seller in a written acknowledgment or acceptance; unless Seller specifically so agrees, any inconsistent, additional or different terms or conditions appearing in any order submitted by Buyer shall be deemed waived by Buyer. Receipt by Buyer of Seller's acceptance of goods without prompt objection to the terms and conditions herein set forth shall constitute acceptance by Buyer of such terms and conditions. It is understood that Seller's acceptance of Buyer's order is subject to credit approval.
3. GENERAL CONTRACT - Seller shall not be bound by the provisions of any contract and related documents governing the general construction requirements except for that portion of the specifications, unless modified in Seller's Acknowledgment, which describes the scope of Sellers work.
4. DELAY - In no event shall Seller be liable for any claims for any consequential or any other damages resulting from failure or delay in delivery of material and/or field labor (if field labor is included as part of this order). Seller will endeavor to ship promptly and to make delivery on the date requested on the front hereof; however, time is not of the essence. It is understood that Seller cannot guarantee any time for delivery; that delivery to the initial carrier shall constitute delivery to Buyer; that Seller's responsibility ceases upon delivery in good order to such carrier; and that all goods are shipped at Buyer's risk. In any event, Seller will not be liable for any delay or failure in delivery or shipment of goods or for any default or failure to perform this contract, or for any damages suffered by reason thereof, when such delay, failure or default is directly or indirectly due to accident (in manufacture or otherwise), fire, flood, riot, war, embargo, labor dispute or stoppage, inadequate transportation, shortage of material or supplies, delay or default on the part of the Seller's vendor, regulation by any governmental authority or any like or dissimilar cause beyond Seller's control. In the event of the occurrence of any such cause or contingency, Seller may extend the delivery schedule of this contract for the duration of such cause or contingency or, at its option, cancel this contract in whole or in part without liability.
5. PARTIAL DELIVERY - Partial delivery shall be accepted by the Buyer and paid for at the price and on the terms herein stated. Any partial delivery of merchandise hereunder, whether or not provided for herein, shall constitute a separate sale, and payment therefor shall be separately made when due.
6. CLAIMS - Claim for errors, deficiencies or imperfections or delay not covered by Section 3 above will not be considered unless made in writing within 30 days after receipt of material. Seller, at its option, will replace or repair such materials as proven defective, or to allow for credit for their return. Seller will not accept the return of materials for credit or replacement without its previous written authority for such return. If materials appear defective, Buyer should discontinue their use and notify Seller Promptly so that Seller may investigate. Seller will not allow any claim for labor or expense occasioned by the use of defective materials, nor be responsible for damages beyond Seller's price of the defective material. Seller shall not be liable for any claims for consequential damages whether founded in contract or in tort. Risk of loss involving materials should be F.O.B. shipping point, even though transportation costs may be included in price. Risk of loss shall be borne by Buyer and Buyer shall pursue claims with the carrier in the event of loss or damage in transit. Seller shall not be liable for liquidated damages. Expenses in connection with detention of carrier's equipment at destination shall be for the account of Buyer. The remedies to Buyer hereunder are exclusive.
7. INDEMNIFICATION - Seller's obligation to indemnify Buyer for any cause, except for patent infringement as provided in this Acknowledgment shall be limited to the established sole negligent acts of Seller's agents and employees.
8. CANCELLATION - After acceptance of Seller, this contract may not be canceled or modified, or releases hereunder held be Buyer after the order is in process, except by Seller's written agreement. If any cancellation or modification is agreed to by Seller, Buyer will promptly pay all reasonable engineering and other expenses incurred by Seller prior to its agreement to such cancellation or to be incurred by Seller in connection with such modification.
9. PAYMENT TERMS - The terms of payment specified on the front hereof shall be subject to change or limitation by Seller at any time either before or after delivery of any part of the goods under this contract, and Seller may demand payment in cash before delivery. Delivery may be withheld or shipment stopped in transit on an accepted order without any liability on the part of the Seller if, in the Seller's opinion, Buyer's ability to pay for the goods on the terms and conditions stated herein is in doubt.
10. LIENS - Seller shall not be required to waive its right of Mechanic's Lien in advance of payment.

11. TAXES - Any tax, excise, duty or other governmental charge, whether federal, state, municipal or foreign, now or hereafter levied upon the manufacture, sales, use of shipment of goods contracted for or sold hereunder will be charged to and paid for by Buyer. Tax exemption certificates acceptable to such taxing authorities will be accepted in lieu of such payment.
12. SELLER'S OPTIONS - If Buyer shall fail to make payments on this or any other order in accordance with Seller's terms, or if Seller shall have any doubt as to Buyer's responsibility, Seller may suspend performance hereunder, except upon receipt of security satisfactory to Seller.
13. COLLECTION - In the event Seller is forced to place the Buyer's account for collection, Buyer agrees to pay all reasonable costs of collection including, but not limited to, reasonable attorney's fees and court costs.
14. QUANTITY, WEIGHT AND SIZE - Material, unless otherwise provided shall be invoiced in accordance with Seller's published schedules of weights, areas, bundles and standard lengths, which invoicing shall govern settlement in absence of a contrary showing.
15. SHOP PAINT - Where a shop coat of paint is specified, it shall mean one temporary protective coat of Seller's standard shop paint and no special treatment, field or permanent painting of any kind is included unless expressly stated on the face hereof.
16. CHANGES IN WORK - Subsequent changes in the scope of the work required of seller shall be subject to any adjustment in price to be agreed upon by Buyer and Seller prior to any obligation of Seller for such changes, and such adjustment shall not be affected by the decision of third parties.
17. LITERATURE AND DESIGN - Material unless otherwise provided shall be in accord with Seller's literature, unless modified in the interest of improvement, in which event it shall be deemed in accord with such literature. Seller assumes no responsibility for design prepared by others.
18. TRANSPORTATION ADJUSTMENT - When the price includes transportation it shall be adjusted to the increase or decrease in transportation rates at the time of shipment with rates at date this order is acknowledged.
19. INSPECTING AND TESTING - Seller shall not be liable for inspecting and testing charges unless expressly stated on the face hereof.
20. PATENTS - Seller shall indemnify and save harmless Buyer from any judgement for damages and cost which may be rendered against Buyer in any suit brought against Buyer on account of the infringement by the materials, per se, supplied by Seller hereunder of any United States patent, provided prompt written notice be given Seller of the bringing of any such suit and an opportunity be given Seller to settle or defend the same as Seller may see fit, provided further that every reasonable assistance which Seller may require in defending any such suit be rendered to Seller by Buyer, the forgoing states the entire liability of Seller to Buyer for patent infringement.
21. APPROVAL OF DRAWINGS - If Seller prepares drawings or placing details, approval thereof by the Buyer or his representative or the representative of the owner of the project for which Seller's materials are regarded as a final interpretation of all other documents, with respect to such drawings or details, and constitute authority for Seller to furnish material in accordance with those drawings or details.
22. DESIGN SAFETY FACTOR - Buyer agrees to any design safety factor provided in the products covered by this transaction is to accommodate variations in the properties of materials, manufacturing and operating conditions, and design assumptions, and under no condition should be considered as implying authorization for or protection against loads on such products which exceed the design limits.
23. COLLATERAL MATERIALS AND LABOR - This order does not include: collateral steel for fastening such material, ornamental iron, anchor bolts, glass, putty, glazing, glass cleaning, field painting, grouting, pointing, caulking, or any other material or labor unless expressly stated on the face hereof.
24. ARBITRATION - Neither Buyer or Seller shall be required to submit to arbitration in the event of any dispute unless Buyer and Seller shall agree in writing hereto at the time of such dispute, and arbitration is not to be a condition precedent, except by mutual agreement of the parties in writing, to the right of legal action by either part.
25. WARRANTY - Seller warrants to Buyer that it will, at its option and in its sole discretion, furnish F.O.B. McKenzie, TN (or other point of origin), a replacement for, repair, or refund the purchase price to Buyer of any goods of its manufacture or part or portion thereof proved to its satisfaction to be defective in workmanship for material under normal use and service within one year (365 days) from the date of delivery to such Buyer, provided that notice of such defect is given to Seller within such one year (365 days) period. Seller makes no warranty with respect to items on the reverse side here of supplied to Buyer by Seller but manufactured by others, except to the extent of any warranty given to Seller by such others. Buyer further agrees that Seller is not responsible for any other conditions over which Seller has no control. In no case shall Seller be liable for consequential damages arising from breach of any of the foregoing warranties. THERE IS NO IMPLIED WARRANTY OF MERCHANTABILITY OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, AND SELLER WILL NOT BE RESPONSIBLE FOR ANY DAMAGES WHATSOEVER, OR FOR ANY LABOR, TRANSPORTATION OR OTHER COSTS OR EXPENSES RELATING TO SUCH REPLACEMENT OR SUCH REPAIR, INCLUDING ANY INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES. This Warranty is for Buyer's exclusive benefit and is not assignable or transferable, nor is Buyer permitted to present to its customer, or any third party, that it may rely on the Warranty.

ABBREVIATIONS	
ACT	Active
ANSI	American National Standards Institute
AR	Adams Rite
AST	Astragal
AUTO	Automatic
B	Beveled lock edge
BH	Binding Head
BJ	Blank Jamb
BS	Backset
C	Cylindrical Lock Prep (2-3/8" Backset)
CAD	Cadmium
CB	Cross Buck
CERT	Certified
CH	Cylindrical Lock Prep (2-3/4" Backset)
CHOL	Cylindrical Lock Edge Prep Omit Face Cutout
CL	Centerline
C/O	Cutout
CR	Closer reinforcement
CRS	Cold rolled steel
COMM	Communicating
CONC V-ROD	Concealed Vertical Rod
CVR	Concealed Vertical Rod
COR/RUS	Corbin/Russwin
CTSK	Countersunk
CW	Continuous Weld
CY	Inverted Blade Louver
CYL	Cylinder
DE	Four (4) Channel Door Without McKenzie Edge
DL	Four (4) Channel Door With Lapped Edge Seams
DP	Pan and Lid Door
DS	Double Swing
DDLK	Dead lock
DEV	Device
DD	Dutch door
DRS	Doors
ELEC	Electric
P1	Embossed 1 Panel Door
P2	Embossed 2 Panel Door
P4	Embossed 4 Panel Door
P6	Embossed 6 Panel Door
P8	Embossed 8 Panel Door
F/AST	Flat Bar Astragal
F	Flush
FA	Folger Adams
FB	Flushbolt
FC	Floor Clearance
FG	Full Glass

ABBREVIATIONS	
F.H.	Flat Head
FL	Full Louver
FRM	Frame
FW	Face Weld
G	Half Glass (G2, G3, G4, G6)
GA	Gauge
GB	Glazing Bead
GBO	Glass By Others
GLV	Galvanized/Galvanneal
GOV'T	Government
GSD	Guide Sheet Doors
GSF	Guide Sheet Frames
HJ	Hinge Jamb
HVY	Heavy
H	Heavy Weight Hinge (example: 5H)
HS	Half Surface
HDWE	Hardware
HNG	Hinge
HNG-BS	Hinge Backset
HR	Hour
INA	Inactive Door
INS	Insulated - Polystyrene
INT	Intermediate
ITS	Intertek Testing Services
I/S	Inside
I/S-PNL	Inside Panel
L	Louver
LF	Leaf
LH	Left Hand
LHR	Left Hand Reverse
LIN	Lineal
LOC	Location
M	Mortise Lock Preparation
MAS	Masonry Anchor
ME	Masonry Frame (Mitered Corner)
MH	Drywall Frame (Mitered Corner)
MK#	Mark Number
MIN	Minute
MISC RNF	Miscellaneous Reinforcement
MOD	Modifiable Door
MOL	Mortise Lock Edge Prep (No Face Cutout)
MOLP	Mortise Lock Edge Prep with Face Prep
MRC	Monarch
M-RNF	Mortise Exit Reinforcement
M.S.	Machine Screw
N	Narrow Lite
NH	Non-Handed

ABBREVIATIONS

NT	Non-Template
NS	Non-Standard
O.H.	Oval Head
OH	Omit Hinge
OHOL	Omit Hinge/Omit Lock Prep
OL	Omit All Lock and Latch Prep
OS	Omit Strike
OBS	Open back strike
OS/PNL	Outside Panel
OSH	Omit Silencer Hole
PA	Parallel Arm
PHIL	Phillips Head
PNL	Panel
PIP	Panel in place
PLT	Plate
POA	Prepared Opening Anchor
PR	Pair
PREP	Preparation
PP-RNF	Push Pull Reinforcement
PS	Polystyrene
RH	Right Hand
RHR	Right Hand Reverse
RIM	Rim Exit Device
RIM-RNF	Rim Exit Device Reinforcement
RIX	Rixson
RNF	Reinforcement
RPL	Remove Panel
SE	Sticks Masonry Profile
SCR	Sleeve Closer reinforcement
S.D.S.	Self Drilling Screw
SGT	Sargent
SH	Sticks Drywall Profile
SJ	Strike Jamb
SLB	Seamless-Bondo
SLW	Seamless Weld
SS	Steel Stiffened
SSA	Steel Stud Anchor
STC	Sound Transmission Class
STD	Standard
S.T.S.	Self Tapping Screw
SUAW	Set Up and Weld
SIL	Silencer
SPC	Special
S	Standard Weight Hinge
STK	Strike
SB	Surface Bolt
S-HDWE	Surface Hardware

ABBREVIATIONS

TAPPL	Tap Plate
TR	Temperature Rise
T/L	Top Leaf
UL	Underwriters Laboratories
URT	Urethane
UNIFIT	Metal Replacement Doors
UNIV	Universal
V	Vision Lite
V-ROD	Vertical Rod
VIEW	Viewer
VD	Von Duprin
W/O	Without
WD	Wood
WH	Warnock Hersey
WMA	Wire Masonry Anchor
WOPOA	Welded on Prepared Opening Anchor
WSA	Wood Stud Anchor
WT	Weight
WD-STUD	Wood Stud
478	4-7/8" Strike

Examples

- For doors with panel in place (PIP), the description will read 22x33G C/O-PIP.
- For doors with the vision insert (GBO) or louver installed, the description will read 22x33G or 24x24L.
- For doors with cutout and remove panel, the description will read 22x33G C/O-RPL.

Please note that for steel stiffened doors both the vision insert (GBO) and louver cutouts will receive reinforcing channels unless otherwise instructed.

DOOR & FRAME SIZES ARE DESIGNATED AS FOLLOWS:

30	=	3'0"
310	=	3'10"
70	=	7'0"
710	=	7'10"
100	=	10'0"
3070	=	3'0" Wide x 7'0" High

Nominal Sizes, Width and Height

DOOR WEIGHTS

SIZE	DP 20	DP18	DL 20	DL 18	DL 16	DE 14	DL 18 STEEL STIFFENED	DL 16 STEEL STIFFENED	DE 14 STEEL STIFFENED
2068	N/A	N/A	49	62	76	84	78	98	106
2468									
2668	57	75	61	77	95	106	98	123	133
2868	61	80	65	82	102	113	104	131	141
21068	65	85	69	87	108	120	111	139	50
3068	69	90	73	92	114	127	117	148	159
3468	76	101	81	103	127	141	130	164	177
3668	80	106	86	108	133	148	137	172	186
3868	84	111	90	113	140	155	143	180	194
31068	88	116	94	118	146	162	150	189	203
4068	91	121	98	123	152	169	156	197	212
4010	N/A	N/A	N/A	N/A	N/A	N/A	206	232	295
2070	N/A	N/A	51	65	80	89	82	103	111
2470	56	74	60	75	93	103	96	121	130
2670	60	79	64	81	100	111	102	129	139
2870	64	84	68	86	107	118	109	138	148
21070	68	90	72	92	113	126	116	146	158
3070	72	95	77	97	120	133	123	155	167
3470	N/A	100	N/A	102	127	140	130	164	176
3670	N/A	111	N/A	113	140	155	143	181	195
3870	N/A	116	N/A	119	147	163	150	189	204
31070	N/A	121	N/A	124	153	170	157	198	213
4070	N/A	127	N/A	129	160	177	164	207	223
5070	N/A	N/A	N/A	169	196	258	219	241	329
2072	N/A	N/A	N/A	66	82	91	84	106	114
2472	N/A	N/A	N/A	77	95	106	98	123	133
2672	N/A	N/A	N/A	83	102	113	105	132	142
2872	N/A	N/A	N/A	88	109	121	112	141	152
21072	N/A	N/A	N/A	94	116	129	119	150	161
3072	N/A	N/A	N/A	99	123	136	126	159	171
3472	N/A	N/A	N/A	110	136	151	140	176	190
3672	N/A	N/A	N/A	116	143	159	147	185	199
3872	N/A	N/A	N/A	121	150	166	154	194	209
31072	N/A	N/A	N/A	124	153	170	157	198	213
4072	N/A	N/A	N/A	132	164	182	168	212	228
5072	N/A	N/A	N/A	173	201	265	221	249	313
2080	N/A	N/A	N/A	74	91	101	94	118	127
2480	N/A	N/A	N/A	86	107	118	109	138	148
2680	N/A	N/A	N/A	92	114	127	117	148	159
2880	N/A	N/A	N/A	99	122	135	125	157	170
21080	N/A	N/A	N/A	105	130	144	133	167	180
3080	N/A	N/A	N/A	111	137	152	141	177	191
3480	N/A	N/A	N/A	123	152	169	156	197	212
3680	N/A	N/A	N/A	129	160	177	164	207	223
3880	N/A	N/A	N/A	136	168	186	172	217	233
31080	N/A	N/A	N/A	142	175	194	1280	226	244
4080	N/A	N/A	N/A	148	183	203	187	236	254
5080	N/A	N/A	N/A	192	223	294	247	278	349

ME SERIES 16 GAUGE FRAME WEIGHTS

FRAME SIZE	5-3/4"	6-3/4"	7-3/4"	8-3/4"	10-3/4"	12-3/4"
2068	35	38	41	44	50	55
2468	36	39	42	45	51	56
2668	36	39	42	45	51	57
2868	37	40	43	46	52	58
21068	37	40	43	46	52	58
3068	37	40	43	46	52	59
3468	38	41	44	47	53	60
3668	38	41	45	48	54	60
3868	39	42	45	48	54	61
31068	39	42	45	49	55	61
4068	39	43	46	49	55	62
4868	42	45	48	52	58	65
5068	42	45	49	52	59	66
5468	43	46	50	53	60	67
5868	43	47	50	54	61	68
6068	44	47	51	54	61	68
6868	45	49	52	56	63	71
7068	45	49	53	57	64	71
7468	46	50	54	57	65	72
7868	47	51	54	58	66	73
8068	47	51	55	59	66	74
10068	53	57	61	66	74	83
2070	37	40	43	46	52	58
2470	37	40	43	46	52	59
2670	38	41	44	47	53	59
2870	38	41	44	47	53	60
21070	38	41	45	48	54	60
3070	39	42	45	48	54	61
3470	39	43	46	49	55	62
3670	40	43	46	49	56	62
3870	40	43	47	50	56	63
31070	40	44	47	50	57	64
4070	41	44	47	51	57	64
4870	43	47	50	53	60	67
5070	43	47	50	54	61	68
5470	44	48	51	55	62	69
5870	45	48	52	56	63	70
6070	45	49	52	56	63	71
6870	46	50	54	58	65	73
7070	47	51	54	58	66	73
7470	48	51	55	59	67	75
7870	48	52	56	60	68	76
8070	49	53	56	60	68	76
10070	54	59	63	67	76	85

FRAME SIZE	5-3/4"	6-3/4"	7-3/4"	8-3/4"	10-3/4"	12-3/4"
2072	37	40	43	46	52	59
2472	38	41	44	47	53	60
2672	38	41	45	48	54	60
2872	39	42	45	48	54	61
21072	39	42	45	49	55	61
3072	39	43	46	49	55	62
3472	40	43	47	50	56	63
3672	40	44	47	50	57	64
3872	41	44	47	51	57	64
31072	41	44	48	51	58	65
4072	41	45	48	52	58	65
4872	44	47	51	54	61	68
5072	44	48	51	55	62	69
5472	45	48	52	56	63	70
5872	45	49	53	57	64	71
6072	46	50	53	57	64	72
6872	47	51	55	59	66	74
7072	48	51	55	59	67	75
7472	48	52	56	60	68	76
7872	49	53	57	61	69	77
8072	49	53	57	61	69	77
10072	55	59	64	68	77	86
2080	42	45	48	52	58	65
2480	42	46	49	53	59	66
2680	43	46	50	53	60	67
2880	43	47	50	53	60	67
21080	43	47	50	54	61	68
3080	44	47	51	54	61	68
3480	44	48	52	55	62	70
3680	45	48	52	56	63	70
3880	45	49	52	56	63	71
31080	45	49	53	57	64	71
4080	46	50	53	57	64	72
4880	48	52	56	60	67	75
5080	49	53	57	61	68	76
5480	50	54	57	61	69	77
5880	50	54	58	62	70	78
6080	51	55	59	63	71	79
6880	52	57	61	65	73	82
7080	53	57	62	66	74	83
7480	54	58	62	67	75	84
7880	54	59	63	68	76	85
8080	55	60	64	68	77	86
10080	59	64	69	74	83	93

ME SERIES 14 GAUGE FRAME WEIGHTS

FRAME SIZE	5-3/4"	6-3/4"	7-3/4"	8-3/4"	10-3/4"	12-3/4"
2068	44	48	51	55	62	69
2468	45	49	52	56	63	71
2668	45	49	53	57	64	72
2868	46	50	53	57	65	72
21068	46	50	54	58	65	73
3068	47	50	54	58	66	74
3468	47	51	55	59	67	75
3668	48	52	56	60	68	76
3868	48	52	56	60	68	77
31068	49	53	57	61	69	77
4068	49	53	57	62	70	78
4868	52	56	60	65	73	82
5068	52	57	61	65	74	82
5468	53	58	62	66	75	84
5868	54	59	63	67	76	85
6068	55	59	64	68	77	86
6868	56	61	66	70	79	89
7068	57	61	66	71	80	89
7468	58	62	67	72	81	91
7868	58	63	68	73	83	92
8068	59	64	69	74	83	93
10068	66	71	77	82	93	104
2070	46	50	53	57	65	72
2470	47	50	54	58	66	74
2670	47	51	55	59	67	74
2870	47	51	55	59	67	75
21070	48	52	56	60	68	76
3070	48	52	56	60	68	77
3470	49	53	57	62	70	78
3670	50	54	58	62	70	79
3870	50	54	58	63	71	79
31070	51	55	59	63	72	80
4070	51	55	59	64	72	81
4870	54	58	63	67	76	85
5070	54	59	63	67	76	85
5470	55	60	64	69	78	87
5870	56	60	65	70	79	88
6070	56	61	66	70	79	89
6870	58	63	68	72	82	92
7070	58	63	68	73	83	92
7470	59	64	69	74	84	94
7870	60	65	70	75	85	95
8070	61	66	71	76	86	96
10070	68	73	79	85	96	107

FRAME SIZE	5-3/4"	6-3/4"	7-3/4"	8-3/4"	10-3/4"	12-3/4"
2072	47	50	54	58	66	74
2472	47	51	55	59	67	75
2672	48	52	56	60	68	76
2872	48	52	56	60	68	77
21072	49	53	57	61	69	77
3072	49	53	57	62	70	78
3472	50	54	58	63	71	79
3672	51	55	59	63	72	80
3872	51	55	59	64	72	81
31072	51	56	60	64	73	81
4072	52	56	60	65	73	82
4872	55	59	64	68	77	86
5072	55	60	64	69	78	87
5472	56	60	65	70	79	88
5872	57	61	66	71	80	89
6072	57	62	67	71	81	90
6872	59	64	69	74	83	93
7072	59	64	69	74	84	94
7472	60	65	70	75	85	95
7872	61	66	71	76	86	96
8072	62	67	72	77	87	97
10072	69	74	80	86	97	108
2080	52	56	60	65	73	82
2480	53	57	61	66	74	83
2680	53	58	62	66	75	84
2880	54	58	63	67	76	85
21080	54	59	63	67	76	85
3080	55	59	64	68	77	86
3480	55	60	65	69	78	87
3680	56	60	65	70	79	88
3880	56	61	66	70	79	89
31080	57	61	66	71	80	89
4080	57	62	67	71	81	90
4880	60	65	70	75	84	94
5080	61	66	71	76	86	95
5480	62	67	72	77	87	97
5880	63	68	73	78	88	98
6080	63	69	74	79	89	100
6880	65	71	76	81	92	102
7080	66	71	77	82	93	104
7480	67	72	78	83	94	105
7880	68	73	79	84	96	107
8080	69	74	80	86	97	108
10080	74	80	86	92	104	116

MH SERIES 16 GAUGE FRAME WEIGHTS

FRAME SIZE	5-7/8"	6-1/4"	7-1/8"	8-1/4"	9"
2068	38	38	41	44	50
2468	36	39	42	45	51
2668	36	39	42	45	51
2868	37	40	43	46	52
21068	37	40	43	46	52
3068	37	40	43	46	52
3468	38	41	44	47	53
3668	38	41	45	48	54
3868	39	42	45	48	54
31068	39	42	45	49	55
4068	39	43	46	49	55
4868	42	45	48	52	58
5068	42	45	49	52	59
5468	43	46	50	53	60
5868	43	47	50	54	61
6068	44	47	51	54	61
6868	45	49	52	56	63
7068	45	49	53	57	64
7468	46	50	54	57	65
7868	47	51	54	58	66
8068	47	51	55	59	66
10068	53	57	61	66	74
2070	37	40	43	46	52
2470	37	40	43	46	52
2670	38	41	44	47	53
2870	38	41	44	47	53
21070	38	41	45	48	54
3070	39	42	45	48	54
3470	39	43	46	49	55
3670	40	43	46	49	56
3870	40	43	47	50	56
31070	40	44	47	50	57
4070	41	44	47	51	57
4870	43	47	50	53	60
5070	43	47	50	54	61
5470	44	48	51	55	62
5870	45	48	52	56	63
6070	45	49	52	56	63
6870	46	50	54	58	65
7070	47	51	54	58	66
7470	48	51	55	59	67
7870	48	52	56	60	68
8070	49	53	56	60	68

FRAME SIZE	5-7/8"	6-1/4"	7-1/8"	8-1/4"	9"
2072	37	40	43	46	52
2472	38	41	44	47	53
2672	38	41	45	48	54
2872	39	42	45	48	54
21072	39	42	45	49	55
3072	39	43	46	49	55
3472	40	43	47	50	56
3672	40	44	47	50	57
3872	41	44	47	51	57
31072	41	44	48	51	58
4072	41	45	48	52	58
4872	44	47	51	54	61
5072	44	48	51	55	62
5472	45	48	52	56	63
5872	45	49	53	57	64
6072	46	50	53	57	64
6872	47	51	55	59	66
7072	48	51	55	59	67
7472	48	52	56	60	68
7872	49	53	57	61	69
8072	49	53	57	61	69
10072	55	59	64	68	77
2080	42	45	48	52	58
2480	42	46	49	53	59
2680	43	46	50	53	60
2880	43	47	50	53	60
21080	43	47	50	54	61
3080	44	47	51	54	61
3480	44	48	52	55	62
3680	45	48	52	56	63
3880	45	49	52	56	63
31080	45	49	53	57	64
4080	46	50	53	57	64
4880	48	52	56	60	67
5080	49	53	57	61	68
5480	50	54	57	61	69
5880	50	54	58	62	70
6080	51	55	59	63	71
6880	52	57	61	65	73
7080	53	57	62	66	74
7480	54	58	62	67	75
7880	54	59	63	68	76
8080	55	60	64	68	77

SE SERIES 16 GAUGE STICK WEIGHTS

Stick Part	5-3/4"	6-3/4"	7-3/4"	8-3/4"	10-3/4"	12-3/4"
Blank Jamb 10' 3"	21	23	25	27	30	34
Filler With Stop 10' 3"	12	14	16	18	21	25
Filler Without Stop 10' 3"	9	11	12	14	18	22
Blank Jamb 4" Face 10' 3"	29	30	32	34	38	42
6" Face Sill 10' 3"	41	43	45	47	52	56
8" Face Sill 10' 3"	50	52	54	56	60	64
10" Face Sill 10' 3"	58	60	62	64	68	72
12" Face Sill 10' 3"	66	68	70	72	77	81
Cased open Blank Jamb 10' 3"	19	21	23	24	28	32
Double Egress Blank Jamb 10' 3"	22	24	26	28	31	35
Blank Mull 10' 3"	34	36	38	40	43	47
Blank Mull 6' 8"	22	23	25	26	28	31
Blank Mull 7' 0"	23	25	26	27	30	32
Blank Mull 7' 2"	24	25	26	28	30	33
Blank Mull 8' 0"	27	28	30	31	34	37
2 Way Corner Post 10' 3"	49	51	53	54	58	62
3 Way Corner Post 10' 3"	50	52	54	55	59	63

SH SERIES 16 GAUGE STICK WEIGHTS

Stick Part	5-7/8"	6-1/4"	7-1/8"	8-3/4"	9"
Blank Jamb 10' 3"	21	22	24	26	27

SE SERIES 14 GAUGE STICK WEIGHTS

Stick Part	5-3/4"	6-3/4"	7-3/4"	8-3/4"	10-3/4"	12-3/4"
Blank Jamb 10' 3"	27	29	32	34	39	43
Filler With Stop 10' 3"	15	18	20	22	27	32
Filler Without Stop 10' 3"	11	13	16	18	23	27
Blank Jamb 4" Face 10' 3"	36	39	41	43	48	53
6" Face Sill 10' 3"	52	54	57	59	64	70
8" Face Sill 10' 3"	62	64	67	70	75	80
10" Face Sill 10' 3"	72	75	77	80	85	90
12" Face Sill 10' 3"	82	85	88	90	95	100
Cased open Blank Jamb 10' 3"	24	26	29	31	36	40
Double Egress Blank Jamb 10' 3"	28	30	33	35	40	44
Blank Mull 10' 3"	43	46	48	50	55	60
Blank Mull 6' 8"	28	30	31	33	36	39
Blank Mull 7' 0"	30	31	33	34	38	41
Blank Mull 7' 2"	30	32	33	35	38	42
Blank Mull 8' 0"	34	36	37	39	43	47
2 Way Corner Post 10' 3"	62	64	67	69	74	78
3 Way Corner Post 10' 3"	63	65	68	70	75	79



SIZE	STC 50 HM DOOR	FEMA 320/361 DOOR	8-3/4" DEPTH FEMA FRAME	BULLET RESISTANT LEVEL 3 DOOR	8-3/4" DEPTH BULLET RESISTANT LEVEL 3 FRAME	BULLET RESISTANT LEVEL 8 DOOR	8-3/4" DEPTH BULLET RESISTANT LEVEL 8 FRAME	1/16" LEAD LINED DOOR	8-3/4" DEPTH 1/16" LEAD LINED FRAME
2068	130	125	56	143	66	275	86	132	78
2468	151	146	57	167	67	321	88	154	79
2668	162	156	58	179	68	344	89	165	80
2868	173	167	58	190	69	367	89	176	81
21068	183	177	59	202	69	389	90	187	82
3068	194	188	60	214	70	412	91	198	83
3468	216	208	61	238	72	458	93	220	84
3668	227	219	61	250	72	481	94	231	85
3868	237	229	62	262	73	504	95	242	86
31068	248	240	63	274	74	527	96	253	87
4068	259	250	63	286	74	550	97	264	88
5068	N/A	N/A	N/A	357	79	687	103	330	93
2070	136	131	58	150	69	289	89	139	81
2470	159	153	60	175	70	337	91	162	83
2670	170	164	60	187	71	361	92	173	84
2870	181	175	61	200	72	385	93	185	84
21070	193	186	61	212	72	409	94	196	85
3070	204	197	62	225	73	433	95	208	86
3470	227	219	63	250	74	481	97	231	88
3670	238	230	64	262	75	505	98	243	89
3870	249	241	64	275	76	529	99	254	89
31070	261	252	65	287	77	553	100	266	90
4070	272	263	66	300	77	577	101	277	91
5070	N/A	N/A	N/A	375	82	722	106	347	96
2072	139	134	60	154	70	296	91	142	83
2472	162	157	61	179	72	345	93	166	84
2672	174	168	61	192	72	369	94	177	85
2872	186	179	62	205	73	394	95	189	86
21072	197	190	63	218	74	419	96	201	87
3072	209	202	63	230	74	443	97	213	88
3472	232	224	64	256	76	492	99	237	89
3672	244	235	65	269	77	517	100	248	90
3872	255	246	66	282	77	542	101	260	91
31072	267	258	66	294	78	566	102	272	92
4072	278	269	67	307	79	591	103	284	93
5072	N/A	N/A	N/A	384	83	739	108	355	98
2080	155	150	66	171	77	330	101	158	91
2480	181	175	67	200	79	385	103	185	93
2680	194	188	67	214	79	412	103	198	94
2880	207	200	68	229	80	440	104	211	95
21080	220	213	69	243	81	467	105	224	95
3080	233	225	69	257	82	495	106	238	96
3480	259	250	71	286	83	550	108	264	98
3680	272	263	71	300	84	577	109	277	99
3880	285	278	72	314	84	605	110	291	100
31080	298	288	72	329	85	632	111	304	100
4080	311	300	73	343	86	660	112	317	101
5080	N/A	N/A	N/A	429	92	825	119	N/A	N/A

DP SERIES

Honeycomb/Polystyrene


Refer to technical data sheet on page 11

- Thickness: 1-3/4"
- Actual Door Size: Door undersized from nominal by 1/4" in width and 7/8" in height. Standard undercut is 3/4".
- Hinge Edge and Reinforcement: Hinge edge is square edge and includes reversible hinge filler plate. Standard 7 gauge hinge reinforcement.
- Lock Edge: Square edge, 14ga reinf. for mortise or 16ga for cylindrical locks. Compliant with ANSI A1115 standards.
- Edge Seams: Visible seam

- Top Channel: Top Channel is a 16 gauge flush channel, projection welded at a maximum 2-1/2" on center. (Optional - Inverted)
- Bottom Channel: Bottom Channel is an inverted 16 gauge channel, projection welded at a maximum 2-1/2" on center
- Face Skins: 20 gauge or 18 gauge, Cold rolled steel or A60 Galvannealed
- Closer Reinforcement (Optional): 14 gauge standard


- Size Availability: Please see price sheet for sizes as indicated
- SDI 100 Level/Model
 - Level 1 Model 1 (Standard Duty, minimum 20 gauge, hollow steel composite)
 - Level 2 Model 1 or 2 (Heavy Duty, minimum 18 gauge, hollow steel composite)
- Universal Hinge Prep: Allowing for an easy modification from standard to heavy weight hinge prep
- Handing Design: Square edge, non-handed

CORES AVAILABLE FOR DP DOORS




Honeycomb Core

- Efficient in 95% of all weather conditions
- STC rating 38
- Inoperable Slab




Polystyrene Core

- Efficient in extreme weather conditions
- STC rating 35
- Inoperable Slab



Bottom Channel


- 16 gauge steel channel (standard inverted)
- Approximate depth 9/16"




Top Channel

- 16 gauge steel channel (standard flush)
- 14 gauge closer reinforcement, when closer is requested


LOCK EDGE OF PAN



16 gauge cylindrical lock reinforcement with provisions for Gov't Series 160 or 161 cylindrical lock sets (2-3/4" backset) and ANSI A115.2 lock front



14 gauge mortise lock reinforcement with provisions for Gov't Series 86 mortise lockset and ANSI A115.1 lock front

Hinge edge with 7 gauge reinforcements
Shown: 4-1/2" hinges

DP HONEYCOMB CORE 1-3/4" THICK				
Width	Height	20 GA	18 GA	
2'6" and 2'8"	6'8"	\$585	\$685	
	7'0"	\$611	\$705	
3'0"	6'8"	\$587	\$666	
	7'0"	\$611	\$686	
	8'0"	N/A	\$875	
3'4" and 3'6"	6'8"	N/A	\$765	
	7'0"	N/A	\$806	
3'8"	6'8"	N/A	\$871	
	7'0"	N/A	\$872	
4'0"	6'8"	N/A	\$871	
	7'0"	N/A	\$872	
	8'0"	N/A	\$1,092	

DP POLYSTYRENE CORE 1-3/4" THICK				
Width	Height	20 GA	18 GA	
2'6" and 2'8"	6'8"	\$626	\$726	
	7'0"	\$652	\$746	
3'0"	6'8"	\$628	\$707	
	7'0"	\$652	\$727	
	8'0"	N/A	\$916	
3'4" and 3'6"	6'8"	N/A	\$806	
	7'0"	N/A	\$847	
3'8"	6'8"	N/A	\$912	
	7'0"	N/A	\$913	
4'0"	6'8"	N/A	\$912	
	7'0"	N/A	\$913	
	8'0"	N/A	\$1,133	

DP EMBOSSED 1-3/4" THICK				
Pattern	Width	Height	20 GA	18 GA
2-Panel	3'0"	6'8"	N/A	\$966
		7'0"	N/A	\$986
		8'0"	N/A	\$1,179
6-Panel	3'0"	6'8"	N/A	\$966
		7'0"	N/A	\$986
6-Panel (8'0")	3'0"	8'0"	N/A	\$1,179

All DP Embossed are A40 galvannealed.

STEEL TYPES		
Cold rolled steel		Included
A60 Galvanized steel		\$111.00

HINGE PREPARATIONS		
Special hinge locations (vertical)		No charge
4-1/2" Heavy weight hinge prep		No charge
Additional hinge prep (per hinge)		\$27.00
3/16" (7 gauge) Hinge reinforcements (per hinge)		Included

CLOSER PREPARATIONS		
Closer reinforcement - 14 GA x 18" x 6"		\$40.00

LABEL PREPARATIONS		
Mark numbers		No charge
U.L. Mylar label (standard unless specified otherwise)		\$22.00
LIMITATIONS		
U.L. Metal label **LIMITATIONS**		\$51.00
ITS/Warnock Hersey Metal label **LIMITATIONS**		\$51.00
Hurricane label (E330 only) **LIMITATIONS** (See Engineering for details)		

SPECIAL CONSTRUCTIONS		
Special width		N/A
Special height		N/A
3/4" Undercuts		No charge
Flush bottom channel		No charge

INACTIVE LEAF PREPARATIONS		
Flush bolt embossed top/bottom channel		No charge
ANSI 4-7/8" Strike prep - requires the application of a Z astragal with tap plates		\$63.00
Attaching astragal (includes astragal)		\$116.00
Flush bolt (edge, top and bottom prep) ANSI A115.4		\$101.00
▪ DP Series door requiring FB prep accommodated by the application of Z astragal with tap plates		
Surface bolt reinforce only		\$38.00

STRIKE/LOCK PREPARATIONS		
Special lock location (vertical)		No charge
Cylindrical or Cyl-DT (Lever)		No charge
Gov't 86 Edge and panel prep		No charge
Gov't 86 Edge prep only		No charge
Cylindrical dead lock prep (min distance between 7")		\$65.00
Rim reinforcement only		\$54.00


FINISH PREPARATIONS		
Second coat of primer		\$132.00
Finish paint setup charge (never waived)		\$1,433.00
Finish paint		\$360.00
▪ Minimum quantity of 20 per color		
▪ Price includes full carton wrap		

HONEYCOMB

DL/DE Series


Refer to technical data sheet on page 11

- Door Thickness: 1-3/4" (14 gauge = 1-13/16")
- Actual Door Size: Door undersized from nominal by 1/4" in width and 7/8" in height. Standard undercut is 3/4".
- Core: 3/4" Cell Honeycomb Core. STC rating of 38 (standard doors are not STC labeled. See STC doors for labeled doors)
- Hinge Rail and Reinforcement: Hinge edge is non-beveled and reinforced with a continuous 16 gauge steel channel (Optional 10 gauge - DE Series) projection welded at a maximum of 5" on center
 - Additional reinforcement plates are provided (DL Series) at the hinge locations to give a total of 3/16" reinforcement (Backset 1/4")
- Top Channel: Top channel is a flush 16 gauge steel channel, projection welded at a maximum of 2-1/2" on center




- Bottom Channel: Bottom channel is an inverted 16 gauge steel channel, projection welded at a maximum of 2-1/2" on center
- Lock Rail: Lock edge is square and reinforced with a continuous 16 gauge steel channel projection welded at a maximum of 5" on center (Optional - Beveled 1/8" in 2")
- 16 gauge reinforcements for mortise or cylindrical locks are of an integral type in accordance with ANSI A115 standards
- Face Skins: 20 gauge, 18 gauge, 16 gauge, or 14 gauge (DE Series) (cold rolled steel or A60 galvannealed)
 - G90 Galvanized available in 16 or 14 gauge only
- Closer Reinforcement: 14 gauge 18" x 6" (Optional 12 gauge)


- Size Availability
 - Max. 4'0" x 10'0" (Singles)
 - Max. 8'0" x 10'0" (Pairs)
- SDI 100 - Grade/Model: Levels 1-4 and Models 1 and 2 (Maximum Duty Performance level A)
- Label Range: 20 minute through 3 hour / Underwriters Laboratory or ITS/Warnock Hersey
- Edge Seam Construction: Visible seam is standard. Continuously welded seamless or intermittently welded seamless available. (Options)
- Universal Standard/Heavy Weight Hinge: Hinge fillers are used allowing for easy modification from heavy to standard weight hinge prep
- Handing Design: Non-handed standard (Optional handed)




Flush Top




Door Hinge Prep



Paired doors without astragal




Cylindrical Lock Prep




Honeycomb Core




Paired doors with flat bar astragal




Paired doors with "Z" astragal



Mortise Lock Prep




Inverted Bottom Channel





SDI CLASSIFICATIONS

Grade		Model	Construction	Republic Series
I	Physical Performance Level C 1-3/4" (44) and 1-3/8" (35) Standard Duty Minimum Gauge = 20	1	Full Flush	DL 420
		2	Seamless (Unavailable)	DL 420
II	Physical Performance Level B 1-3/4" (44) Only Heavy Duty Minimum Gauge = 18	1	Full Flush	DL 418, DE 418
		2	Seamless	DL 418, DE 418
III	Physical Performance Level A 1-3/4" (44) Only Extra-Heavy Duty Minimum Gauge = 16	1	Full Flush	DL 416, DE 416
		2	Seamless	DL 416, DE 416
IV	Physical Performance Level A 1-3/4" (44) Only Extra-Heavy Duty Minimum Gauge = 14	1	Full Flush	DE 414
		2	Seamless	DE 414



Universal Lock
Prep "DT"

HONEYCOMB DOOR 1-3/4" THICK

Width	Height	20 GA	18 GA	16 GA	14 GA
1'6" – 2'8"	6'8"	\$817	\$913	\$1,123	\$1,533
	7'0"	\$845	\$947	\$1,161	\$1,653
	7'2"	N/A	\$1,027	\$1,196	\$1,654
	8'0"	N/A	\$1,272	\$1,478	\$2,057
	9'0"	N/A	\$1,672	\$1,819	\$2,497
	10'0"	N/A	\$1,869	\$2,109	\$2,551
Over 2'8" – 3'0"	6'8"	\$853	\$921	\$1,140	\$1,546
	7'0"	\$870	\$953	\$1,141	\$1,597
	7'2"	N/A	\$1,055	\$1,236	\$1,677
	8'0"	N/A	\$1,306	\$1,523	\$2,078
	9'0"	N/A	\$1,672	\$1,819	\$2,497
	10'0"	N/A	\$1,869	\$2,109	\$2,551
Over 3'0" – 3'6"	6'8"	N/A	\$1,106	\$1,316	\$1,736
	7'0"	N/A	\$1,154	\$1,359	\$1,757
	7'2"	N/A	\$1,186	\$1,402	\$1,822
	8'0"	N/A	\$1,461	\$1,666	\$2,243
	9'0"	N/A	\$1,859	\$2,098	\$2,511
	10'0"	N/A	\$2,059	\$2,355	\$2,747
Over 3'6" – 4'0"	6'8"	N/A	\$1,218	\$1,426	\$1,830
	7'0"	N/A	\$1,272	\$1,465	\$1,896
	7'2"	N/A	\$1,341	\$1,576	\$1,963
	8'0"	N/A	\$1,576	\$1,757	\$2,339
	9'0"	N/A	\$1,976	\$2,299	\$2,622
	10'0"	N/A	\$2,059	\$2,355	\$2,747

STEEL TYPES

Cold rolled steel	Included
A60 Galvanized steel	\$111.00
G90 Galvanized steel (available in 14 and 16 gauge only)	\$445.00

HINGE PREPARATIONS

Special hinge locations	No charge
4-1/2" or 5" Universal hinge prep	No charge
Additional hinge prep (per hinge)	\$27.00
Electric hinge	\$27.00
▪ Cutout in one hinge reinf., no conduit, no wiring	
Surface mounted hinges (reinforced only)	\$121.00
Continuous hinge reinforcement	\$94.00
Special backset (per hinge)	\$139.00
Power transfer	\$145.00
▪ No junction box or conduit	
▪ Cutout with reinforcement/tap plate(s)	

CLOSER PREPARATIONS

Closer reinforcement	\$40.00
Concealed overhead door closer, holder or stop	\$394.00
Allegion Concealed overhead door closer, holder or stop	\$343.00

SPECIAL FINISH PREPARATIONS

Second coat of primer	\$132.00
Finish paint setup charge (never waived)	\$1,433.00
Finish paint	\$360.00
▪ Minimum quantity of 20 per color	
▪ Price includes full carton wrap	

LOCK PREPARATIONS	
Special lock location	No charge
Special lock backset up to 5"	No charge
Sectional trim prep (mortise lock with function holes)	No charge
Cylindrical dead lock	\$65.00
Mortise dead lock	\$65.00
Rim reinforcement only	\$54.00
Rim reinforcement with function prep	\$60.00
Mortise exit device reinforcement only	\$39.00
Mortise exit device reinforcement with function prep	\$95.00
Allegion Mortise exit device reinforcement with function prep	\$76.00
Surface vertical rod reinforcement only	\$87.00
Surface vertical rod reinforcement with function prep	\$105.00
Allegion Surface vertical rod reinforcement with function prep	\$93.00
Concealed vertical rod	\$648.00
▪ Frame mortise strike (per prep)	
▪ Door per template	
Allegion Concealed vertical rod	\$515.00
▪ Frame mortise strike (per prep)	
▪ Door per template	
Exit alarm reinforcement only	\$66.00
Inset exit device (14 and 16 gauge doors only)	\$505.00
Push pull reinforcement	\$42.00

SPECIAL CONSTRUCTIONS	
Undercut - less than 3/8" price as next larger door height	No charge
Inverted top channel	No charge
Flush bottom channel	No charge
Dutch door (4) 4.5" hinge preps x (1) 161 lock prep	\$353.00
Unifit (retrofit) hinge channel	\$95.00
Seal top or bottom channel and finish smooth each	\$150.00
Mag switch/DPS - Hole only	\$25.00
Mag switch/DPS - Prep and reinf.	\$131.00
Bondo filled edge	\$128.00
Continuous welded edge (N/A in 20 gauge)	\$192.00
Beveled lock edge (1/8" in 2") N/A in 14 gauge and Inactive leafs with strike(s)	\$23.00
10 Gauge hinge and 14 gauge lock channels DE Series (standard on 14 gauge door)	\$166.00
1-3/8" Thick door - DE Series (See Engineering for details)	\$166.00
Door viewer	\$32.00
Mail slot	\$91.00
Automatic door bottom (mortise type)	\$239.00
Conduit/raceway - includes wire pull	\$202.00

LABEL PREPARATIONS	
Mark numbers	No charge
U.L. Mylar label (standard unless specified otherwise)	\$22.00
U.L. Metal label	\$51.00
ITS/Warnock Hersey Metal label	\$51.00
Hurricane label (See Engineering for details)	\$22.00

INACTIVE LEAF PREPARATIONS	
Flush bolt embossed top/bottom channel	No charge
Cylindrical (2-3/4") or mortise (3-1/2") dead lock strike	\$65.00
Electric strike (no conduit)	\$143.00
ASA Strike only	\$63.00
Attaching astragal (includes astragal)	\$116.00
Flush bolt prep (ANSI 115.4)	\$101.00
Surface bolt reinforce only	\$38.00
Open back strike	\$171.00

GLASS KIT OPTIONS			
	Vision/ Narrow Lite up to 100 inch ²	Half Glass over 100 inch ² up to 800 inch ²	Full Glass over 800 inch ²
Cutout with kit installed	\$245	\$290	N/A
Cutout with kit and reinf.	\$332	\$377	\$421
Sunburst kit (1/2" glass included)	\$594	N/A	N/A
Muntin bar (each)	\$160	\$160	\$160
Galvanized kit add	\$131	\$131	\$131
Glass pocket add (other than 1/4")	\$221	\$221	\$221

Prices are based on Republic standard lite kit. (No glass unless noted otherwise.)

CUTOUT ONLY OPTIONS (GLASS KITS & LOUVERS)			
	Up to 100 inch ²	Over 100 inch ² up to 800 inch ²	Over 800 inch ²
Panel in place	\$91	\$91	N/A
Cutout only	\$91	\$91	N/A
Cutout with reinforcement	\$181	\$181	\$181
Round cutout only (no reinf)	\$345	\$345	N/A

LOUVER OPTIONS		
Description	Size	Price
Louver installed no reinf	12" x 12"	\$424.00
Louver installed no reinf	18" x 12"	\$481.00
Louver installed no reinf	24" x 12"	\$568.00
Louver installed no reinf	24" x 18"	\$640.00
Louver installed no reinf	24" x 24"	\$779.00
Louver installed no reinf	24" x 60"	\$1,617.00
Galvanized louver add	-	\$58.00
Fusible link louver add	-	\$426.00

Prices are based on Republic standard louver.

See [Engineering Section](#) for further options and/or details.




INSULATED

DL/DE Series


Refer to technical data sheet on page 11

- Door Thickness: 1-3/4" (14 gauge = 1-13/16")
- Actual Door Size: Door undersized from nominal by 1/4" in width and 7/8" in height. Standard undercut is 3/4".
- Core - 1 lb. density Polystyrene (standard)/ Optional 2 lb. Polyurethane core
- Polystyrene Core
 - "U" Factor = 0.41/STC = 35
 - "R" Factor = 2.43 (per ASTM C1363)
- Polyurethane Core
 - "U" Factor = 0.39/STC = 33
 - "R" Factor = 2.56 (per ASTM C1363)
- Hinge Rail and Reinforcement: Hinge edge is non-beveled and reinforced with a continuous 16 gauge steel channel (Optional 10 gauge - DE Series) projection welded at a maximum of 5" on center
 - Additional reinforcement plates are provided (DL Series) at the hinge locations to give a total of 3/16" reinforcement (Backset 1/4")




- Lock Rail: Lock edge is non-beveled and reinforced with a continuous 16 gauge steel channel projection welded at a maximum of 5" on center (Optional - Beveled 1/8" in 2")
 - 16 gauge reinforcements for mortise or cylindrical locks are of an integral type in accordance with ANSI A115 standards
- Top Channel: Top channel is a flush 16 gauge steel channel, projection welded at a maximum of 2-1/2" on center
- Bottom Channel: Bottom channel is an inverted 16 gauge steel channel, projection welded at a maximum of 2-1/2" on center
- Face Skins: 20 gauge (DL Series), 18 gauge, 16 gauge or 14 gauge (DE Series) (cold rolled steel or A60 galvannealed)
 - * G90 Galvanized available in 16 or 14 gauge only
- Closer Reinforcement: 14 gauge 18" x 6" (Optional 12 gauge)


- Size Availability
 - Max. 4'0" x 10'0" (Singles)
 - Max. 8'0" x 10'0" (Pairs)
- SDI 100 - Grade/Model: Levels 1-4 and Models 1 and 2 (Maximum Duty Performance level A)
- Label Range: 20 minute through 3 hour/ Underwriters Laboratory or ITS/Warnock Hersey (Not available in urethane)
- Edge Seam Construction: Visible seam is standard. Continuously welded or intermittently welded seamless available (Options)
- Universal Standard/Heavy Weight Hinge: Hinge fillers are used allowing for easy modification from standard to heavy weight hinge prep
- Handing Design: Non-handed standard (Optional handed)




Flush Top




Door Hinge Prep




Cylindrical Lock Prep




Insulated Core




Mortise Lock Prep




Inverted Bottom Channel



Paired doors without astragal



Paired doors with flat bar astragal



Paired doors with "Z" astragal



F



V



N



G



FG




LI



D



SDI CLASSIFICATIONS				
Grade		Model	Construction	Republic Series
I	Physical Performance Level C 1-3/4" (44) and 1-3/8" (35) Standard Duty Minimum Gauge = 20		1 Full Flush	DL 420
	2 Seamless (Unavailable)		DL 420	
II	Physical Performance Level B 1-3/4" (44) Only Heavy Duty Minimum Gauge = 18		1 Full Flush	DL 418, DE 418
	2 Seamless		DL 418, DE 418	
III	Physical Performance Level A 1-3/4" (44) Only Extra-Heavy Duty Minimum Gauge = 16		1 Full Flush	DL 416, DE 416
	2 Seamless		DL 416, DE 416	
IV	Physical Performance Level A 1-3/4" (44) Only Extra-Heavy Duty Minimum Gauge = 14		1 Full Flush	DE 414
	2 Seamless		DE 414	



Universal Lock
Prep "DT"

POLYSTYRENE DOOR 1-3/4" THICK					
Width	Height	20 GA	18 GA	16 GA	14 GA
1'6" - 2'8"	6'8"	\$858	\$954	\$1,164	\$1,574
	7'0"	\$886	\$988	\$1,202	\$1,694
	7'2"	N/A	\$1,068	\$1,237	\$1,695
	8'0"	N/A	\$1,313	\$1,519	\$2,098
	9'0"	N/A	\$1,713	\$1,860	\$2,538
	10'0"	N/A	\$1,910	\$2,150	\$2,592
Over 2'8" - 3'0"	6'8"	\$894	\$962	\$1,181	\$1,587
	7'0"	\$911	\$994	\$1,182	\$1,638
	7'2"	N/A	\$1,096	\$1,277	\$1,718
	8'0"	N/A	\$1,347	\$1,564	\$2,119
	9'0"	N/A	\$1,713	\$1,860	\$2,538
	10'0"	N/A	\$1,910	\$2,150	\$2,592
Over 3'0" - 3'6"	6'8"	N/A	\$1,147	\$1,357	\$1,777
	7'0"	N/A	\$1,195	\$1,400	\$1,798
	7'2"	N/A	\$1,227	\$1,443	\$1,863
	8'0"	N/A	\$1,502	\$1,707	\$2,284
	9'0"	N/A	\$1,900	\$2,139	\$2,552
	10'0"	N/A	\$2,100	\$2,396	\$2,788
Over 3'6" - 4'0"	6'8"	N/A	\$1,259	\$1,467	\$1,871
	7'0"	N/A	\$1,313	\$1,506	\$1,937
	7'2"	N/A	\$1,382	\$1,617	\$2,004
	8'0"	N/A	\$1,617	\$1,798	\$2,380
	9'0"	N/A	\$2,017	\$2,340	\$2,663
	10'0"	N/A	\$2,100	\$2,396	\$2,788

INSULATED CORES	
Polystyrene	Included
Polyurethane (N/A for fire rated)	\$206.00
Temperature rise (250° mineral fiberboard)	\$1,087.00

STEEL TYPES	
Cold rolled steel	Included
A60 Galvanized steel	\$111.00
G90 Galvanized steel (available in 14 and 16 gauge only)	\$445.00

HINGE PREPARATIONS	
Special hinge locations	No charge
4-1/2" or 5" Universal hinge prep	No charge
Additional hinge prep (per hinge)	\$27.00
Electric hinge	\$27.00
▪ Cutout in one hinge reinf., no wiring included, no conduit	
Surface mounted hinges (reinforced only)	\$121.00
Continuous hinge reinforcement	\$94.00
Special backset (per hinge)	\$139.00
Power transfer	\$145.00
▪ No junction box or conduit	
▪ Cutout with reinforcement/tap plate(s)	

CLOSER PREPARATIONS	
Closer reinforcement	\$40.00
Concealed overhead door closer, holder or stop	\$394.00
Allegion Concealed overhead door closer, holder or stop	\$343.00

LOCK PREPARATIONS

Special lock location	No charge
Special lock backset up to 5"	No charge
Sectional trim prep (mortise lock with function holes)	No charge
Cylindrical dead lock	\$65.00
Mortise dead lock	\$65.00
Rim reinforcement only	\$54.00
Rim reinforcement with function prep	\$60.00
Mortise exit device reinforcement only	\$39.00
Mortise exit device reinforcement with function prep	\$95.00
Allegion Mortise exit device reinforcement with function prep	\$76.00
Surface vertical rod reinforcement only	\$87.00
Surface vertical rod reinforcement with function prep	\$105.00
Allegion Surface vertical rod reinforcement with function prep	\$93.00
Concealed vertical rod	
▪ Frame mortise strike (per prep)	
▪ Door per template	\$648.00
Allegion Concealed vertical rod	
▪ Frame mortise strike (per prep)	
▪ Door per template	\$515.00
Exit alarm reinforcement only	\$66.00
Inset exit device (14 and 16 gauge doors only)	\$505.00
Push pull reinforcement	\$42.00

LABEL PREPARATIONS

Mark numbers	No charge
U.L. Mylar label (standard unless specified otherwise)	\$22.00
U.L. Metal label	\$51.00
ITS/Warnock Hersey Metal label	\$51.00
Hurricane label (See Engineering for details)	\$22.00

SPECIAL CONSTRUCTIONS

Undercut - under 3/8" price next larger size	No charge
Inverted top channel	No charge
Flush bottom channel	No charge
Dutch door (4) 4.5" hinge preps x (1) 161 lock prep	\$353.00
Unifit hinge channel	\$95.00
Seal top or bottom channel and finish smooth each	\$150.00
Mag switch/DPS - Hole only	\$25.00
Mag switch/DPS - Prep and reinf.	\$131.00
Bondo filled edge	\$128.00
Continuous welded edge (N/A in 20 gauge)	\$192.00
Beveled lock edge (1/8" in 2") N/A in 14 gauge and Inactive leafs with strike(s)	\$23.00
10 Gauge hinge and 14 gauge lock channels DE Series (standard on 14 gauge door)	\$166.00
1-3/8" Thick door - DE Series (See Engineering for details)	\$166.00
Door viewer	\$32.00
Mail slot	\$91.00
Automatic door bottom (mortise type)	\$239.00
Conduit/raceway - includes wire pull	\$202.00

INACTIVE LEAF PREPARATIONS

Flush bolt embossed top/bottom channel	No charge
Cylindrical (2-3/4") or mortise (3-1/2") dead lock strike	\$65.00
Electric strike (no conduit)	\$143.00
ASA Strike only	\$63.00
Attaching astragal (includes astragal)	\$116.00
Flush bolt prep (ANSI 115.4)	\$101.00
Surface bolt reinforce only	\$38.00
Open back strike	\$171.00

SPECIAL FINISH PREPARATIONS

Second coat of primer	\$132.00
Finish paint setup charge (never waived)	\$1,433.00
Finish paint	\$360.00
▪ Minimum quantity of 20 per color	
▪ Price includes full carton wrap	

GLASS KIT OPTIONS

	Vision/ Narrow Lite up to 100 inch ²	Half Glass over 100 inch ² up to 800 inch ²	Full Glass over 800 inch ²
Cutout with kit installed	\$245	\$290	N/A
Cutout with kit and reinf.	\$332	\$377	\$421
Sunburst kit (1/2" glass included)	\$594	N/A	N/A
Muntin bar (each)	\$160	\$160	\$160
Galvanized kit add	\$131	\$131	\$131
Glass pocket add (other than 1/4")	\$221	\$221	\$221

Prices are based on Republic standard lite kit. (No glass unless noted otherwise.)

CUTOUT ONLY OPTIONS

	Up to 100 inch ²	Over 100 inch ² up to 800 inch ²	Over 800 inch ²
Panel in place	\$91	\$91	N/A
Cutout only	\$91	\$91	N/A
Cutout with reinforcement	\$181	\$181	\$181
Round cutout only (no reinf)	\$345	\$345	N/A

LOUVER OPTIONS

Description	Size	Price
Louver installed no reinf	12" x 12"	\$424.00
Louver installed no reinf	18" x 12"	\$481.00
Louver installed no reinf	24" x 12"	\$568.00
Louver installed no reinf	24" x 18"	\$640.00
Louver installed no reinf	24" x 24"	\$779.00
Louver installed no reinf	24" x 60"	\$1,617.00
Galvanized louver add	-	\$58.00
Fusible link louver add	-	\$426.00

Prices are based on Republic standard louver.


See [Engineering Section](#) for further options and/or details.

STEEL STIFFENED

DL/DE Series


Refer to technical data sheet on page 11

- Door Thickness: 1-3/4" (14 gauge = 1-13/16")
- Actual Door Size: Door undersized from nominal by 1/4" in width and 7/8" in height. Standard undercut is 3/4".
- Core: Fiberglass batting between each stiffener
 - "U" Factor = 0.61
 - "R" Factor = 1.65
 - (Optional) Polystyrene or polyurethane between stiffeners
- Hinge Rail and Reinforcement: Hinge edge is non-beveled and reinforced with a continuous 16 gauge steel channel projection welded at a maximum of 5" on center. (Optional 10 gauge)
- Lock Rail: Lock edge is non-beveled and reinforced with a continuous 16 gauge steel channel projection welded at a maximum of 5" on center. (Optional 14 gauge) (Beveled 1/8" in 2" optional)




- Top Channel: Top channel is a flush 16 gauge steel channel, projection welded at a maximum of 2-1/2" on center
- Bottom Channel: Bottom channel is an inverted 16 gauge steel channel, projection welded at a maximum of 2-1/2" on center
- Face Skins: 18 gauge, 16 gauge, or 14 gauge (cold rolled steel or A60 galvannealed)
 - * G90 Galvanized available in 16 or 14 gauge only
- Stiffener Gauge: 20 gauge (Optional 18 or 16 gauge)
- Stiffener Spacing: 6" maximum apart (Varies according to door width)
- Stiffener Welding: 5" maximum on center (Vertically)
- Closer Reinforcement: 14 gauge 18" x 6" (Optional 12 gauge)

- Size Availability
 - Max. 4'10" x 10'0" (Singles)
 - Max. 9'8" x 10'0" (Pairs)
 - (max. 18 ga – 4'0" x 8'0")
- SDI 100 - Grade/Model: Levels 2-4 and Models 1 and 2 (Maximum Duty Performance level A)
- Label Range: 20 minute through 3 hour/ Underwriters Laboratory or ITS/Warnock Hersey (Not available in urethane)
- Edge Seam Construction: Visible seam (standard), continuously welded seamless or intermittently welded seamless available
- Universal Standard/Heavy Weight Hinge: Hinge fillers are used allowing for easy modification from standard to heavy weight hinge prep
- Handing Design: Non-handed standard (Optional handed)




Flush Top




Door Hinge Prep



Paired doors without astragal



Cylindrical Lock Prep




Steel Stiffened Core




Paired doors with flat bar astragal




Paired doors with "Z" astragal



Mortise Lock Prep




Inverted Bottom Channel





SDI CLASSIFICATIONS

Grade		Model	Construction	Republic Series
II	Physical Performance Level B 1-3/4" (44) Only Heavy Duty Minimum Gauge = 18	1	Full Flush	DL 418, DE 418
		2	Seamless	DL 418, DE 418
III	Physical Performance Level A 1-3/4" (44) Only Extra-Heavy Duty Minimum Gauge = 16	1	Full Flush	DL 416, DE 416
		2	Seamless	DL 416, DE 416
IV	Physical Performance Level A 1-3/4" (44) Only Extra-Heavy Duty Minimum Gauge = 14	1	Full Flush	DE 414
		2	Seamless	DE 414



Universal Lock
Prep "DT"

STEEL STIFFENED DOOR 1-3/4" THICK

Width	Height	20 GA	18 GA	16 GA	14 GA
1'6" – 2'8"	6'8"	N/A	\$1,223	\$1,418	\$1,901
	7'0"	N/A	\$1,269	\$1,468	\$1,981
	7'2"	N/A	\$1,332	\$1,501	\$2,004
	8'0"	N/A	\$1,653	\$1,840	\$2,360
	9'0"	N/A	\$2,055	\$2,311	\$2,862
	10'0"	N/A	\$2,170	\$2,450	\$2,943
Over 2'8" – 3'0"	6'8"	N/A	\$1,236	\$1,490	\$1,909
	7'0"	N/A	\$1,279	\$1,505	\$1,989
	7'2"	N/A	\$1,367	\$1,558	\$2,017
	8'0"	N/A	\$1,653	\$1,840	\$2,360
	9'0"	N/A	\$2,055	\$2,311	\$2,862
	10'0"	N/A	\$2,170	\$2,450	\$2,943
Over 3'0" – 3'6"	6'8"	N/A	\$1,451	\$1,645	\$2,083
	7'0"	N/A	\$1,497	\$1,693	\$2,155
	7'2"	N/A	\$1,526	\$1,710	\$2,232
	8'0"	N/A	\$1,818	\$2,030	\$2,504
	9'0"	N/A	\$2,212	\$2,492	\$3,016
	10'0"	N/A	\$2,381	\$2,500	\$3,214
Over 3'6" – 4'0"	6'8"	N/A	\$1,582	\$1,735	\$2,206
	7'0"	N/A	\$1,603	\$1,772	\$2,269
	7'2"	N/A	\$1,607	\$1,835	\$2,359
	8'0"	N/A	\$1,972	\$2,129	\$2,634
	9'0"	N/A	\$2,251	\$2,588	\$3,153
	10'0"	N/A	\$2,445	\$2,610	\$3,421
Over 4'0" – 4'10"	6'8"	N/A	N/A	\$4,449	\$5,618
	7'0"	N/A	N/A	\$4,679	\$5,733
	7'2"	N/A	N/A	\$4,785	\$5,877
	8'0"	N/A	N/A	\$4,973	\$6,091
	9'0"	N/A	N/A	\$5,188	\$6,304
	10'0"	N/A	N/A	\$5,283	\$6,400

14/16 Gauge doors over 4'0 available in Galv only.

CORES

20 Gauge stiffeners	Included
18 Gauge stiffeners	\$398.00
16 Gauge stiffeners	\$558.00
Polystyrene between stiffeners	\$41.00
Polyurethane between stiffeners (N/A as fire rated)	\$398.00

STEEL TYPES

Cold rolled steel	Included
A60 Galvanized steel	\$111.00
G90 Galvanized steel (available in 14 and 16 gauge only); N/A in 14 gauge doors over 4'0" wide)	\$445.00

HINGE PREPARATIONS

Special hinge locations	No charge
4-1/2" or 5" Universal hinge prep	No charge
Additional hinge prep (per hinge)	\$27.00
Electric hinge	\$27.00
▪ Cutout in one hinge reinf. ▪ No wiring included, no conduit	
Surface mounted hinges (reinforced only)	\$121.00
Continuous hinge reinforcement	\$94.00
Special backset (per hinge)	\$139.00
Power transfer (no conduit)	\$145.00

CLOSER PREPARATIONS

Closer reinforcement	\$40.00
Concealed overhead door closer, holder or stop	\$394.00
Allegion Concealed overhead door closer, holder or stop	\$343.00

LOCK PREPARATIONS	
Special lock location	No charge
Special lock backset up to 5"	No charge
Sectional trim prep (mortise lock with function holes)	No charge
Cylindrical dead lock	\$65.00
Mortise dead lock	\$65.00
Rim reinforcement only	\$54.00
Rim reinforcement with function prep	\$60.00
Mortise exit device reinforcement only	\$39.00
Mortise exit device reinforcement with function prep	\$95.00
Allegion Mortise exit device reinforcement with function prep	\$76.00
Surface vertical rod reinforcement only	\$87.00
Surface vertical rod reinforcement with function prep	\$105.00
Allegion Surface vertical rod reinforcement with function prep	\$93.00
Concealed vertical rod	
▪ Frame mortise strike (per prep)	\$648.00
▪ Door per template	
Allegion Concealed vertical rod	\$515.00
▪ Frame mortise strike (per prep)	
▪ Door per template	
Exit alarm reinforcement only	\$66.00
Inset exit device (14 and 16 gauge doors only)	\$505.00
Push pull reinforcement	\$42.00

LABEL PREPARATIONS	
Mark numbers	No charge
U.L. Mylar label (standard unless specified otherwise)	\$22.00
U.L. Metal label	\$51.00
ITS/Warnock Hersey Metal label	\$51.00
Hurricane label (See Engineering for details)	\$22.00

Polyurethane unavailable as fire rated.

SPECIAL CONSTRUCTIONS	
Undercut - under 3/8" price next larger size	No charge
Inverted top channel	No charge
Flush bottom channel	No charge
Dutch door (4) 4.5" hinge preps x (1) 161 lock prep	\$353.00
Unifit hinge channel	\$95.00
Seal top or bottom channel and finish smooth each	\$150.00
Mag switch/DPS - Hole only	\$25.00
Mag switch/DPS - Prep and reinf.	\$131.00
Bondo filled edge	\$128.00
Continuous welded edge (N/A in 20 gauge)	\$192.00
Beveled lock edge (1/8" in 2") N/A in 14 gauge	\$23.00
10 Gauge hinge and 14 gauge lock channels DE Series (standard on 14 gauge door)	\$166.00
1-3/8" Thick door DE (See Engineering for details)	\$166.00
Door viewer	\$32.00
Mail slot	\$91.00
Automatic door bottom (mortise type)	\$239.00
Conduit/raceway - includes wire pull	\$202.00

See [Engineering Section](#) for further options and/or details.

INACTIVE LEAF PREPARATIONS	
Flush bolt embossed top/bottom channel	No charge
Cylindrical (2-3/4") or mortise (3-1/2") dead lock strike	\$65.00
Electric strike (no conduit)	\$143.00
ASA Strike only	\$63.00
Attaching astragal (includes astragal)	\$116.00
Flush bolt prep (ANSI 115.4)	\$101.00
Surface bolt reinforce only	\$38.00
Open back strike	\$171.00

SPECIAL FINISH PREPARATIONS	
Second coat of primer	\$132.00
Finish paint setup charge (never waived)	\$1,433.00
Finish paint	\$360.00
▪ Minimum quantity of 20 per color	
▪ Price includes full carton wrap	

GLASS KIT OPTIONS			
	Vision/ Narrow Lite up to 100 inch ²	Half Glass over 100 inch ² up to 800 inch ²	Over 800 inch ²
Cutout with kit installed	\$245	\$290	N/A
Cutout with kit and reinf.	\$332	\$377	\$421
Sunburst kit (1/2" glass included)	\$594	N/A	N/A
Muntin bar (each)	\$160	\$160	\$160
Galvanized kit add	\$131	\$131	\$131
Glass pocket add (other than 1/4")	\$221	\$221	\$221

1. Prices are based on Republic standard lite kit. (No glass unless noted otherwise.)

2. Full glass cutout and kits not available in stiffened.

CUTOUT ONLY OPTIONS (GLASS KITS & LOUVERS)			
	Up to 100 inch ²	Over 100 inch ² up to 800 inch ²	Over 800 inch ²
Panel in place	N/A	N/A	N/A
Cutout only	N/A	N/A	N/A
Cutout with reinforcement	\$181	\$181	\$181
Round cutout only (no reinf)	N/A	N/A	N/A

LOUVER OPTIONS		
Description	Size	Price
Louver installed no reinf	12" x 12"	\$424.00
Louver installed no reinf	18" x 12"	\$481.00
Louver installed no reinf	24" x 12"	\$568.00
Louver installed no reinf	24" x 18"	\$640.00
Louver installed no reinf	24" x 24"	\$779.00
Louver installed no reinf	24" x 60"	\$1,617.00
Galvanized louver add	-	\$58.00
Fusible link louver add	-	\$426.00

Prices are based on Republic standard louver.

EMBORESSED

DL/DE Series


Refer to technical data sheet on page 11

- Door Thickness: 1-3/4" (1-3/8" available in 6-Panel only)
- Actual Door Size: Door undersized from nominal by 1/4" in width and 7/8" in height. Standard undercut is 3/4".
- Core: 1 to 1.25 lb. density Polystyrene (standard)
- Hinge Rail and Reinforcement: Hinge edge is non-beveled and reinforced with a continuous 16 gauge steel channel (Optional 10 gauge - DE Series) projection welded at a maximum of 5" on center
 - Additional reinforcement plates are provided at the hinge locations to give a total of 3/16" reinforcement (Backset 1/4")
- Lock Rail: Lock edge is non-beveled and reinforced with a continuous 16 gauge steel channel projection welded at a maximum of 5" on center (Optional - Beveled 1/8" in 2")
- 16 gauge reinforcements for mortise or cylindrical locks are of an integral type in accordance with ANSI A115 standards


- Top Channel: Top channel is a flush 16 gauge steel channel, projection welded at a maximum of 2-1/2" on center
- Bottom Channel: Bottom channel is an inverted 16 gauge steel channel, projection welded at a maximum of 2-1/2" on center
- Face Skins: 18 or 16 - Faces shall be deep drawn embossed raised panels, both inside and out (16 gauge only available in 6-panel)
- Closer Reinforcement: 14 gauge 18" x 6" (Optional 12 gauge)
- Size Availability
 - Minimum 2'8" x 6'8"
 - Maximum 3'2" x 8'0"
 - (Optional - 3'0" x 8'0", 6-Panel design with elongated panel embossments)
- SDI 100 - Grade/Model: Levels 1-3 and Models 1 and 2 (Maximum Duty Performance level A)
- Label Range: 20 minute through 3 hour/ Underwriters Laboratory or ITS/Warnock Hersey



Intertek



SDI CLASSIFICATIONS			
Grade	Model	Construction	Republic Series
II	1	Full Flush (Not applicable)	DL 418, DE418
	2	Seamless	DL 418, DE418
III	1	Full Flush (Not applicable)	DL 416, DE 416
	2	Seamless	DL 416, DE 416



Standard 6-Panel Embossment



High Def Embossment (1 and 2 Panel only)


Embossed patterns and sizes


P1 - One Panel				
	Width	Height	18 GA	16 GA
	Over 2'8"-3'0"	6'8"	\$1,345	N/A
		7'0"	\$1,345	N/A
		8'0"	\$1,611	N/A
	Over 3'0"-3'2"	6'8"	\$1,492	N/A
		7'0"	\$1,533	N/A
		8'0"	\$1,838	N/A

P2 - Two Panel				
	Width	Height	18 GA	16 GA
	2'8"	6'8"	\$1,381	N/A
		7'0"	\$1,445	N/A
		8'0"	\$1,600	N/A
	Over 2'8"-3'0"	6'8"	\$1,418	N/A
		7'0"	\$1,485	N/A
		8'0"	\$1,600	N/A
	Over 3'0"-3'2"	6'8"	\$1,578	N/A
		7'0"	\$1,598	N/A
		8'0"	\$1,829	N/A

AP2 - Arch Two Panel				
	Width	Height	18 GA	16 GA
	2'8"	6'8"	\$1,443	N/A
		7'0"	\$1,495	N/A
	Over 2'8"-3'0"	6'8"	\$1,479	N/A
		7'0"	\$1,524	N/A
	Over 3'0"-3'2"	6'8"	\$1,629	N/A
		7'0"	\$1,655	N/A

P4 - Four Panel				
	Width	Height	18 GA	16 GA
	2'8"	6'8"	\$1,374	N/A
		7'0"	\$1,374	N/A
		8'0"	\$1,611	N/A
	Over 2'8"-3'0"	6'8"	\$1,345	N/A
		7'0"	\$1,345	N/A
		8'0"	\$1,611	N/A
	Over 3'0"-3'2"	6'8"	\$1,492	N/A
		7'0"	\$1,533	N/A

PB4 - Four Panel				
	Width	Height	18 GA	16 GA
	2'8"	6'8"	\$1,374	N/A
		7'0"	\$1,374	N/A
	Over 2'8"-3'0"	6'8"	\$1,345	N/A
		7'0"	\$1,345	N/A
	Over 3'0"-3'2"	6'8"	\$1,492	N/A
		7'0"	\$1,533	N/A

6-Panel				
	Width	Height	18 GA	16 GA
	2'8"	6'8"	\$1,303	\$1,527
		7'0"	\$1,380	\$1,517
	Over 2'8"-3'0"	6'8"	\$1,303	\$1,527
		7'0"	\$1,380	\$1,517
	Over 3'0"-3'2"	6'8"	\$1,498	N/A
		7'0"	\$1,555	N/A

8-0 x 6-Panel				
	Width	Height	18 GA	16 GA
	2'8"	8'0"	\$1,677	\$1,975
	Over 2'8"-3'0"	8'0"	\$1,677	\$1,975

1. For patterns, sizes or gauges not shown above please contact Customer Care for availability and options. Minimum buys may be required.
2. See Glass Kit Options section for options and price adders to above styles which do not include pricing for cutout/glass/kits as standard.
3. 6-Panel available STC 40 with Temp rise 250 core (see STC Eco).
4. 6-Panel cutout option: Limited to a 24-1/2" x 38-1/2" cutout with reinforcement.

CLOSER PREPARATIONS	
Closer reinforcement	\$40.00
Concealed overhead door closer, holder or stop	\$394.00
Allegion Concealed overhead door closer, holder or stop	\$343.00

SPECIAL CONSTRUCTIONS	
Undercut - under 3/8" price as next larger size	No charge
Inverted top channel	No charge
Flush bottom channel	No charge
Dutch door	\$353.00
Unifit hinge channel	\$95.00
Seal top or bottom channel and finish smooth each	\$150.00
Mag switch/DPS - Hole only	\$25.00
Mag switch/DPS - Prep and reinf.	\$131.00
Bondo filled edge	\$128.00
Continuous welded edge (N/A in 20 gauge)	\$192.00
Beveled lock edge (1/8" in 2")	\$23.00
10 Gauge hinge and 14 gauge lock channels (DE Series - standard on 14 gauge door)	\$166.00
1-3/8" Thick door (6 Panel only) DE (See Engineering)	\$166.00
Door viewer	\$32.00
Mail slot	\$91.00
Automatic door bottom (mortise type)	\$239.00
Conduit/raceway - includes wire pull	\$202.00

INACTIVE LEAF PREPARATIONS	
Flush bolt embossed top/bottom channel	No charge
Cylindrical (2-3/4") or mortise (3-1/2") dead lock strike	\$65.00
Electric strike (no conduit)	\$143.00
ASA Strike only	\$63.00
Attaching astragal (includes astragal)	\$116.00
Flush bolt prep (ANSI 115.4)	\$101.00
Surface bolt reinforce only	\$38.00
Open back strike	\$171.00

LABEL PREPARATIONS	
Mark numbers	No charge
U.L. Mylar label (standard unless specified otherwise)	\$22.00
U.L. Metal label	\$51.00
Warnock Hersey Metal Label	\$51.00
Hurricane label (See Engineering Section)	\$22.00

LOCK PREPARATIONS	
Special lock location	No charge
Special lock backset up to 5"	No charge
Sectional trim prep (mortise lock with function holes)	No charge
Cylindrical dead lock	\$65.00
Mortise dead lock	\$65.00
Rim reinforcement only	\$54.00
Rim reinforcement with function prep	\$60.00
Mortise exit device reinforcement only	\$39.00
Mortise exit device reinforcement with function prep	\$95.00
Allegion Mortise exit device reinforcement with function prep	\$76.00
Concealed vertical rod	\$648.00
Allegion Concealed vertical rod	\$515.00
▪ Frame mortise strike (per prep)	
▪ Door per template	
Surface vertical rod reinforcement only	\$87.00
Surface vertical rod reinforcement with function prep	\$105.00
Allegion Surface vertical rod reinforcement with function prep	\$93.00
Exit alarm reinforcement only	\$66.00
Inset exit device (16 gauge doors only)	Consult Factory
Push pull reinforcement	\$42.00

SPECIAL FINISH PREPARATIONS	
Second coat of primer	\$132.00
Finish paint setup charge (never waived)	\$1,433.00
Finish paint ▪ Minimum quantity of 20 per color ▪ Price includes full carton wrap	\$360.00

	Vision/ Narrow Lite up to 100 inch ²	Half Glass over 100 inch ² up to 800 inch ²	Full Glass over 800 inch ²
Cutout with kit installed	N/A	N/A	N/A
Cutout with kit and reinf.	\$332	\$377	\$421
Sunburst kit (1/2" glass included)	\$594	N/A	N/A
Muntin bar (each)	\$160	\$160	\$160
Galvanized kit add	\$131	\$131	\$131
Glass pocket add (other than 1/4")	\$221	\$221	\$221

Prices are based on Republic standard lite kit. (No glass unless noted otherwise.)

See [Engineering Section](#) for further options and/or details.

CUTOUT ONLY OPTIONS (GLASS KITS & LOUVERS)			
	Up to 100 inch ²	Over 100 inch ² up to 800 inch ²	Over 800 inch ²
Panel in place	N/A	N/A	N/A
Cutout only	N/A	N/A	N/A
Cutout with reinforcement	\$181	\$181	N/A
Round cutout only (no reinf)	N/A	N/A	N/A

STEEL TYPE	
Cold rolled steel	N/A
A40 Galvanized Steel	Included

See [Engineering Section](#) for further options and/or details.

HINGE PREPARATIONS	
Special hinge locations	No charge
4-1/2" or 5" Universal hinge prep	No charge
Additional hinge prep (per hinge)	\$27.00
Electric hinge	\$27.00
▪ Cutout in one hinge reinf.	
▪ No wiring included, no conduit	
Surface mounted hinges (reinforced only)	\$121.00
Continuous hinge reinforcement	\$94.00
Special backset (per hinge)	\$139.00
Power transfer (no conduit)	\$145.00

DP SERIES

HONEYCOMB

INSULATED

STEEL STIFFENED

EMBOSSED

this page intentionally blank



ME SERIES

Universal frames


Refer to technical data sheet on page 12 and 13

- Thickness: Made for two basic door thicknesses, 1-3/8" or 1-3/4" (Consult factory for optional thicknesses)
- Gauges: 16 or 14 (12 gauge available with coped corner connections for welding)
- Faces: 1" to 4"
- Standard Rabbets
 - 1-3/8" (actual dimension 1-9/16")
 - 1-3/4" (actual dimension 1-15/16")
 - Rabbet dimension is 3/16" greater than the door thickness
- Stop: 5/8" standard
- Closer Reinforcement (Optional): 1-3/8" x 14" x 14 gauge plate
- Size Availability
 - Maximum Size 5'0" x 10'0" Single
 - Maximum Size 10'0" x 10'0" Double
- Label Range: Maximum fire rating 180 minute
- Hinge Backset: 5/16"
- Backbend: 7/16" (Single Return)


- Universal Standard/Heavy Weight Hinge
 - Frames for 1-3/4" doors shall have a 7 gauge steel hinge reinforcement plate, projection welded with provisions for 4-1/2" x 4-1/2" template hinges. Hinge plate is designed to be modified to accept a heavy weight hinge by removing spacer plate.
 - Frames for 1-3/8" doors shall have a 11 gauge steel hinge reinforcement plate, projection welded with provisions for 3-1/2" x 3-1/2" standard weight template hinges
- Strike Prep
 - Frames for 1-3/4" doors shall have a 14 gauge steel strike reinforcement plate, extruded and formed to the equivalent of 10 gauge, projection welded with provisions for Universal ANSI A115.1 or ANSI A115.2 strike (4-7/8")
 - Frames for 1-3/8" doors shall have a 14 gauge steel strike reinforcement plate, extruded and formed to the equivalent of 10 gauge projection welded with provision for Universal ANSI A115.3 strike (2-3/4")
- Anchors: Sill anchors are included with all ME frames. All other anchors must be ordered separately.
- Silencer Prep: 9/32" dia. holes shall be provided as standard on strike jambs and double headers, (3 per strike jamb and 2 per double head). Mutes are not supplied and must be ordered separately.
- Double Heads: Double heads are undersized 1/16" (except for cased open heads, which are nominal)
- Mortar Guards: Mortar guards of 26 gauge steel shall be welded to each hinge and strike reinforcement plate
- Profiles: Equal Rabbet, Unequal Rabbet, Single Rabbet, Double Egress, Cased Opening and Kerf (Special profiles available, consult factory)
- Handing: Frames are handed




Corner Connection




Frame Strike Prep




Face Welded





Full Profile Weld




Frame Hinge Prep





Standard Sill Anchor

Prepared
Opening Anchor
(Bolt sold separately)

Masonry Wire Anchor



"Z" Anchor

Snap In
Universal Anchor
(stock depths only)Masonry "T" Anchor
(stock depths only)

SPECIAL CONSTRUCTIONS

Description	List add
Special width (use next larger size)	No charge
Special height (use next larger size)	No charge
Communicating (6) 4.5" hinge preps x (2) ASA preps	\$88.00
Dutch prep (4) 4.5" hinge preps x ASA prep	\$91.00
Cap top or bottom of jamb (each)	\$147.00
Mag switch/DPS - Hole only	\$25.00
Mag switch/DPS - Prep and reinf. (no junction box)	\$97.00
Hospital stop (galv) up to 6"	\$238.00
8" Junction box welded in	\$34.00
14" Junction box welded in	\$34.00
10" Junction box welded in soffit	\$34.00

LABEL PREPARATIONS

Description	List add
Mark numbers	No charge
U.L. Mylar label (standard unless specified otherwise)	\$24.00
U.L. Metal label	\$31.00
ITS/Warnock Hersey Metal label	\$31.00
FBC/Florida building code (See Engineering for details)	\$24.00

SPECIAL FINISH PREPARATIONS

Description	List add
Second coat of primer	\$123.00
Finish paint setup charge frame (never waived)	\$1,433.00
Finish paint ▪ Minimum quantity of 20 frames per color ▪ Price includes full carton wrap	\$360.00

Finish paint unavailable on welded frames.

ANCHOR OPTIONS

Description	List add
Welded in prepared opening anchor (per anchor)	\$17.00
Welded in anchor (per anchor)	\$7.50
Punch and dimple only (per prep)	\$6.00

Prepared Opening Frames up 7'1" require 8 anchors (max 8-3/4" depth). Over 7'2" thru 10'0" require 10 (max 8-3/4" depth). Frames over 8-3/4" receive double the quantity and price.

FRAME CONSTRUCTION

Description	List add
Unit bundle (3pc)	\$7.00
Standard face weld (3pc)	\$121.00
Full profile weld (3pc)	\$220.00

FRAME PROFILE OPTIONS

Description	List add
No returns	No charge
Cased open	No charge
Single rabbet	No charge
4" Face heads (through 4'0")	\$64.00
4" Face heads (over 4'0")	\$89.00
Non-standard face - per frame (1" to 3-7/8" uniform)	\$79.00
Non-standard rabbet (per frame)	\$261.00
Kerf (includes weather-stripping) (16 gauge only)	\$194.00
Non-standard returns (uniform)	\$79.00

UNIVERSAL FRAMES 7/16" SINGLE RETURN													
Single		16 Gauge						14 Gauge					
Width	Height	4-5/8" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"	4-5/8" thru 5-7/8"	5-7/8" thru 7-3/4"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"
Thru 3'0"	6'8"	\$286	\$324	\$382	\$439	\$521	\$722	\$360	\$400	\$446	\$501	\$592	\$793
	7'0"	\$297	\$342	\$393	\$455	\$537	\$738	\$370	\$419	\$458	\$517	\$609	\$810
	7'2"	\$313	\$358	\$416	\$480	\$564	\$765	\$394	\$440	\$480	\$537	\$635	\$836
	8'0"	\$369	\$398	\$460	\$530	\$619	\$820	\$454	\$493	\$532	\$594	\$695	\$896
	9'0"	\$411	\$456	\$509	\$590	\$688	\$889	\$506	\$559	\$598	\$664	\$774	\$975
	10'0"	\$467	\$515	\$581	\$663	\$767	\$968	\$572	\$623	\$669	\$747	\$862	\$1,063
Over 3'0" to 4'0"	6'8"	\$302	\$341	\$399	\$457	\$537	\$738	\$372	\$415	\$459	\$518	\$603	\$804
	7'0"	\$313	\$359	\$410	\$473	\$553	\$754	\$382	\$434	\$471	\$534	\$620	\$821
	7'2"	\$329	\$375	\$433	\$498	\$580	\$781	\$406	\$455	\$493	\$554	\$646	\$847
	8'0"	\$385	\$415	\$477	\$548	\$635	\$836	\$466	\$508	\$545	\$611	\$706	\$907
	9'0"	\$427	\$473	\$526	\$608	\$704	\$905	\$518	\$574	\$611	\$681	\$785	\$986
	10'0"	\$483	\$532	\$598	\$681	\$783	\$984	\$584	\$638	\$682	\$764	\$873	\$1,074
Over 4'0" to 5'0"	6'8"	\$333	\$370	\$430	\$491	\$571	\$772	\$408	\$454	\$497	\$559	\$641	\$842
	7'0"	\$344	\$388	\$441	\$507	\$587	\$788	\$418	\$473	\$509	\$575	\$658	\$859
	7'2"	\$360	\$404	\$464	\$532	\$614	\$815	\$442	\$494	\$531	\$595	\$684	\$885
	8'0"	\$416	\$444	\$508	\$582	\$669	\$870	\$502	\$547	\$583	\$652	\$744	\$945
	9'0"	\$458	\$502	\$557	\$642	\$738	\$939	\$554	\$613	\$649	\$722	\$823	\$1,024
	10'0"	\$514	\$561	\$629	\$715	\$817	\$1,018	\$620	\$677	\$720	\$805	\$911	\$1,112

Frames are priced as equal or unequal rabbet. Frames 3" to 4-1/2" jamb depth must be single rabbet (minimum 1" soffit).

UNIVERSAL FRAMES 7/16" SINGLE RETURN													
Double		16 Gauge						14 Gauge					
Width	Height	4-5/8" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"	4-5/8" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"
Over 4'0" to 5'0"	6'8"	\$347	\$384	\$449	\$512	\$592	\$793	\$422	\$469	\$516	\$582	\$663	\$864
	7'0"	\$355	\$400	\$461	\$524	\$606	\$807	\$434	\$485	\$530	\$590	\$673	\$874
	7'2"	\$373	\$426	\$485	\$550	\$640	\$841	\$456	\$511	\$556	\$612	\$709	\$910
	8'0"	\$445	\$472	\$535	\$610	\$704	\$905	\$530	\$573	\$614	\$682	\$783	\$984
	9'0"	\$491	\$536	\$589	\$674	\$772	\$973	\$588	\$641	\$680	\$754	\$857	\$1,058
	10'0"	\$549	\$598	\$673	\$756	\$868	\$1,069	\$660	\$719	\$770	\$848	\$959	\$1,160
Over 5'0" to 6'0"	6'8"	\$357	\$397	\$466	\$528	\$610	\$811	\$437	\$484	\$531	\$592	\$681	\$882
	7'0"	\$365	\$413	\$478	\$540	\$624	\$825	\$449	\$500	\$545	\$600	\$691	\$892
	7'2"	\$383	\$439	\$502	\$566	\$658	\$859	\$471	\$526	\$571	\$622	\$727	\$928
	8'0"	\$455	\$485	\$552	\$626	\$722	\$923	\$545	\$588	\$629	\$692	\$801	\$1,002
	9'0"	\$501	\$549	\$606	\$690	\$790	\$991	\$603	\$656	\$695	\$764	\$875	\$1,076
	10'0"	\$559	\$611	\$690	\$772	\$886	\$1,087	\$675	\$734	\$785	\$858	\$977	\$1,178
Over 6'0" to 8'0"	6'8"	\$381	\$424	\$499	\$561	\$646	\$847	\$465	\$514	\$567	\$633	\$721	\$922
	7'0"	\$389	\$440	\$511	\$573	\$660	\$861	\$477	\$530	\$581	\$641	\$731	\$932
	7'2"	\$407	\$466	\$535	\$599	\$694	\$895	\$499	\$556	\$607	\$663	\$767	\$968
	8'0"	\$479	\$512	\$585	\$659	\$758	\$959	\$573	\$618	\$665	\$733	\$841	\$1,042
	9'0"	\$525	\$576	\$639	\$723	\$826	\$1,027	\$631	\$686	\$731	\$805	\$915	\$1,116
	10'0"	\$583	\$638	\$723	\$805	\$922	\$1,123	\$703	\$764	\$821	\$899	\$1,017	\$1,218
Over 8'0" to 10'0"	6'8"	\$420	\$466	\$552	\$623	\$708	\$909	\$513	\$572	\$634	\$704	\$796	\$997
	7'0"	\$428	\$482	\$564	\$635	\$722	\$923	\$525	\$588	\$648	\$712	\$806	\$1,007
	7'2"	\$446	\$508	\$588	\$661	\$756	\$957	\$547	\$614	\$674	\$734	\$842	\$1,043
	8'0"	\$518	\$554	\$638	\$721	\$820	\$1,021	\$621	\$676	\$732	\$804	\$916	\$1,117
	9'0"	\$564	\$618	\$692	\$785	\$888	\$1,089	\$679	\$744	\$798	\$876	\$990	\$1,191
	10'0"	\$622	\$680	\$776	\$867	\$984	\$1,185	\$751	\$822	\$888	\$970	\$1,092	\$1,293

Frames are priced as equal or unequal rabbet. Frames 3" to 4-1/2" jamb depth must be single rabbet (minimum 1" soffit).

COMPONENTS UNIVERSAL FRAMES 7/16" SINGLE RETURN													
Header		16 Gauge							14 Gauge				
	Width	4-5/8" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"	4-5/8" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"
SGL Head	Thru 3'0"	\$56	\$66	\$79	\$96	\$122	\$189	\$76	\$85	\$103	\$118	\$148	\$215
	Over 3'0" - 4'0"	\$72	\$83	\$96	\$114	\$138	\$205	\$88	\$100	\$116	\$135	\$159	\$226
	Over 4'0" - 5'0"	\$103	\$112	\$127	\$148	\$172	\$239	\$124	\$139	\$154	\$176	\$197	\$264
DBL Head	Over 5'0" - 6'0"	\$113	\$125	\$144	\$164	\$190	\$257	\$139	\$154	\$169	\$186	\$215	\$282
	Over 6'0" - 8'0"	\$137	\$152	\$177	\$197	\$226	\$293	\$167	\$184	\$205	\$227	\$255	\$322
	Over 8'0" - 10'0"	\$176	\$194	\$230	\$259	\$288	\$355	\$215	\$242	\$272	\$298	\$330	\$397

COMPONENTS UNIVERSAL FRAMES 7/16" SINGLE RETURN													
Jamb Pair		16 Gauge						14 Gauge					
	Height	4-5/8" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"	4-5/8" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"
SGL Pair	6'8"	\$230	\$258	\$303	\$343	\$399	\$533	\$284	\$315	\$343	\$383	\$444	\$578
	7'0"	\$241	\$276	\$314	\$359	\$415	\$549	\$294	\$334	\$355	\$399	\$461	\$595
	7'2"	\$257	\$292	\$337	\$384	\$442	\$576	\$318	\$355	\$377	\$419	\$487	\$621
	8'0"	\$313	\$332	\$381	\$434	\$497	\$631	\$378	\$408	\$429	\$476	\$547	\$681
	9'0"	\$355	\$390	\$430	\$494	\$566	\$700	\$430	\$474	\$495	\$546	\$626	\$760
	10'0"	\$411	\$449	\$502	\$567	\$645	\$779	\$496	\$538	\$566	\$629	\$714	\$848
DBL Pair	6'8"	\$244	\$272	\$322	\$364	\$420	\$554	\$298	\$330	\$362	\$406	\$466	\$600
	7'0"	\$252	\$288	\$334	\$376	\$434	\$568	\$310	\$346	\$376	\$414	\$476	\$610
	7'2"	\$270	\$314	\$358	\$402	\$468	\$602	\$332	\$372	\$402	\$436	\$512	\$646
	8'0"	\$342	\$260	\$408	\$462	\$532	\$666	\$406	\$434	\$460	\$506	\$586	\$720
	9'0"	\$388	\$424	\$462	\$526	\$600	\$734	\$464	\$502	\$526	\$578	\$660	\$794
	10'0"	\$446	\$486	\$546	\$608	\$696	\$830	\$536	\$580	\$616	\$672	\$762	\$896

STEEL TYPES	
Description	List add
Cold rolled steel	Included
A60 Galvanized steel	\$61.00
G90 Galvanized steel (available in 14 and 16 gauge only)	\$108.00
12 Gauge - See Stick Section	N/A

HINGE PREPARATIONS	
Description	List add
Special hinge locations	No charge
4-1/2" or 5" Universal hinge prep	No charge
Additional hinge prep (per hinge)	\$25.00
4" Template hinge prep (square corner only) (per hinge)	\$62.00
Electric hinge	\$25.00
▪ One 1/2" dia. hole in one hinge reinf.	
▪ No wiring included, no junction box	
Continuous hinge reinforcement (rabbet or face)	\$88.00
Power transfer (no junction box)	\$111.00

See [Engineering Section](#) for further options and/or details.

FRAME - STRIKE PREPARATIONS	
Description	List add
Special strike location	No charge
Standard strike at non standard location	No charge
Cylindrical dead lock (2-3/4" strike)	\$25.00
Mortise dead lock (3-1/2" strike)	\$25.00
Unit lock/double strike prep (ex. Schlage H)	N/A
Rim reinforcement only	\$33.00
Surface vertical rod reinforcement only	\$33.00
Concealed vertical rod (mortise strike) (per prep)	\$73.00
Exit alarm reinforcement only	\$33.00
Electric strike (no junction box)	\$107.00
Flush bolt strike prep/reversible or automatic	\$63.00
Surface bolt reinforce only	\$33.00

CLOSER PREPARATIONS	
Description	List add
Closer reinforcement - 14 GA Plate - RA or PA	\$33.00
Full depth reinforcement (price per foot)	\$35.00
Concealed overhead door closer, holder or stop	\$307.00
Allegion Concealed overhead door closer, holder or stop	\$278.00




MH SERIES

Drywall frames


Refer to technical data sheet on page 14

- Thickness: Made for two basic door thicknesses, 1-3/8" or 1-3/4" (Consult factory for optional thicknesses)
- Gauges: 16 or 14
- Faces: 1-1/4" to 4"
- Standard Rabbets
 - 1-3/8" (actual dimension 1-9/16")
 - 1-3/4" (actual dimension 1-15/16")
 - Rabbet dimension is 3/16" greater than the door thickness
- Stop: 5/8" standard
- Closer Reinforcement (Optional): 1-3/8" x 14" x 14 gauge plate
- Size Availability
 - Maximum Size 5'0" x 10'0" Single
 - Maximum Size 10'0" x 10'0" Double
- Label Range: Maximum fire rating 90 minute with compression anchors
- Hinge Backset: 5/16"
- Backbend: 1/2" (Double Return)



- Universal Standard/Heavy Weight Hinge
 - Frames for 1-3/4" doors shall have a 7 gauge steel hinge reinforcement plate, projection welded with provisions for 4-1/2" x 4-1/2" template hinges. Hinge plate is designed to be modified to accept a heavy weight hinge by removing spacer plate
 - Frames for 1-3/8" doors shall have a 11 gauge steel hinge reinforcement plate, projection welded with provisions for 3-1/2" x 3-1/2" standard weight template hinges
- Strike Prep
 - Frames for 1-3/4" doors shall have a 14 gauge steel strike reinforcement plate, extruded and formed to the equivalent of 10 gauge, projection welded with provisions for Universal ANSI A115.1 or ANSI A115.2 strike (4-7/8")
 - Frames for 1-3/8" doors shall have a 14 gauge steel strike reinforcement plate, extruded and formed to the equivalent of 10 gauge projection welded with provision for Universal ANSI A115.3 strike (2-3/4")
- Anchors: Welded in compression anchors with loose sill anchors and hole plugs (Ordered separately)
- Silencer Prep: 9/32" dia. holes shall be provided as standard on strike jambs and double headers, (3 per strike jamb and 2 per double head). Mutes are not supplied and must be ordered separately.
- Double Heads: Double heads are undersized 1/16" (except for cased open heads, which are nominal)
- Profiles: Equal Rabbet, Unequal Rabbet, Single Rabbet, Double Egress, Cased Opening and Kerf. (Special profiles available, consult factory)
- Handing: Frames are handed

MH
Corner Connection



Frame Strike Prep



Frame Hinge Prep

"Z" Anchor (Optional)
(welded in)

Compression Anchor

Drywall Sill Anchor
(Sold/Shipped Loose)L Strap Anchor
(Optional)


SPECIAL CONSTRUCTIONS

Description	List add
Special width (use next larger size)	No charge
Special height (use next larger size)	No charge
Communicating (6) 4.5" hinge preps x (2) ASA preps	\$88.00
Dutch prep (4) 4.5" hinge preps x ASA prep	\$91.00
Cap top or bottom of jamb (each)	\$147.00
Mag switch/DPS - Hole only	\$25.00
Mag switch/DPS - Prep and reinf. (no junction box)	\$97.00
Hospital stop (galv) up to 6"	\$238.00
8" Junction box welded in	N/A
14" Junction box welded in	N/A
10" Junction box welded in soffit	\$34.00

LABEL PREPARATIONS

Description	List add
Mark numbers	No charge
U.L. Mylar label (standard unless specified otherwise)	\$24.00
U.L. Metal label	\$31.00
ITS/Warnock Hersey Metal label	\$31.00

1. Maximum fire rating 1-1/2 hour with compression anchors.
2. Single rabbet min 3", max 4-3/8" depth.
3. Double rabbet min 4-1/2", max 15" depth.

SPECIAL FINISH PREPARATIONS

Description	List add
Second coat of primer	\$123.00
Finish paint setup charge (never waived)	\$1,433.00
Finish paint <ul style="list-style-type: none"> ▪ Minimum quantity of 20 frames per color ▪ Price includes full carton wrap 	\$360.00

Finish paint unavailable on welded frames.

ANCHOR OPTIONS

Description	Price adj.
Welded in anchor (per anchor)	\$7.50
Omit drywall compression anchor (deduct)	-\$6.00
Embossed hole at bottom face	No charge

Drywall frames standard with (1) each compression anchor per jamb.

FRAME CONSTRUCTION

Description	List add
Unit bundle (3pc)	\$7.00
Standard face weld (3pc) (omit compression anchor)	\$121.00
Full profile weld (3pc) (omit compression anchor)	\$220.00

FRAME PROFILE OPTIONS

Description	List add
No returns	No charge
Cased open	No charge
Single rabbet	No charge
4" Face heads (through 4'0")	\$64.00
4" Face heads (over 4'0")	\$89.00
Non-standard face - per frame (1" – 3-7/8" uniform)	\$79.00
Non-standard rabbet (per frame)	\$261.00
Kerf (includes weather-stripping) (16 gauge only)	\$194.00

FRAMES 1/2" DOUBLE RETURN X COMPRESSION ANCHORS													
Single		16 Gauge						14 Gauge					
Width	Height	4-1/2" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"	4-1/2" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"
Thru 3'0"	6'8"	\$320	\$372	\$411	\$463	\$548	\$749	\$409	\$470	\$506	\$573	\$679	\$880
	7'0"	\$344	\$390	\$426	\$480	\$570	\$771	\$434	\$487	\$526	\$592	\$696	\$897
	7'2"	\$361	\$408	\$445	\$503	\$598	\$799	\$442	\$505	\$543	\$607	\$726	\$927
	8'0"	\$406	\$458	\$494	\$552	\$652	\$853	\$503	\$551	\$597	\$653	\$760	\$961
	9'0"	\$461	\$526	\$561	\$620	\$732	\$933	\$562	\$625	\$672	\$744	\$863	\$1,064
	10'0"	\$539	\$594	\$646	\$794	\$995	\$658	\$715	\$769	\$817	\$931	\$1,132	
Over 3'0" – 4'0"	6'8"	\$335	\$390	\$423	\$479	\$559	\$760	\$419	\$484	\$515	\$595	\$688	\$889
	7'0"	\$359	\$408	\$438	\$496	\$581	\$782	\$444	\$501	\$535	\$614	\$705	\$906
	7'2"	\$376	\$426	\$457	\$519	\$609	\$810	\$452	\$519	\$552	\$629	\$735	\$936
	8'0"	\$421	\$476	\$506	\$568	\$663	\$864	\$513	\$565	\$606	\$675	\$769	\$970
	9'0"	\$476	\$544	\$573	\$636	\$743	\$944	\$572	\$639	\$681	\$766	\$872	\$1,073
	10'0"	\$554	\$612	\$658	\$713	\$805	\$1,006	\$668	\$729	\$778	\$839	\$940	\$1,141
Over 4'0" – 5'0"	6'8"	\$375	\$421	\$461	\$513	\$596	\$797	\$477	\$539	\$573	\$646	\$742	\$943
	7'0"	\$399	\$439	\$476	\$530	\$618	\$819	\$502	\$556	\$593	\$665	\$759	\$960
	7'2"	\$416	\$457	\$495	\$553	\$646	\$847	\$510	\$574	\$610	\$680	\$789	\$990
	8'0"	\$461	\$507	\$544	\$602	\$700	\$901	\$571	\$620	\$664	\$726	\$823	\$1,024
	9'0"	\$516	\$575	\$611	\$670	\$780	\$981	\$630	\$694	\$739	\$817	\$926	\$1,127
	10'0"	\$594	\$643	\$696	\$747	\$842	\$1,043	\$726	\$784	\$836	\$890	\$994	\$1,195

Frames are priced as equal or unequal rabbet. Frames 3"–4-1/2" jamb depth must be single rabbet (minimum 1" soffit).

FRAMES 1/2" DOUBLE RETURN X COMPRESSION ANCHORS													
Double		16 Gauge						14 Gauge					
Width	Height	4-1/2" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"	4-1/2" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"
Over 4'0" – 6'0"	6'8"	\$388	\$440	\$484	\$531	\$617	\$818	\$497	\$568	\$590	\$664	\$762	\$963
	7'0"	\$408	\$452	\$502	\$545	\$639	\$840	\$521	\$578	\$612	\$684	\$778	\$979
	7'2"	\$426	\$478	\$518	\$575	\$677	\$878	\$533	\$602	\$630	\$706	\$808	\$1,009
	8'0"	\$484	\$536	\$580	\$639	\$731	\$932	\$601	\$662	\$704	\$760	\$854	\$1,055
	9'0"	\$546	\$608	\$648	\$707	\$817	\$1,018	\$673	\$752	\$796	\$882	\$990	\$1,191
	10'0"	\$640	\$678	\$744	\$779	\$881	\$1,082	\$761	\$830	\$874	\$932	\$1,028	\$1,229
Over 6'0" – 8'0"	6'8"	\$412	\$465	\$511	\$561	\$650	\$851	\$530	\$601	\$625	\$697	\$804	\$1,005
	7'0"	\$432	\$477	\$529	\$575	\$672	\$873	\$554	\$611	\$647	\$717	\$820	\$1,021
	7'2"	\$450	\$503	\$545	\$605	\$710	\$911	\$566	\$635	\$665	\$739	\$850	\$1,051
	8'0"	\$508	\$561	\$607	\$669	\$764	\$965	\$634	\$695	\$739	\$793	\$896	\$1,097
	9'0"	\$570	\$633	\$675	\$737	\$850	\$1,051	\$706	\$785	\$831	\$915	\$1,032	\$1,233
	10'0"	\$664	\$703	\$771	\$809	\$914	\$1,115	\$794	\$863	\$909	\$965	\$1,070	\$1,271
Over 8'0" – 9'0"	6'8"	\$433	\$497	\$551	\$604	\$692	\$893	\$543	\$618	\$654	\$728	\$835	\$1,036
	7'0"	\$453	\$509	\$569	\$618	\$714	\$915	\$567	\$628	\$676	\$748	\$851	\$1,052
	7'2"	\$471	\$535	\$585	\$648	\$752	\$953	\$579	\$652	\$694	\$770	\$881	\$1,082
	8'0"	\$529	\$593	\$647	\$712	\$806	\$1,007	\$647	\$712	\$768	\$824	\$927	\$1,128
	9'0"	\$591	\$665	\$715	\$780	\$892	\$1,093	\$719	\$802	\$860	\$946	\$1,063	\$1,264
	10'0"	\$685	\$735	\$811	\$852	\$956	\$1,157	\$807	\$880	\$938	\$996	\$1,101	\$1,302
Over 9'0" – 10'0"	6'8"	\$475	\$554	\$613	\$668	\$762	\$963	\$613	\$690	\$727	\$802	\$909	\$1,110
	7'0"	\$495	\$566	\$631	\$682	\$784	\$985	\$637	\$700	\$749	\$822	\$925	\$1,126
	7'2"	\$513	\$592	\$647	\$712	\$822	\$1,023	\$649	\$724	\$767	\$844	\$955	\$1,156
	8'0"	\$571	\$650	\$709	\$776	\$876	\$1,077	\$717	\$784	\$841	\$898	\$1,001	\$1,202
	9'0"	\$633	\$722	\$777	\$844	\$962	\$1,163	\$789	\$874	\$933	\$1,020	\$1,137	\$1,338
	10'0"	\$727	\$792	\$873	\$916	\$1,026	\$1,227	\$877	\$952	\$1,011	\$1,070	\$1,175	\$1,376

Frames are priced as equal or unequal rabbet. Frames 3"–4-1/2" jamb depth must be single rabbet (minimum 1" soffit).



COMPONENT FRAMES 1/2" DOUBLE RETURN X COMPRESSION ANCHORS													
Header		16 Gauge							14 Gauge				
	Width	4-1/2" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"	4-1/2" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"
SGL Head	Thru 3'0"	\$61	\$77	\$90	\$103	\$131	\$198	\$85	\$97	\$107	\$119	\$149	\$216
	Over 3'0" – 4'0"	\$76	\$95	\$102	\$119	\$142	\$209	\$95	\$111	\$116	\$141	\$158	\$225
	Over 4'0" – 5'0"	\$161	\$183	\$207	\$226	\$254	\$321	\$199	\$216	\$238	\$256	\$285	\$352
DBL Head	Over 5'0" – 6'0"	\$116	\$126	\$140	\$153	\$179	\$246	\$153	\$166	\$174	\$192	\$212	\$279
	Over 6'0" – 8'0"	\$140	\$151	\$167	\$183	\$212	\$279	\$186	\$199	\$209	\$225	\$254	\$321
	Over 8'0" – 10'0"	\$203	\$240	\$269	\$290	\$324	\$391	\$269	\$288	\$311	\$330	\$359	\$426

COMPONENT FRAMES 1/2" DOUBLE RETURN X COMPRESSION ANCHORS													
Jamb Pair		16 Gauge						14 Gauge					
	Height	4-1/2" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"	4-1/2" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"
SGL Pair	6'8"	\$259	\$295	\$321	\$360	\$417	\$551	\$324	\$373	\$399	\$454	\$530	\$664
	7'0"	\$283	\$313	\$336	\$377	\$439	\$573	\$349	\$390	\$419	\$473	\$547	\$681
	7'2"	\$300	\$331	\$355	\$400	\$467	\$601	\$357	\$408	\$436	\$488	\$577	\$711
	8'0"	\$345	\$381	\$404	\$449	\$521	\$655	\$418	\$454	\$490	\$534	\$611	\$745
	9'0"	\$400	\$449	\$471	\$517	\$601	\$735	\$477	\$528	\$565	\$625	\$714	\$848
	10'0"	\$478	\$517	\$556	\$594	\$663	\$797	\$573	\$618	\$662	\$698	\$782	\$916
DBL Pair	6'8"	\$272	\$314	\$344	\$378	\$438	\$572	\$344	\$402	\$416	\$472	\$550	\$684
	7'0"	\$292	\$326	\$362	\$392	\$460	\$594	\$368	\$412	\$438	\$492	\$566	\$700
	7'2"	\$310	\$352	\$378	\$422	\$498	\$632	\$380	\$436	\$456	\$514	\$596	\$730
	8'0"	\$368	\$410	\$440	\$486	\$552	\$686	\$448	\$496	\$530	\$568	\$642	\$776
	9'0"	\$430	\$482	\$508	\$554	\$638	\$772	\$520	\$586	\$622	\$690	\$778	\$912
	10'0"	\$524	\$552	\$604	\$626	\$702	\$836	\$608	\$664	\$700	\$740	\$816	\$950

STEEL TYPES	
Description	List add
Cold rolled steel	Included
A60 Galvanized steel	\$61.00
G90 Galvanized steel (available in 14 and 16 gauge only)	\$108.00
12 Gauge - N/A with drywall returns	N/A

FRAME - STRIKE PREPARATIONS	
Description	List add
Special strike location	No charge
Standard strike at non-standard location	No charge
Cylindrical dead lock (2-3/4" strike)	\$25.00
Mortise dead lock (3-1/2" strike)	\$25.00
Unit lock/double strike prep (ex. Schlage H)	N/A
Rim reinforcement only	\$33.00
Surface vertical rod reinforcement only	\$33.00
Concealed vertical rod (mortise strike) (per prep)	\$73.00
Exit alarm reinforcement only	\$33.00
Electric strike (no junction box)	\$107.00
Flush bolt strike prep/reversible or automatic	\$63.00
Surface bolt reinforce only	\$33.00

HINGE PREPARATIONS	
Description	List add
Special hinge locations	No charge
4-1/2" or 5" Universal hinge prep	No charge
Additional hinge prep (per hinge)	\$25.00
Electric hinge	\$25.00
▪ One 1/2" dia. hole in one hinge reinf.	
▪ No wiring included, no junction box	
Continuous hinge reinforcement (rabbet or face)	\$88.00
Power transfer (no junction box)	\$111.00

CLOSER PREPARATIONS	
Description	List add
Closer reinforcement - 14 gauge plate - RA or PA	\$33.00
Full depth reinforcement (price per foot)	\$35.00
Concealed overhead door closer, holder or stop	\$307.00
Allegion Concealed overhead door closer, holder or stop	\$278.00

See [Engineering Section](#) for further options and/or details.



ME SERIES

Double egress


Refer to technical data sheet on page 12 and 13

- Double Egress Openings are designed to permit the flow of traffic in two directions through the same opening
 - All double egress openings shall be supplied as right hand swing unless otherwise specified
- Fire Labeled: Maximum 3 hour
- Face: 1-3/8" standard, 2" optional


- Universal Standard/Heavy Weight Hinge: Frames for 1-3/4" doors shall have a 7 gauge steel hinge reinforcement plate, projection welded with provisions for 4-1/2" x 4-1/2" template hinges. Hinge plate is designed to be modified to accept a heavy weight hinge by removing spacer plate.
- Frames for 1-3/8" doors shall have a 11 gauge steel hinge reinforcement plate, projection welded with provisions for 3-1/2" x 3-1/2" standard weight template hinges
- Hinge Backset: 5/16"
- Backbend: 7/16" (Single Return)




Welded
Corner Connection




Double
Egress
Corner




Double Egress
Anchor
(welded in)




Double Egress
Prepared
Opening Anchor




L Strap Anchor
Double Egress
(Wood Stud)
(welded in)




Double Egress
Hinge




Double Egress
Head Anchor
(welded in)



Double Egress
Wire Anchor




1-3/8" Face (standard)



2" Face (optional)

Rough Opening Required for Butted Frame

Door Width Opening + 2x Smaller Face Dimension + 1-3/4"
Door Height Opening + Smaller Face Dimension + 1/4"



FRAMES 7/16" SINGLE RETURN X 1-3/8" FACE

Width	Height	16 Gauge						14 Gauge					
		4-1/2" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"	4-1/2" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"
Thru 6'0"	6'8"	\$984	\$1,019	\$1,053	\$1,126	\$1,234	\$1,435	\$1,077	\$1,095	\$1,142	\$1,236	\$1,333	\$1,534
	7'0"	\$990	\$1,021	\$1,061	\$1,138	\$1,242	\$1,443	\$1,092	\$1,117	\$1,166	\$1,248	\$1,357	\$1,558
	7'2"	\$1,026	\$1,049	\$1,087	\$1,158	\$1,266	\$1,467	\$1,114	\$1,123	\$1,176	\$1,254	\$1,369	\$1,570
	8'0"	\$1,086	\$1,111	\$1,147	\$1,222	\$1,338	\$1,539	\$1,193	\$1,207	\$1,256	\$1,334	\$1,463	\$1,664
	9'0"	\$1,116	\$1,151	\$1,181	\$1,248	\$1,372	\$1,573	\$1,211	\$1,255	\$1,290	\$1,364	\$1,493	\$1,694
	10'0"	\$1,162	\$1,195	\$1,235	\$1,314	\$1,434	\$1,635	\$1,261	\$1,291	\$1,340	\$1,436	\$1,565	\$1,766
Over 6'0" – 8'0"	6'8"	\$1,020	\$1,055	\$1,092	\$1,164	\$1,272	\$1,473	\$1,106	\$1,134	\$1,180	\$1,274	\$1,379	\$1,580
	7'0"	\$1,026	\$1,057	\$1,100	\$1,176	\$1,280	\$1,481	\$1,120	\$1,156	\$1,204	\$1,286	\$1,403	\$1,604
	7'2"	\$1,062	\$1,085	\$1,126	\$1,196	\$1,304	\$1,505	\$1,146	\$1,162	\$1,214	\$1,292	\$1,415	\$1,616
	8'0"	\$1,122	\$1,147	\$1,186	\$1,260	\$1,376	\$1,577	\$1,222	\$1,246	\$1,294	\$1,372	\$1,509	\$1,710
	9'0"	\$1,152	\$1,187	\$1,220	\$1,286	\$1,410	\$1,611	\$1,242	\$1,294	\$1,328	\$1,402	\$1,539	\$1,740
	10'0"	\$1,198	\$1,231	\$1,274	\$1,352	\$1,472	\$1,673	\$1,290	\$1,330	\$1,378	\$1,474	\$1,611	\$1,812
Over 8'0" – 9'0"	6'8"	\$1,039	\$1,088	\$1,122	\$1,181	\$1,296	\$1,497	\$1,143	\$1,172	\$1,214	\$1,299	\$1,405	\$1,606
	7'0"	\$1,045	\$1,090	\$1,130	\$1,193	\$1,304	\$1,505	\$1,157	\$1,194	\$1,238	\$1,311	\$1,429	\$1,630
	7'2"	\$1,081	\$1,118	\$1,156	\$1,213	\$1,328	\$1,529	\$1,183	\$1,200	\$1,248	\$1,317	\$1,441	\$1,642
	8'0"	\$1,141	\$1,180	\$1,216	\$1,277	\$1,400	\$1,601	\$1,259	\$1,284	\$1,328	\$1,397	\$1,535	\$1,736
	9'0"	\$1,171	\$1,220	\$1,250	\$1,303	\$1,434	\$1,635	\$1,279	\$1,332	\$1,362	\$1,427	\$1,565	\$1,766
	10'0"	\$1,217	\$1,264	\$1,304	\$1,369	\$1,496	\$1,697	\$1,327	\$1,368	\$1,412	\$1,499	\$1,637	\$1,838
Over 9'0" – 10'0"	6'8"	\$1,101	\$1,165	\$1,200	\$1,260	\$1,381	\$1,582	\$1,215	\$1,264	\$1,307	\$1,399	\$1,503	\$1,704
	7'0"	\$1,107	\$1,167	\$1,208	\$1,272	\$1,389	\$1,590	\$1,229	\$1,286	\$1,331	\$1,411	\$1,527	\$1,728
	7'2"	\$1,143	\$1,195	\$1,234	\$1,292	\$1,413	\$1,614	\$1,255	\$1,292	\$1,341	\$1,417	\$1,539	\$1,740
	8'0"	\$1,203	\$1,257	\$1,294	\$1,356	\$1,485	\$1,686	\$1,331	\$1,376	\$1,421	\$1,497	\$1,633	\$1,834
	9'0"	\$1,233	\$1,297	\$1,328	\$1,382	\$1,519	\$1,720	\$1,351	\$1,424	\$1,455	\$1,527	\$1,663	\$1,864
	10'0"	\$1,279	\$1,341	\$1,382	\$1,448	\$1,581	\$1,782	\$1,399	\$1,460	\$1,505	\$1,599	\$1,735	\$1,936

Minimum jamb depth is 4-1/2".

COMPONENT FRAMES 7/16" SINGLE RETURN X 1-3/8" FACE

Heads		16 Gauge						14 Gauge					
	Width	4-1/2" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"	4-1/2" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"
DBL Head	Thru 6'0"	\$342	\$351	\$363	\$388	\$424	\$491	\$379	\$381	\$398	\$426	\$459	\$526
	Over 6'0" – 8'0"	\$378	\$387	\$402	\$426	\$462	\$529	\$408	\$420	\$436	\$464	\$505	\$572
	Over 8'0" – 9'0"	\$397	\$420	\$432	\$443	\$486	\$553	\$445	\$458	\$470	\$489	\$531	\$598
	Over 9'0" – 10'0"	\$459	\$497	\$510	\$522	\$571	\$638	\$517	\$550	\$563	\$589	\$629	\$696

COMPONENT FRAMES 7/16" SINGLE RETURN X 1-3/8" FACE

Jamb Pairs		16 Gauge						14 Gauge					
	Height	4-1/2" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"	4-1/2" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"
DBL Pair	6'8"	\$642	\$668	\$690	\$738	\$810	\$944	\$698	\$714	\$744	\$810	\$874	\$1,008
	7'0"	\$648	\$670	\$698	\$750	\$818	\$952	\$712	\$736	\$768	\$822	\$898	\$1,032
	7'2"	\$684	\$698	\$724	\$770	\$842	\$976	\$738	\$742	\$778	\$828	\$910	\$1,044
	8'0"	\$744	\$760	\$784	\$834	\$914	\$1,048	\$814	\$826	\$858	\$908	\$1,004	\$1,138
	9'0"	\$774	\$800	\$818	\$860	\$948	\$1,082	\$834	\$874	\$892	\$938	\$1,034	\$1,168
	10'0"	\$820	\$844	\$872	\$926	\$1,010	\$1,144	\$882	\$910	\$942	\$1,010	\$1,106	\$1,240



STEEL TYPES	
Cold rolled steel	Included
A60 Galvanized steel	\$61.00
G90 Galvanized steel (available in 14 and 16 gauge only)	\$108.00
12 Gauge - see Cut-N-Notch	N/A

HINGE PREPARATIONS	
Special hinge locations	No charge
4-1/2" or 5" Universal hinge prep	No charge
Additional hinge prep (per hinge)	\$25.00
Electric hinge	\$25.00
▪ One 1/2" dia. hole in one hinge reinf. ▪ No wiring included, no junction box	
Continuous hinge reinforcement (rabbet)	\$88.00
Power transfer (no junction box)	\$111.00

FRAME - STRIKE PREPARATIONS	
Surface vertical rod reinforcement only	\$33.00
Concealed vertical rod (mortise strike) (per prep)	\$73.00

CLOSER PREPARATIONS	
Closer reinforcement - 14 gauge plate - RA or PA	\$33.00
Full depth reinforcement (price per foot)	\$35.00
Concealed overhead door closer, holder or stop	\$307.00
Allegion Concealed overhead door closer, holder or stop	\$278.00

SPECIAL CONSTRUCTIONS	
Special width (use next larger size)	No charge
Special height (use next larger size)	No charge
Mag switch/DPS - Hole only	\$25.00
Mag switch/DPS - Prep and reinf. (no junction box)	\$97.00
8" Junction box welded in	\$34.00
10" Junction box welded in soffit	\$34.00
14" Junction box welded in	\$34.00

LABEL PREPARATIONS	
Mark numbers	No charge
U.L. Emboss (must specify)	No charge
U.L. Mylar label (standard unless specified otherwise)	\$24.00
U.L. Metal label	\$31.00
ITS/Warnock Hersey Metal label	\$31.00

Fire rating - max depth 14". Heads will have anchors welded in.

SPECIAL FINISH PREPARATIONS	
Second coat of primer	\$123.00
Finish paint setup charge (never waived)	\$1,433.00
Finish paint	\$360.00
▪ Minimum quantity of 20 frames per color ▪ Price includes full carton wrap	

Finish paint unavailable on welded frames.

ANCHOR OPTIONS	
Welded in prepared opening anchor (per anchor)	\$17.00
Welded in anchor (per anchor)	\$7.50
Punch and dimple only (per prep)	\$6.00

Prepared Opening Frames up 7'1" require 8 anchors (max 8-3/4" depth). Over 7'2" thru 10'0" require 10 (max 8-3/4" depth). Frames over 8-3/4" receive double the quantity and price.

FRAME CONSTRUCTION	
Unit bundle (3pc)	\$7.00
Standard face weld (3pc)	\$121.00
Full profile weld (3pc)	\$220.00

FRAME PROFILE OPTIONS	
No returns	No charge
Non-standard face - see Cut-N-Notch section	N/A
2" Face	No charge



See [Engineering Section](#) for further options and/or details.

MH SERIES


Double egress

Refer to technical data sheet on page 14


- Double Egress Openings are designed to permit the flow of traffic in two directions through the same opening
- Face: 2"
- Universal Standard/Heavy Weight Hinge: Frames for 1-3/4" doors shall have a 7 gauge steel hinge reinforcement plate, projection welded with provisions for 4-1/2" x 4-1/2" template hinges.
- Hinge plate is designed to be modified to accept a heavy weight hinge by removing spacer plate.
- Hinge Backset: 5/16"
- Backbend: 1/2" (Double Return)




Double Egress Corner




Double Egress Hinge



Compression Anchor (Standard)



Rough Opening Required for DW Double Egress Frame Based on (1) compression anchor located on door rabbit (per jamb)
Door width opening + 3"
Door height opening + 1"





FRAMES 1/2" DOUBLE RETURN X 2" FACE X COMPRESSION ANCHORS													
Width	Height	16 Gauge						14 Gauge					
		4-1/2" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"	4-1/2" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"
Thru 6'0"	6'8"	\$1,090	\$1,146	\$1,200	\$1,257	\$1,388	\$1,555	\$1,249	\$1,316	\$1,350	\$1,445	\$1,551	\$1,707
	7'0"	\$1,098	\$1,150	\$1,210	\$1,277	\$1,398	\$1,565	\$1,267	\$1,340	\$1,371	\$1,452	\$1,567	\$1,741
	7'2"	\$1,133	\$1,179	\$1,240	\$1,305	\$1,429	\$1,604	\$1,288	\$1,355	\$1,381	\$1,452	\$1,579	\$1,750
	8'0"	\$1,201	\$1,248	\$1,303	\$1,363	\$1,499	\$1,661	\$1,384	\$1,450	\$1,480	\$1,548	\$1,690	\$1,841
	9'0"	\$1,231	\$1,293	\$1,334	\$1,403	\$1,533	\$1,708	\$1,399	\$1,491	\$1,520	\$1,587	\$1,720	\$1,895
	10'0"	\$1,281	\$1,344	\$1,404	\$1,471	\$1,606	\$1,769	\$1,460	\$1,549	\$1,584	\$1,666	\$1,802	\$1,964
Over 6'0" – 8'0"	6'8"	\$1,128	\$1,190	\$1,244	\$1,300	\$1,425	\$1,606	\$1,283	\$1,354	\$1,395	\$1,493	\$1,595	\$1,758
	7'0"	\$1,136	\$1,194	\$1,254	\$1,320	\$1,435	\$1,616	\$1,301	\$1,378	\$1,416	\$1,500	\$1,611	\$1,792
	7'2"	\$1,171	\$1,223	\$1,284	\$1,348	\$1,466	\$1,655	\$1,322	\$1,393	\$1,426	\$1,500	\$1,623	\$1,801
	8'0"	\$1,239	\$1,292	\$1,347	\$1,406	\$1,536	\$1,712	\$1,418	\$1,488	\$1,525	\$1,596	\$1,734	\$1,892
	9'0"	\$1,269	\$1,337	\$1,378	\$1,446	\$1,570	\$1,759	\$1,433	\$1,529	\$1,565	\$1,635	\$1,764	\$1,946
	10'0"	\$1,319	\$1,388	\$1,448	\$1,514	\$1,643	\$1,820	\$1,494	\$1,587	\$1,629	\$1,714	\$1,846	\$2,015
Over 8'0" – 9'0"	6'8"	\$1,147	\$1,222	\$1,275	\$1,317	\$1,453	\$1,631	\$1,318	\$1,396	\$1,429	\$1,515	\$1,628	\$1,800
	7'0"	\$1,155	\$1,226	\$1,285	\$1,337	\$1,463	\$1,641	\$1,336	\$1,420	\$1,450	\$1,522	\$1,644	\$1,834
	7'2"	\$1,190	\$1,255	\$1,315	\$1,365	\$1,494	\$1,680	\$1,357	\$1,435	\$1,460	\$1,522	\$1,656	\$1,843
	8'0"	\$1,258	\$1,324	\$1,378	\$1,423	\$1,564	\$1,737	\$1,453	\$1,530	\$1,559	\$1,618	\$1,767	\$1,934
	9'0"	\$1,288	\$1,369	\$1,409	\$1,463	\$1,598	\$1,784	\$1,468	\$1,571	\$1,599	\$1,657	\$1,797	\$1,988
	10'0"	\$1,338	\$1,420	\$1,479	\$1,531	\$1,671	\$1,845	\$1,529	\$1,629	\$1,663	\$1,736	\$1,879	\$2,057
Over 9'0" – 10'0"	6'8"	\$1,216	\$1,308	\$1,367	\$1,408	\$1,548	\$1,730	\$1,401	\$1,502	\$1,540	\$1,631	\$1,742	\$1,917
	7'0"	\$1,224	\$1,312	\$1,377	\$1,428	\$1,558	\$1,740	\$1,419	\$1,526	\$1,561	\$1,638	\$1,758	\$1,951
	7'2"	\$1,259	\$1,341	\$1,407	\$1,456	\$1,589	\$1,779	\$1,440	\$1,541	\$1,571	\$1,638	\$1,770	\$1,960
	8'0"	\$1,327	\$1,410	\$1,470	\$1,514	\$1,659	\$1,836	\$1,536	\$1,636	\$1,670	\$1,734	\$1,881	\$2,051
	9'0"	\$1,357	\$1,455	\$1,501	\$1,554	\$1,693	\$1,883	\$1,551	\$1,677	\$1,710	\$1,773	\$1,911	\$2,105
	10'0"	\$1,407	\$1,506	\$1,571	\$1,622	\$1,766	\$1,944	\$1,612	\$1,735	\$1,774	\$1,852	\$1,993	\$2,174

COMPONENT FRAMES 1/2" DOUBLE RETURN X 2" FACE X COMPRESSION ANCHORS													
Heads		16 Gauge						14 Gauge					
	Width	4-1/2" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"	4-1/2" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"
DBL Head	Thru 6'0"	\$379	\$394	\$414	\$437	\$481	\$531	\$441	\$461	\$466	\$492	\$526	\$580
	Over 6'0" – 8'0"	\$417	\$438	\$458	\$480	\$518	\$582	\$475	\$499	\$511	\$540	\$570	\$631
	Over 8'0" – 9'0"	\$436	\$470	\$489	\$497	\$546	\$607	\$510	\$541	\$545	\$562	\$603	\$673
	Over 9'0" – 10'0"	\$505	\$556	\$581	\$588	\$641	\$706	\$593	\$647	\$656	\$678	\$717	\$790

COMPONENT FRAMES 1/2" DOUBLE RETURN X 2" FACE X COMPRESSION ANCHORS													
Jamb Pair		16 Gauge						14 Gauge					
	Height	4-1/2" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"	4-1/2" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"
DBL Pair	6'8"	\$711	\$752	\$786	\$820	\$907	\$1,024	\$808	\$855	\$884	\$953	\$1,025	\$1,127
	7'0"	\$719	\$756	\$796	\$840	\$917	\$1,034	\$826	\$879	\$905	\$960	\$1,041	\$1,161
	7'2"	\$754	\$785	\$826	\$868	\$948	\$1,073	\$847	\$894	\$915	\$960	\$1,053	\$1,170
	8'0"	\$822	\$854	\$889	\$926	\$1,018	\$1,130	\$943	\$989	\$1,014	\$1,056	\$1,164	\$1,261
	9'0"	\$852	\$899	\$920	\$966	\$1,052	\$1,177	\$958	\$1,030	\$1,054	\$1,095	\$1,194	\$1,315
	10'0"	\$902	\$950	\$990	\$1,034	\$1,125	\$1,238	\$1,019	\$1,088	\$1,118	\$1,174	\$1,276	\$1,384

STEEL TYPES	
Cold rolled steel	Included
A60 Galvanized steel	\$61.00
G90 Galvanized steel (available in 14 and 16 gauge only)	\$108.00
12 Gauge (N/A on drywall frame)	N/A

HINGE PREPARATIONS	
Special hinge locations	No charge
4-1/2" or 5" Universal hinge prep	No charge
Additional hinge prep (per hinge)	\$25.00
Electric hinge	\$25.00
▪ One 1/2" dia. hole in one hinge reinf. ▪ No wiring included, no junction box	
Continuous hinge reinforcement (rabbet)	\$88.00
Power transfer (no junction box)	\$111.00

FRAME - STRIKE PREPARATIONS	
Surface vertical rod reinforcement only	\$33.00
Concealed vertical rod (mortise strike) (per prep)	\$73.00

CLOSER PREPARATIONS	
Closer reinforcement - 14 gauge plate - RA or PA	\$33.00
Full depth reinforcement (price per foot)	\$35.00
Concealed overhead door closer, holder or stop	\$307.00
Allegion Concealed overhead door closer, holder or stop	\$278.00

SPECIAL CONSTRUCTIONS	
Special width (use next larger size)	No charge
Special height (use next larger size)	No charge
Mag switch/DPS - Hole only	\$25.00
Mag switch/DPS - Prep and reinf. (no junction box)	\$97.00
8" Junction box welded in	\$34.00
14" Junction box welded in	\$34.00
10" Junction box welded in soffit	\$34.00

LABEL PREPARATIONS	
Mark numbers	No charge
U.L. Emboss (must specify)	N/A
U.L. Mylar label (standard unless specified otherwise)	N/A
U.L. Metal label	N/A
ITS/Warnock Hersey Metal label	N/A

Fire rating not available.

SPECIAL FINISH PREPARATIONS	
Second coat of primer	\$123.00
Finish paint setup charge (never waived)	\$1,433.00
Finish paint	\$360.00
▪ Minimum quantity of 20 frames per color ▪ Price includes full carton wrap	

Finish paint unavailable on welded frames.

ANCHOR OPTIONS	
Welded in prepared opening anchor (per anchor)	\$17.00
Welded in anchor (per anchor)	\$7.50
Punch and dimple only (per prep)	\$6.00

Prepared Opening Frames up 7'1" require 8 anchors (max 8-3/4" depth). Over 7'2" thru 10'0" require 10 (max 8-3/4" depth). Frames over 8-3/4" receive double the quantity and price.

FRAME CONSTRUCTION	
Unit bundle (3pc)	\$7.00
Standard face weld (3pc) (omit compression anchor)	\$121.00
Full face weld (3pc) (omit compression anchor)	\$220.00

FRAME PROFILE OPTIONS	
No returns	No charge
Non-standard face - see Cut-N-Notch	N/A
2" Face	No charge

See [Engineering Section](#) for further options and/or details.

this page intentionally blank



LEAD LINED DOORS AND FRAMES

Specialty

Refer to technical data sheet on page 16

Typical construction based on DL Series door

DOOR

- Lead Thickness: 1/16" standard
- Edge Seam Construction: Visible seam
- Thickness: 1-3/4"
- Actual Door Size: Door undersized from nominal by 1/4" in width and 7/8" in height. Standard undercut is 3/4".
- Hinge Rail and Reinforcement: Hinge edge is non-beveled and reinforced with a continuous 10 or 16 gauge steel channel projection welded at a maximum 5" on center
- Lock Rail: Lock edge is non-beveled and reinforced with a continuous 16 or 14 gauge steel channel projection welded at a maximum 5" on center. (Beveled lock edge 1/8" in 2" optional.)

- Top Channel: Top Channel is a flush 16 gauge steel channel, projection welded at a maximum 2-1/2" on center
- Bottom Channel: Bottom Channel is an inverted 16 gauge steel channel, projection welded at a maximum 2-1/2" on center
- Cores Available: Steel Stiffened core
- Face Skins: Galvannealed, 18 gauge, 16 gauge or 14 gauge
- Closer Reinforcement (Optional): When closer reinforcement requested 14 gauge standard/12 gauge optional. (18" x 6")



- Size Availability
 - Maximum 4'10" x 10'0" (Singles)
 - Maximum 9'8" x 10'0" (Pairs)
- SDI 100 Level/Model: Level 2-4 Model 1 (Maximum Duty Performace Level A and B)
- Universal Standard/Heavy Weight Hinge: Hinge fillers are used allowing for an easy modification from standard to heavy weight hinge prep
- Handing Design: Non-Handed standard (Handed optional)


FRAME

- Thickness: Made for standard door 1-3/4"
- Gauges: 16 or 14 (12 gauge available with coped corner condition for welding)
- Faces: 2" standard
- Standard Rabbets
 - 1-3/8" (actual dimension 1-9/16")
 - 1-3/4" (actual dimension 1-15/16")
 - Rabbet dimension is 3/16" greater than the door thickness.
- Stop: 5/8" standard

- Closer Reinforcement (Optional): 1-3/8" x 14" x 14 gauge plate
- Size Availability
 - Maximum Size 4'10" x 10'0" Single
 - Maximum Size 9'8" x 10'0" Double
- Universal Standard/Heavy Weight Hinge: Frames for 1-3/4" doors shall have a 7 gauge steel hinge reinforcement plate, projection welded with provisions for 4-1/2" x 4-1/2" template hinges. Hinge plate is designed to be modified to accept a heavy weight hinge by removing spacer plate.

- Strike Prep: Frames for 1-3/4" doors shall have a 14 gauge steel strike reinforcement plate, extruded and formed to the equivalent of 10 gauge, projection welded with provisions for Universal ANSI A115.1 or ANSI A115.2 strike (4-7/8")
- Hinge Backset
 - Frame = 5/16"
 - Door = 1/4"





Doors

1/16" THICK LEAD WITH 20 GA STIFFENERS				
Width	Height	18 GA	16 GA	14 GA
Thru 3'0"	Thru 7'0"	\$6,340	\$6,504	\$7,112
	Thru 8'0"	\$6,669	\$6,889	\$7,451
	Thru 10'0"	\$8,554	\$8,678	\$9,225
Over 3'0" – 4'0"	Thru 7'0"	\$6,683	\$6,903	\$7,465
	Thru 8'0"	\$6,935	\$7,201	\$7,718
	Thru 10'0"	\$10,799	\$10,972	\$11,625
Over 4'0" – 4'10"	Thru 7'0"	N/A	\$9,726	\$10,787
	Thru 8'0"	N/A	\$10,022	\$11,149
	Thru 10'0"	N/A	\$19,165	\$20,532

LEAD OPTIONS

Description	Door	Frame
1/16" Lead	Included	Included

STEEL TYPES


Description	Door	Frame
Cold rolled steel	N/A	N/A
A60 Galvanized steel	Included	Included
G90 Galvanized steel (14 and 16 gauge only)	\$445.00	\$108.00

LABEL PREPARATIONS

Description	Door	Frame
Mark numbers	No charge	No charge
U.L. Mylar label (standard unless specified otherwise)	N/A	N/A
U.L. Metal label	N/A	N/A
Warnock Hersey Metal label	N/A	N/A

NOTES:

Frames are priced as Equal or Unequal rabbet.
 Frames 3"-4-1/2" Jamb depth must be single rabbet.
 For Borrowed Lite, Side Lite, and Elevation Pricing,
 see [Cut-N-Notch Section](#). Mullions are not available as Lead-Lined.



Lead-Line Astragal required on pairs

Frames

SINGLE OR DOUBLE RETURN - 16 GAUGE					
Single Frame		Jamb Depth			
Width	Height	4-5/8" thru 5-3/4"	5-7/8" thru 8-3/4"	8-7/8" thru 14-3/4"	14-7/8" thru 20"
Thru 3'0"	Thru 7'0"	\$5,024	\$5,136	\$5,258	\$5,410
	Thru 8'0"	\$5,106	\$5,204	\$5,326	\$5,490
	Thru 10'0"	\$5,294	\$5,448	\$5,571	\$5,730
Over 3'0" – 4'0"	Thru 7'0"	\$5,041	\$5,146	\$5,268	\$5,431
	Thru 8'0"	\$5,123	\$5,212	\$5,335	\$5,497
	Thru 10'0"	\$5,310	\$5,454	\$5,581	\$5,741
Over 4'0" – 4'10"	Thru 7'0"	\$5,090	\$5,205	\$5,327	\$5,491
	Thru 8'0"	\$5,172	\$5,275	\$5,395	\$5,558
	Thru 10'0"	\$5,360	\$5,515	\$5,637	\$5,799
Double Frame		Jamb Depth			
Thru 6'0"	Thru 7'0"	\$5,109	\$5,250	\$5,369	\$5,532
	Thru 8'0"	\$5,206	\$5,335	\$5,455	\$5,618
	Thru 10'0"	\$5,438	\$5,586	\$5,706	\$5,869
Over 6'0" – 8'0"	Thru 7'0"	\$5,124	\$5,280	\$5,401	\$5,562
	Thru 8'0"	\$5,223	\$5,368	\$5,489	\$5,649
	Thru 10'0"	\$5,454	\$5,618	\$5,737	\$5,900
Over 8'0" – 9'8"	Thru 7'0"	\$5,176	\$5,361	\$5,486	\$5,646
	Thru 8'0"	\$5,276	\$5,450	\$5,571	\$5,730
	Thru 10'0"	\$5,503	\$5,701	\$5,820	\$5,983

SINGLE OR DOUBLE RETURN - 14 GAUGE

Single Frame		Jamb Depth			
Width	Height	4-5/8" thru 5-3/4"	5-7/8" thru 8-3/4"	8-7/8" thru 14-3/4"	14-7/8" thru 20"
Thru 3'0"	Thru 7'0"	\$5,106	\$5,253	\$5,392	\$5,553
	Thru 8'0"	\$5,199	\$5,331	\$5,470	\$5,633
	Thru 10'0"	\$5,414	\$5,595	\$5,733	\$5,898
Over 3'0" – 4'0"	Thru 7'0"	\$5,124	\$5,268	\$5,401	\$5,562
	Thru 8'0"	\$5,219	\$5,347	\$5,477	\$5,639
	Thru 10'0"	\$5,431	\$5,611	\$5,742	\$5,905
Over 4'0" – 4'10"	Thru 7'0"	\$5,205	\$5,346	\$5,469	\$5,631
	Thru 8'0"	\$5,268	\$5,426	\$5,559	\$5,724
	Thru 10'0"	\$5,512	\$5,724	\$5,826	\$5,987
Double Frame		Jamb Depth			
Thru 6'0"	Thru 7'0"	\$5,238	\$5,399	\$5,532	\$5,693
	Thru 8'0"	\$5,345	\$5,493	\$5,629	\$5,789
	Thru 10'0"	\$5,596	\$5,762	\$5,895	\$6,052
Over 6'0" – 8'0"	Thru 7'0"	\$5,256	\$5,431	\$5,562	\$5,726
	Thru 8'0"	\$5,367	\$5,527	\$5,656	\$5,818
	Thru 10'0"	\$5,618	\$5,795	\$5,920	\$6,086
Over 8'0" – 9'8"	Thru 7'0"	\$5,310	\$5,522	\$5,652	\$5,814
	Thru 8'0"	\$5,419	\$5,617	\$5,748	\$5,909
	Thru 10'0"	\$5,671	\$5,883	\$6,012	\$6,177

HINGE PREPARATIONS

Description	Door	Frame
Special hinge locations	No charge	No charge
4-1/2" or 5" Universal hinge prep	No charge	No charge
Additional hinge prep (per hinge)	\$27.00	\$25.00
4" Template hinge prep (square corner only) (per hinge)	\$62.00	\$62.00
Anchor hinge prep (no drilling or tapping)	\$518.00	\$305.00
Electric hinge	\$27.00	\$25.00
▪ Cutout in one hinge reinf.		
▪ No junction box or conduit		
Continuous hinge reinforcement	\$94.00	\$88.00
Power transfer	\$145.00	\$111.00
▪ Cutout and reinf.		
▪ No junction box or conduit		
8" Junction box welded in	N/A	\$34.00
10" Junction box welded in soffit	N/A	\$34.00
14" Junction box welded in	N/A	\$34.00

PIVOT OPTIONS

Description	Door	Frame
Center hung - per prep (no drilling or tapping) (N/A for intermediate and offset pivots)	N/A	\$114.00
Rescue hardware prep - one pivot (no drilling or tapping) and emergency stop	N/A	\$305.00
Double lipped strike	N/A	\$152.00
Pocket pivot - per prep	\$206.00	\$173.00

DOOR - LOCK/FRAME - STRIKE PREPARATIONS

Description	Door	Frame
Standard lock (strike) at non-standard location	No charge	No charge
Cylindrical dead lock (2-3/4" strike)	\$65.00	\$25.00
Mortise dead lock (3-1/2" strike)	\$65.00	\$25.00
Electric strike (no junction box or conduit)	\$143.00	\$107.00
ASA Strike	\$63.00	Included
Rim reinforcement only	\$54.00	\$33.00
Rim reinforcement with function prep	\$60.00	N/A
Mortise exit device reinforcement with function prep	\$95.00	N/A
Surface vertical rod reinforcement only	\$87.00	\$33.00
Concealed vertical rod (strike) per prep	\$648.00	N/A
Exit alarm reinforcement only	\$66.00	\$33.00
Push pull reinforcement	\$42.00	N/A

CLOSER PREPARATIONS

Description	Door	Frame
Closer reinforcement (frame 14 gauge plate)	\$40.00	\$33.00
Concealed overhead door closer, holder or stop	\$394.00	\$307.00

SPECIAL CONSTRUCTIONS

Description	Door	Frame
Undercut - under 3/8" price next larger size	No charge	N/A
Inverted top channel	No charge	N/A
Flush bottom channel	No charge	N/A
Hospital Stops	N/A	N/A
Seal top or bottom channel and finish smooth each	\$150.00	N/A
Mag switch/DPS - Hole only	\$25.00	\$25.00
Mag switch/DPS - Prep and reinf. (no junction box)	\$131.00	\$97.00
Bondo filled edge	\$128.00	N/A
Continuous welded edge (N/A in 20 gauge)	\$192.00	N/A
Beveled lock edge (1/8" in 2") N/A in 14 gauge and Inactive leafs with strike(s)	\$23.00	N/A
10 Gauge hinge and 14 gauge lock channels (DE Series - standard on 14 gauge door)	\$166.00	N/A
Automatic door bottom (mortise type)	\$239.00	N/A
Conduit/raceway - includes wire pull	\$202.00	N/A

SPECIAL FINISH PREPARATIONS

Description	Door	Frame
Second coat of primer	N/A	N/A
Finish paint setup charge (never waived)	N/A	N/A
Finish paint	N/A	N/A
▪ Minimum quantity of 20 door or frame units		
▪ Price includes full carton wrap		

ANCHOR OPTIONS

Description	Door	Frame
Welded in prepared opening anchor (per anchor)	N/A	\$17.00
Welded in anchor (per anchor)	N/A	\$7.50
Punch and dimple only (per prep)	N/A	\$6.00

FRAME CONSTRUCTION

Description	Door	Frame
Unit bundle (3pc)	N/A	\$7.00
Standard face weld (3pc)	N/A	\$121.00
Full profile weld (3pc)	N/A	\$220.00

FRAME PROFILE OPTIONS

Description	Door	Frame
Single rabbet	N/A	No charge
Cased opening	N/A	N/A
4" Face heads (through 4'0")	N/A	\$64.00
4" Face heads (over 4'0")	N/A	\$89.00
Non-standard face (per frame) (equal faces)	N/A	\$79.00

DOUBLE SWING PREPARATIONS

Description	Door	Frame
Attaching astragal (includes astragal lead-lined)	\$766.00	N/A
Flush bolt prep (ANSI 115.4)	\$101.00	\$63.00
Surface bolt reinforce only	\$38.00	\$33.00
Open back strike	\$171.00	N/A

GLASS KIT OPTIONS

	Vision/ Narrow Lite up to 100 inch ²	Half Glass over 100 inch ² up to 800 inch ²	Full Glass over 800 inch ²
Cutout with kit installed	\$245	\$290	N/A
Cutout with kit and reinf.	\$332	\$377	\$421
Sunburst kit (1/2" glass included)	\$594	N/A	N/A
Muntin bar (each)	\$160	\$160	\$160
Galvanized kit add	\$131	\$131	\$131
Glass pocket add (other than 1/4")	\$221	\$221	\$221

Prices are based on Republic standard lite kit (No glass unless noted otherwise). Contact customer service for lead-lined lite insert add.

CUTOUT ONLY OPTIONS (GLASS KITS & LOUVERS)

	Up to 100 inch ²	Over 100 inch ² up to 800 inch ²	Over 800 inch ²
Panel in place	N/A	N/A	N/A
Cutout only	N/A	N/A	N/A
Cutout with reinforcement	\$181	\$181	\$181

See [Engineering Section](#) for further options and/or details.

BULLET RESISTANT DOORS AND FRAMES

Specialty

Refer to technical data sheet on page 16

DOOR

- Door Thickness: 1-13/16" (+/- 1/16")
- Edge Seam Construction: Seamless
- Actual Door Size: Door undersized from nominal by 1/4" in width and 7/8" in height. Standard undercut is 3/4".
- Hinge Rail and Reinforcement: Hinge edge is non-beveled and reinforced with a continuous 10 gauge steel channel projection welded at a maximum 5" on center. (Backset 1/4")
- Lock Rail: Lock edge is non-beveled and reinforced with a continuous 14 gauge steel channel projection welded at a maximum 5" on center. 16 gauge reinforcements for mortise or cylindrical locks are of an integral type in accordance with ANSI A115 Standards.

- Top Channel: Top Channel is a flush 16 gauge channel, projection welded at a maximum 2-1/2" on center
- Bottom Channel: Bottom Channel is an inverted 16 gauge steel channel, projection welded at a maximum 2-1/2" on center
- Cores Available
 - Polystyrene Levels 1
 - Polystyrene with armor plating Levels 2-3
 - Mineral wool or fiberglass battening with armor plating Levels 4-8
- Face Skins: 14 gauge (cold rolled steel or A60 Galvannealed)
- Handing Design: Non-Handed (Handed optional)



- Closer Reinforcement (Optional): Only available on Levels 1-3. Closer reinforcement not necessary on levels 4-8 due to plating in construction requirements.
- Size Availability
 - Minimum 1'0" x 1'0"
 - Maximum 4'10" x 10'0"
- SDI 100 Level/Model: Level 4 Model 2
- Universal Standard/Heavy Weight Hinge: Levels 1, 2, and 3 are prepped for (3) 4-1/2" or 5" butt hinges up to 3476 nominal size opening. Over 3476 and Levels 4-8 (all sizes) are prepped for (4) 4-1/2" or 5" butt hinges or continuous hinge application.

FRAME


- Frame Thickness: Made to accommodate 14 gauge door - 2" rabbet (+/- 1/16")
- Gauges: 14 gauge only
- Stop: 5/8" standard
- Closer Reinforcement (Optional): 1-3/8" x 14" x 14 gauge plate
- Universal Standard/Heavy Weight Hinge: Frames shall have a 7 gauge steel hinge reinforcement plate, projection welded with provisions for 4-1/2" x 4-1/2" template hinges. Hinge plate is designed to be modified to accept a heavy weight hinge by removing spacer plate.

- Strike Prep: Frames shall have a 14 gauge steel strike reinforcement plate, extruded and formed to the equivalent of 10 gauge, projection welded with provisions for Universal ANSI A115.1 or ANSI A115.2 strike (4-7/8")
- Hinge Backset
 - Frame = 5/16"
 - Door = 1/4"
- Backbend: 7/16" (Single Return)
- Anchors: Level 1 only - Snap in universal anchor and masonry tee. All Levels - Masonry wire, Prepared Opening Anchors, and adjustable strap anchors.


- Double Heads: Double heads are undersized 1/16"
- Silencer Prep: 9/32" dia. holes shall be provided as standard on strike jambs and double headers, (3 per strike jamb and 2 per double head). Mutes are not supplied and must be ordered separately.
- Mortar Guards: Mortar guards of 26 gauge steel shall be welded to each hinge and strike reinforcement plate
- Profiles: Equal Rabbet, Unequal Rabbet, Single Rabbet not available.
- Handing: Frames are handed




Welded Corner Connection




Adjustable Strap




Corner Connection



Masonry Wire




Standard Sill Anchor



Prepared Opening Anchor



Level 2-3 BR Frame



Level 4, 5, 7 and 8 BR Frame



Level	No. of Shots		Ammunition	Grain	Min. Velocity	Results
	Min. Req'd	Tested				
1	3	19	9mm full metal copper jacket	124	1,256 fps	Pass
2	3	19	.357 Magnum	125	1,250 fps	Pass
3	3	19	.44 Magnum lead semi-wad cutter gas checked	240	1,350 fps	Pass
4	1	19	.30 caliber rifle lead core	180	2,540 fps	Pass
5	1	5	7.62mm rifle full metal jacket military ball	150	2,750 fps	Pass
6	5	5	9mm full metal jacket	124	1,400 fps	Pass
7	5	12	5.56mm rifle full metal jacket	55	3,080 fps	Pass
8	5	12	7.62mm rifle full metal jacket military ball	150	2,750 fps	Pass
Supplementary Shotgun	3	3	12 ga. Rifled lead slug	437	1,585 fps	Pass
	3	3	12 ga. 00 lead buckshot (12 pellets)	650	1,200 fps	Pass

Levels 4–8: All hardware and anchoring must be reviewed, due to required construction.

All door and frame assemblies tested in accordance with: UL 752-1995

SINGLES							
Level	Width	Height	Door	Frames - Single Return (14 Gauge)			
				5-3/4"	5-7/8" thru 8-3/4"	8-7/8" thru 14-3/4"	
1	Thru 3'0"	7'0"	\$3,376	\$765	\$897	\$1,024	\$1,170
		8'0"	\$3,714	\$851	\$970	\$1,094	\$1,241
		10'0"	\$4,026	\$1,045	\$1,208	\$1,337	\$1,485
	Over 3'0" – 4'0"	7'0"	\$3,728	\$782	\$912	\$1,033	\$1,179
		8'0"	\$3,981	\$865	\$985	\$1,103	\$1,250
		10'0"	\$4,292	\$1,060	\$1,225	\$1,344	\$1,491
	Over 4'0" – 4'10"	7'0"	\$7,369	\$855	\$984	\$1,105	\$1,252
		8'0"	\$7,729	\$942	\$1,057	\$1,177	\$1,323
		10'0"	\$8,040	\$1,134	\$1,296	\$1,417	\$1,565
	Thru 3'0"	7'0"	\$3,832	\$940	\$1,068	\$1,199	\$1,345
		8'0"	\$4,169	\$1,024	\$1,143	\$1,269	\$1,416
		10'0"	\$4,482	\$1,215	\$1,384	\$1,509	\$1,656
2-3	Over 3'0" – 4'0"	7'0"	\$4,184	\$955	\$1,088	\$1,206	\$1,353
		8'0"	\$4,436	\$1,041	\$1,160	\$1,275	\$1,422
		10'0"	\$4,747	\$1,235	\$1,398	\$1,517	\$1,666
	Over 4'0" – 4'10"	7'0"	\$7,824	\$1,029	\$1,157	\$1,280	\$1,426
		8'0"	\$8,184	\$1,115	\$1,230	\$1,350	\$1,498
		10'0"	\$8,495	\$1,308	\$1,469	\$1,591	\$1,740
	Thru 3'0"	7'0"	\$10,893	\$3,307	\$3,437	\$3,567	\$3,713
		8'0"	\$11,231	\$3,392	\$3,510	\$3,638	\$3,785
		10'0"	\$11,541	\$3,585	\$3,751	\$3,877	\$4,024
4 & 6	Over 3'0" – 4'0"	7'0"	\$11,246	\$3,323	\$3,455	\$3,573	\$3,720
		8'0"	\$11,498	\$3,403	\$3,528	\$3,644	\$3,791
		10'0"	\$23,899	\$3,602	\$3,764	\$3,885	\$4,032
	Over 4'0" – 4'10"	7'0"	\$14,886	\$3,397	\$3,527	\$3,647	\$3,796
		8'0"	\$15,247	\$3,482	\$3,598	\$3,717	\$3,866
		10'0"	\$29,280	\$3,675	\$3,836	\$3,959	\$4,107

SINGLES							
Level	Width	Height	Door	Frames - Single Return (14 Gauge)			
				5-3/4"	5-7/8" thru 8-3/4"	8-7/8" thru 14-3/4"	
5	Thru 3'0"	7'0"	\$12,032	\$3,307	\$3,437	\$3,567	\$3,713
		8'0"	\$12,371	\$3,392	\$3,510	\$3,638	\$3,785
		10'0"	\$17,300	\$3,585	\$3,751	\$3,877	\$4,024
	Over 3'0" – 4'0"	7'0"	\$12,385	\$3,323	\$3,455	\$3,573	\$3,720
		8'0"	\$12,637	\$3,403	\$3,528	\$3,644	\$3,791
		10'0"	\$23,899	\$3,602	\$3,764	\$3,885	\$4,032
	Over 4'0" – 4'10"	7'0"	\$16,025	\$3,397	\$3,527	\$3,647	\$3,796
		8'0"	\$16,385	\$3,482	\$3,598	\$3,717	\$3,866
		10'0"	\$29,280	\$3,675	\$3,836	\$3,959	\$4,107
	Thru 3'0"	7'0"	\$17,727	\$3,307	\$3,437	\$3,567	\$3,713
		8'0"	\$18,065	\$3,392	\$3,510	\$3,638	\$3,785
		10'0"	\$20,759	\$3,585	\$3,751	\$3,877	\$4,024
7-8	Over 3'0" – 4'0"	7'0"	\$18,080	\$3,323	\$3,455	\$3,573	\$3,720
		8'0"	\$18,332	\$3,403	\$3,528	\$3,644	\$3,791
		10'0"	\$23,899	\$3,602	\$3,764	\$3,885	\$4,032
	Over 4'0" – 4'10"	7'0"	\$21,719	\$3,397	\$3,527	\$3,647	\$3,796
		8'0"	\$22,080	\$3,482	\$3,598	\$3,717	\$3,866
		10'0"	\$29,280	\$3,675	\$3,836	\$3,959	\$4,107

Levels 4–8: All hardware and anchoring must be reviewed, due to required construction. 14 gauge doors over 4'0 available in GALV only.

DOUBLES					
Level	Width	Height	Frames - Single Or Double Return 14 Gauge		
			5-3/4"	5-7/8" thru 8-3/4"	8-7/8" thru 14-3/4"
1	Thru 6'0"	7'0"	\$873	\$1,006	\$1,132
		8'0"	\$970	\$1,094	\$1,213
		10'0"	\$1,200	\$1,339	\$1,458
	Over 6'0"-8'0"	7'0"	\$883	\$1,030	\$1,154
		8'0"	\$983	\$1,118	\$1,237
		10'0"	\$1,210	\$1,360	\$1,480
	Over 8'0"-10'0"	7'0"	\$903	\$1,060	\$1,179
		8'0"	\$1,000	\$1,145	\$1,265
		10'0"	\$1,231	\$1,389	\$1,508
2 - 3	Thru 6'0"	7'0"	\$1,046	\$1,181	\$1,304
		8'0"	\$1,143	\$1,269	\$1,389
		10'0"	\$1,373	\$1,510	\$1,632
	Over 6'0"-8'0"	7'0"	\$1,058	\$1,205	\$1,325
		8'0"	\$1,156	\$1,293	\$1,412
		10'0"	\$1,385	\$1,534	\$1,653
	Over 8'0"-10'0"	7'0"	\$1,076	\$1,235	\$1,478
		8'0"	\$1,176	\$1,320	\$1,563
		10'0"	\$1,404	\$1,563	\$1,807

Doubles available up to Level 3 maximum.

Frames are priced 14 gauge, CRS. Doors are priced 14 gauge, CRS.

STEEL TYPES		
Description	Door	Frame
Cold rolled steel	Included	Included
A60 Galvanized steel	\$111.00	\$61.00
G90 Galvanized steel (14 and 16 gauge only)	\$445.00	\$108.00

HINGE PREPARATIONS		
Description	Door	Frame
Special hinge locations	No charge	No charge
4-1/2" or 5" Universal hinge prep	No charge	No charge
Additional hinge prep (per hinge)	\$27.00	\$25.00
4" Template hinge prep (square corner only) (per hinge)	N/A	N/A
Anchor hinge prep (no drilling or tapping) (per hinge) (Level 1 only)	\$518.00	\$305.00
Electric hinge (Levels 1-3 only) ▪ Cutout in one hinge reinf. ▪ No junction box or conduit	\$27.00	\$25.00
Continuous hinge reinforcement (Levels 1-3 only)	\$94.00	\$88.00
Power transfer (no junction box or conduit)	\$145.00	\$111.00
8" Junction box welded in (Level 1 only)	N/A	\$34.00
14" Junction box welded in (Level 1 only)	N/A	\$34.00
10" Junction box welded in soffit	N/A	\$34.00

DOOR - LOCK/FRAME - STRIKE PREPARATIONS		
Description	Door	Frame
Standard lock (strike) at non-standard location	No charge	No charge
2-3/4" Lipped strike in lieu of 4-7/8"	N/A	No charge
Cylindrical dead lock (2-3/4" strike)	\$65.00	\$25.00
Mortise dead lock (3-1/2" strike)	\$65.00	\$25.00
Electric strike (no conduit/no junction box) (Level 1)	\$143.00	\$107.00
ASA Strike	\$63.00	No charge
Rim reinforcement only	\$54.00	\$33.00
Surface vertical rod reinforcement only (Level 1-3, Levels 4-8 N/A built in)	\$87.00	\$33.00
Concealed vertical rod (strike) (per prep) (Level 1)	\$648.00	N/A
Exit alarm reinforcement only (Level 1-3, Levels 4-8 N/A built in)	\$66.00	\$33.00
Push pull reinforcement (Level 1-3, Levels 4-8 N/A built in)	\$42.00	N/A

CLOSER PREPARATIONS		
Description	Door	Frame
Closer reinforcement (Level 1-3, Levels 4-8 N/A built in)	\$40.00	\$33.00

SPECIAL CONSTRUCTIONS		
Description	Door	Frame
Undercut - under 3/8" price next larger size	No charge	N/A
Inverted top channel (Levels 1-3 only)	No charge	N/A
Flush bottom channel (Levels 1-3 only)	No charge	N/A
Seal top or bottom channel and finish smooth each	\$150.00	N/A
Bondo filled edge (included)	N/A	N/A
Continuous welded edge	\$192.00	N/A
Beveled lock edge (1/8" in 2") N/A in 14 gauge and Inactive leafs with strike(s)	N/A	N/A
10 Gauge Hinge and 14 Gauge Lock Channels (DE Series - standard on 14 gauge door)	Included	N/A
Mail slot	N/A	N/A
Automatic door bottom (mortise type) (Level 1 only)	\$239.00	N/A
Mag switch/DPS - Hole only (Levels 1-3 only)	\$25.00	\$25.00
Mag switch/DPS Mortise prep and reinf. (no junction box)	N/A	\$97.00
Conduit/raceway - includes wire pull (Levels 1-3)	\$202.00	N/A

LABEL PREPARATIONS		
Description	Door	Frame
Mark numbers	No charge	No charge
UL Mylar Label - Level 1 only (standard unless specified otherwise)	\$22.00	\$24.00
UL Metal Label - Level 1 only	\$51.00	\$31.00
ITS/Warnock Hersey Metal label - Level 1 only	\$51.00	\$31.00

SPECIAL FINISH PREPARATIONS

Description	Door	Frame
Second coat of primer	N/A	N/A
Finish paint setup charge (never waived)	N/A	N/A
Finish paint	N/A	N/A
▪ Minimum quantity of 20 color ▪ Price includes full carton wrap		

DOUBLE SWING PREPARATION

Description	Door	Frame
Attaching astragal (includes bullet flat bar astragal, Levels 1-3 only, required)	\$691.00	N/A
Flush bolt prep (ANSI 115.4) (Levels 1-3 only)	\$101.00	\$63.00
Surface bolt reinforce only (Levels 1-3 only)	\$38.00	\$33.00
Open back strike	N/A	N/A

ANCHOR OPTIONS

Description	Door	Frame
Welded in prepared opening anchor (per anchor)	N/A	\$17.00
Welded in anchor (per anchor)	N/A	\$7.50
Punch and dimple only (per prep)	N/A	\$6.00

Prepared Opening Frames up 7'1" require 8 anchors (max 8-3/4" depth). Over 7'2" thru 10'0" require 10 (max 8-3/4" depth). Frames over 8-3/4" receive double the quantity and price.

FRAME CONSTRUCTION

Description	Door	Frame
Unit bundle (3pc)	N/A	N/A
Standard face weld (3pc)	N/A	Included
Full profile weld (3pc)	N/A	\$220.00

FRAME PROFILE OPTIONS

Description	Door	Frame
Single rabbet	N/A	N/A
4" Face heads (through 4'0")	N/A	\$64.00
4" Face Heads (over 4'0")	N/A	\$89.00
Non-standard face - per frame	N/A	\$79.00

Non-standard face is Level 1 only.

GLASS KIT OPTIONS

Up to and including Level 3 only	Vision/ Narrow Lite up to 100 inch ²	Half Glass over 100 inch ² up to 800 inch ²	Full Glass over 800 inch ²
Anemostat BR7 Kit	\$1,784.00	\$2,922.00	N/A

Anemostat BR7 Kit is kit only, approved glass by others.

See [Engineering Section](#) for further options and/or details.

PALADIN™ SERIES**1-3/4" Tornado Resistant doors and frames**

DF Tornado doors and frames are no longer available through Republic. They are now processed and fulfilled through Steelcraft as Paladin PW doors and FP frames.

- Send orders directly to SteelcraftOrderEntry@allegion.com or refer to [Working with Steelcraft](#).
- Purchase Orders sent to Republic will be forwarded to Steelcraft order entry for processing through Steelcraft as Paladin.

For product information and downloads, please visit: [Steelcraft's Paladin PW Series](#).



HUR(I) DL/DE SERIES IMPACT DP/DL/DE SERIES NON-IMPACT

Hurricane and wind resistance

Hurricane Impact assemblies require specially constructed DL/DE doors identified as HUR(I) prefix.


Non-Impact/E330 labeled openings may also use standard DP/DL/DE doors.

See DP/DL/DE pages for pricing and options.

- Door Thickness: 1-3/4" (14 gauge = 1-13/16")
- Actual Door Size: Door undersized from nominal by 1/4" in width and 1/2" in height. Std undercut 3/8" or per listing threshold requirements.
- Core: Honeycomb Core. Optional Polystyrene, Stiffened, Polyurethane (non-fire label), Temp Rise
- Hinge Rail and Reinforcement: 10 gauge hinge reinforcements. Hinge edge is non-beveled and reinforced with a continuous 16 gauge steel channel projection welded at a maximum of 5" OC (optional 10 ga - DE Series).
- Lock Rail: Lock edge is non-beveled (bevel 1/8" in 2" option) and reinforced with hurricane channel and a continuous 16 gauge steel channel projection welded at a maximum of 5" OC (optional 14 gauge - DE Series).
- Top Channel: Top channel is a flush 16 gauge steel channel, projection welded at a max 2-1/2" OC

- Bottom Channel: Bottom channel is an inverted 16 gauge steel channel, projection welded max 2-1/2" OC
- Face Skins: HUR(I) 16 gauge or 14 gauge A60 galvannealed steel (G90 Galv option by special request)
- See FBC and TDI Third Party (FBC) listings, RepublicDoor.com, hurricane section ordering tools for more information on approved offerings and ordering
- Closer Reinforcement: 14 Gauge 18" x 6" (Optional 12 Gauge)
- Size Availability
 - Max. 4'0" x 8'0" (Singles)
 - Max. 8'0" x 8'0" (Pairs)
- SDI 100 - Grade/Model for HUR(I) Impact: Levels 3-4 and Models 1 and 2 (Extra Heavy Duty and Maximum Duty Commercial and Institutional)

- Fire Label Range: 20 minute through 3 hour/ Underwriters Laboratory or Warnock Hersey
- Windstorm Labels: FBC labels supporting FBC and TDI
 - FBC Impact
 - FBC E330 Non-Impact (See standard DP/ DL/DE product pricing)
- Edge Seam Construction: Visible seam is standard. Continuously welded seamless or intermittently welded seamless available. (Options)
- Universal Standard/Heavy Weight Hinge: Hinge fillers are used allowing for easy modification from heavy to standard weight hinge prep
- Handing Design: Non-handed standard (Optional handed)




Hurricane impact assemblies include extra heavy duty windstorm resistant door construction per listing approvals.


Standard frames are used with anchors/locations and details as specified in listing approvals.

Assembly with standard Honeycomb (optional cores available).


Refer to Listings and COACH validations for all available door, frame and hardware options.




Flush Top




Door Hinge Prep




Cyl Prep
(E330 shown)



Honeycomb Core



Mortise Prep
(E330 shown)



Inverted
Bottom Channel

ORDERING FBC AND TDI APPROVED REPUBLIC HURRICANE PRODUCTS

Approved Products and Labels


- FBC Approved assemblies with Allegion Hardware (link below)
 - Impact Labeled Hurricane Doors: HUR(I) - DL16/DE14
 - Non-Impact E330 Labeled Doors: DP/DL/DE standard series
 - Impact or Non-Impact Frames and Elevations: ME/SE standard series with approved anchors
 - See next pages for FBC approved product pricing and offering ranges
- TDI Approved assemblies with Allegion hardware
 - Order as FBC labeled products supported by TDI's Third-Party Evaluation Reports
- UL and WHI fire labels available up to 3 hours

Go to RepublicDoor.com, hurricane section, for downloadable tools and helpful links, including:


- COACH: FBC Order Assistant and Order Form Generation tool (verify with active public listing)
- Approval LOOKUPs: Filterable summary of FBC
- Anchor LOOKUP: Anchor types and quantities for FBC
- Public Listing Links to [FBC](#) and [TDI Door Assemblies](#), and [TDI Store Front Systems](#)
- Code Requirements and additional information

Note: Please verify that you have the latest versions of the Hurricane Order Form (COACH), Lookup Tool, Approvals/install instructions, and Price Book before ordering and installing. The Authority Having Jurisdiction is the final authority in issues related to the installation and use of any building products. While we have tried to maintain accuracy in product literature and tools, Allegion is not responsible for errors and omissions, and is not responsible for verifying that the correct products for your opening are ordered or installed correctly in the field. This is the responsibility of the contractor and their architects and engineers.


SDI CLASSIFICATIONS					
Grade		Model	Construction	Republic Series	
II	Physical Performance Level A 1-3/4" (44) Only Heavy Duty Minimum Gauge = 18		1	Full Flush-Non-Impact	DP 418, DL 418, DE 418
			2	Seamless-Non-Impact	DL 418, DE 418
III	Physical Performance Level A 1-3/4" (44) Only Extra-Heavy Duty Minimum Gauge = 16		1	Full Flush-Non-Impact	DL 416, DE 416
			2	Seamless-Non-Impact	DL 416, DE 416
			1	Flush-Impact	HUR(I) DL 416
			2	Seamless-Impact	HUR(I) DL 416
IV	Physical Performance Level A 1-3/4" (44) Only Extra-Heavy Duty Minimum Gauge = 14		1	Full Flush-Non-Impact	DE 414
			2	Seamless-Non-Impact	DE 414
			1	Flush-Impact	HUR(I) DE 414
			2	Seamless-Impact	HUR(I) DE 414



Paired doors without astragal



NOTE – See standard embossed doors for "E330 only" door pricing. Other emboss patterns available for impact with 50-door MOQ. Call for availability and pricing.



Paired doors with "Z" astragal



HUR(I) Impact Door options and pricing:

See standard door pages for Non-Impact/E330

HONEYCOMB HUR(I) - DL/DE IMPACT DOORS¹				
Door Height	Door Width	DL16	DE14	DL16-Emb²
Up to 6'8"	1'6" - 2'8"	\$1,450	\$1,751	N/A
	Over 2'8" - 3'0"	\$1,527	\$1,861	\$1,854
	Over 3'0" - 3'6"	\$1,676	\$2,038	N/A
	Over 3'6" - 4'0"	\$1,782	\$2,112	N/A
Up to 7'0"	1'6" thru 2'8"	\$1,495	\$1,846	N/A
	Over 2'8" - 3'0"	\$1,555	\$1,941	\$1,890
	Over 3'0" - 3'6"	\$1,737	\$2,112	N/A
	Over 3'6" - 4'0"	\$1,827	\$2,193	N/A
Up to 7'2"	1'6" - 2'8"	\$1,527	\$1,879	N/A
	Over 2'8" - 3'0"	\$1,587	\$1,973	N/A
	Over 3'0" - 3'6"	\$1,754	\$2,159	N/A
	Over 3'6" - 4'0"	\$1,844	\$2,255	N/A
Up to 8'0"	2'8" - 3'0"	\$1,946	\$2,461	\$2,451
	Over 3'0" - 3'6"	\$2,096	\$2,572	N/A
	Over 3'6" - 4'0"	\$2,171	\$2,644	N/A

1. Price includes FBC Impact label, Fasseal Door Sweep, A60 Steel, CH/MOL, 4-1/2" Hinges.
2. Other emboss patterns available with 50 door MOQ and longer lead times. Call for availability and pricing.

HUR(I) - DL/DE IMPACT LABELED HURRICANE DOORS

- Option Ranges based on specific configurations in Approvals
- Inward and Outward Design Pressures available up to 50-170 PSF
- Max opening 4'0" x 8'0" single and 8'0" x 8'0" pair
- Max exposed glass based on hardware 34.25" w x 74.5" h or 24" w x 64" h or 100" sq limit using standard 3" w x 33" h, 4" w x 20" h, or 5" w x 20" h (70 max pressure per glass trim)
- Max louver: Impact openings 35.78" w x 76.03" h (cylinder and mortise locks only)

DP/DL/DE NON-IMPACT/E330 LABELED DOORS

- See [Engineering Section](#) for pricing. E330 label to standard DP18, DL 16/18, DE 14/16/18
- Inward and outward design pressures available up to 40-60 PSF
- Max opening 4'0" x 8'0" single and 8'0" x 8'0" pair
- Max exposed glass 34.25" w x 74.5" h (70 max pressure per trim)
- See DP/DL/DE standard series pages for pricing and options with E330 labels

HURRICANE FRAMES FOR IMPACT OR NON-IMPACT E330 OPENINGS

- See standard ME14/16 and SE12/14/16 product/pricing with options as defined in FBC/TDI approvals
 - Typ exterior 14 gauge ME used with 16 gauge doors
 - Typ interior 16 gauge ME used with 18 gauge doors
- Max door opening 8'0" x 8'0"
- KD or Welded
- Jamb depths 5-3/4" thru 14-3/4"
- 2" face jambs, 4" face head option
- Elevation borrowed lite/storefronts calculated (see listing). Max exposed glass 54.75" w x 80.75" h or 34.75" w x 116.75" h
- Anchor quantity, type, and locations vary per approval

See ME and SE pages for pricing and options for both Impact and Non-impact E330 labels.

INSULATED CORES	DOOR
Honeycomb	Included
Polystyrene	\$41.00
Polystyrene embossed	See chart
Polyurethane	\$206.00
Steel stiffened (20 gauge stiffeners with fiberglass insulation, standard)	\$319.00
Steel stiffened (20 gauge stiffeners with polystyrene insulation)	\$398.00
Temperature rise (250° mineral fiberboard)	\$1,087.00

STEEL TYPES	DOOR
A60 Galvanized steel	Included
G90 Galvanized steel (14 and 16 gauge only) upon request	\$445.00

HINGE PREPARATIONS	DOOR
Special hinge locations	No charge
4-1/2" Universal hinge prep (1) prep for every 30" in height	No charge
Additional hinge prep (per hinge)	\$27.00
5" Universal hinge prep (per hinge)	No charge
Electric hinge <ul style="list-style-type: none"> ▪ No conduit, no wiring included ▪ One 1/2" dia. hole in one hinge reinf. 	\$27.00
Surface mounted hinges (reinforced only)	N/A
Continuous hinge reinforcement	\$94.00
Special backset (per hinge)	N/A
Power transfer <ul style="list-style-type: none"> ▪ No junction box or conduit, no wiring ▪ Cutout with reinforcement/tap plate(s) 	\$145.00

LOCK PREPARATIONS	DOOR
Special lock location	No charge
Special lock backset up to 5"	No charge
Sectional trim prep (mortise lock with function holes)	No charge
Cylindrical dead lock - Gov't 160 or 161 prep	\$65.00
Mortise dead lock - Gov't 86 mortise lock prep	\$65.00
Rim reinforcement only	\$54.00
Rim reinforcement with function prep	\$60.00
Mortise exit device reinforcement only	\$39.00
Mortise exit device reinforcement with function prep	\$95.00
Surface vertical rod reinforcement only	\$87.00
Surface vertical rod reinforcement with function prep	\$105.00
Concealed vertical rod	\$648.00
Exit alarm reinforcement only	\$66.00
Inset exit device (14 and 16 gauge doors only)	N/A
Push pull reinforcement	N/A

Notes:

Refer to Republic FBC/TDI Hurricane Listings to verify approved options prior to ordering.
(Reference COACH and LOOKUP tools for assistance)

CLOSER PREPARATIONS		DOOR
Closer reinforcement		\$40.00
Concealed overhead door closer, holder or stop		N/A

SPECIAL CONSTRUCTIONS		DOOR
UC - less than 3/8", price as next larger size		No charge
Inverted top channel		No charge
Flush bottom channel		No charge
Dutch door (4) 4.5" hinge preps x (1) 161 lock prep		N/A
Unifit hinge channel		N/A
Seal top or bottom channel and finish smooth each		\$150.00
Mag switch/DPS - Hole only		\$25.00
Mag switch/DPS - Prep and reinf.		\$131.00
Bondo filled edge		\$128.00
Continuous welded edge (N/A in 20 gauge)		\$192.00
Beveled lock edge (1/8" in 2") N/A in 14 gauge and Inactive leafs with strike(s)		\$23.00
10 Gauge hinge/14 gauge lock channels DE Series (standard on 14 gauge door)		\$166.00
Door viewer		\$32.00
Mail slot		N/A
Automatic door bottom (mortise type)		N/A
Conduit/raceway - includes wire pull (available with electric hinge or power transfer options)		\$202.00

SPECIAL FINISH PREPARATIONS		DOOR
Second coat of primer		\$132.00
Finish paint setup charge (never waived)		\$1,433.00
Finish paint		\$360.00
▪ Minimum quantity of 20 per color		
▪ Price includes full carton wrap		

LABEL PREPARATIONS		DOOR
Mark numbers		No charge
U.L. Mylar fire label (standard unless specified otherwise)		\$22.00
U.L. Metal fire label		\$51.00
Warnock Hersey Metal fire label		\$51.00
Hurricane FBC Label on HUR(I) - DL/DE		No charge
Hurricane E330/Non-Impact label on standard DP/DL/DE		\$51.00
Hurricane TDI: Use FBC label on HUR(I) - DL/DE		No charge
Hurricane/Tornado FBC EHPA label	Use Paladin™ Series by Steelcraft	

INACTIVE LEAF PREPARATIONS		DOOR
Flush bolt embossed top/bottom channel (E330 only)		No charge
Cylindrical (2-3/4") dead lock strike		\$65.00
Electric strike (no conduit)		N/A
ASA Strike only		\$63.00
Attaching astragal (includes astragal)		\$116.00
Flush bolt prep (ANSI 115.4) - E330 only		\$101.00
Surface bolt reinforce only		\$38.00
Open back strike		N/A

GLASS / LOUVER INSERT OPTIONS			
	Vision/ Narrow Lite up to 100 inch²	Half Glass over 100 inch up to 800 inch²	Full Glass over 800 inch²
*Cutout with reinforcement	\$317	\$419	\$500
Glass pocket add (other than 1/4")	\$221	\$221	\$221
Hurricane approved light kits - Air louvers VLFIGHRC or VLFEZHRC (add to Cutout price above)	\$1,744	\$3,160	\$3,160
Hurricane approved louver insert - Air louvers 1500 (add to Cutout price above) (Call for other sizes)	\$797 (10x10)	\$1,568 (up to 24x24)	\$3,677 (up to 24x60)

*For 45–90 minute fire rated glass, order Cutout with reinforcement and approved trim and glass by others as shown in Glazing Details of FBC listings FL12400.5 Glazed Singles and FL12400.3 Glazed Doubles. See NGP Types F and 2, 1-1/16" glass (45 min), NGP Types E and 3, 1-7/16" glass (60 min), and NGP Types E and 4, 1-13/16" glass (90 min).

Note: Refer to listings for availability

Bullet Resistant Options
(see [Specialty Section](#))

Refer to Republic FBC/TDI Hurricane Listings to verify approved options prior to ordering.
(Reference COACH and LOOKUP tools for assistance)

SOUND TRANSMISSION CONTROL (STC) ECO

Specialty

Refer to technical data sheet on page 16

SOUND TRANSMISSION CONTROL (STC) 40, 42, 43 and 47 DOORS

- Thickness: 1-3/4" (+/- 1/16")
- Actual Door Size: Door undersized from nominal by 1/4" in width and 1/2" in height. Standard undercut is 3/8". Undercut contingent on threshold.
- Hinge Rail and Reinforcement: Hinge edge is non-beveled and reinforced with a continuous 16 gauge steel channel projection welded to each skin at a maximum of 5" on center. Hinge channels have an additional 9 gauge reinforcement at each hinge location, providing over 3/16" reinforcement (Backset 1/4")
- Lock Rail: Lock edge is non-beveled and reinforced with a continuous 16 gauge steel channel. 16 gauge reinforcements for mortised or cylindrical locks are of an integral type in accordance with ANSI A115 standards.
- Top Channel: Top channel is flush 16 gauge channel, projection welded at a maximum of 2-1/2" on center
- Bottom Channel: Bottom channel is 16 gauge flush, projection welded at a maximum of 2-1/2" on center
- Core: Proprietary Sound Core
- Face Skin: 16 gauge, Cold Roll Steel, A60 Galvannealed or G90 Galvanized
- Closer Reinforcement (Required): 14 gauge standard
- Size Availability: Maximum 4'0" x 8'0"
- SDI 100 Grade/Model: Grade 3/Model 1 – 2 (Physical Performance Level A)
- Edge Seam Construction: Visible edge seam standard. Optional - Intermittently welded or Continuously welded edge seam.
- Universal Standard/Heavy Weight Hinge: Hinge fillers are used allowing for an easy modification from standard to heavy weight hinge Prep: 4-1/2" hinges standard.
- Handing Design: Non-Handed standard/Optional Handed design

STC 40 – 6 PANEL EMBOSSED SOUND TRANSMISSION CONTROL (STC) 40 DOORS

- Thickness: 1-3/4" (+/- 1/16")
- Hinge Rail and Reinforcement: Hinge edge is non-beveled and reinforced with a continuous 16 gauge steel channel projection welded to each skin at a maximum of 5" on center. Hinge channels have an additional 9 gauge reinforcement at each hinge location, providing over 3/16" reinforcement (Backset 1/4")
- Lock Rail: Lock edge is non-beveled and reinforced with a continuous 16 gauge steel channel. 16 gauge reinforcements for mortised or cylindrical locks are of an integral type in accordance with ANSI A115 standards.
- Top Channel: Top channel is flush 16 gauge channel, projection welded at a maximum of 2-1/2" on center
- Bottom Channel: Bottom channel is 16 gauge flush, projection welded at a maximum of 2-1/2" on center
- Core: 250° Temperature Rise core
- Face Skin: 16 gauge, A40 Galvannealed
- Closer Reinforcement (Optional): 14 gauge standard
- Size Availability: Maximum 3'6" x 8'0"
- SDI 100 Grade/Model: Grade 3/Model 1 – 2 (Physical Performance Level A)
- Edge Seam Construction: Visible edge seam, standard. Optional Intermittently or Continuous welded edge seam
- Universal Standard/Heavy Weight Hinge: Hinge fillers are used allowing for an easy modification from standard to heavy weight hinge Prep: 4-1/2" hinges standard
- Handing Design: Non-Handed standard/Optional Handed design

SECTION 08348 ACOUSTIC STEEL DOOR & FRAME ASSEMBLY



PART 1 - GENERAL		PART 2 - PRODUCTS	
Quality Assurance		Materials	
Sound Rating: Certify that the construction is identical to the Sound Transmission Classification (STC) assembly tested at an independent acoustical laboratory qualified under NVLAP by the National Institute for Science and Technology (NIST) according to ASTM E90 and that the STC rating according to ASTM E413 is not less than that specified or scheduled. Minimum STC rating shall be one of the following: 40, 42, 43, 47.		<ul style="list-style-type: none"> ▪ All steels used to manufacture doors, frames, anchors and accessories shall be in accordance with SDI-100/ANSI A250.8. ▪ Door Core shall be manufacturer's proprietary standard core to achieve specified ratings. ▪ Shop primer shall be manufacturer's standard rust inhibitive baked on or air dried shop primer. ▪ Door seals shall be manufacturer's standard sound seals. ▪ Hardware shall be manufacturer's standard seals, gasketing and threshold (when required). 	
Warranty		Fabrication	
Material and workmanship shall be warranted by manufacturer for a period of one (1) year from the date of shipment. Warranty shall apply to replacement or retrofit of product only.		<ul style="list-style-type: none"> ▪ Doors shall be minimum 16 gauge (STC 40, 42, 43 and 47), 1-3/4" thick, without visible joints on exposed faces. Reinforce top and bottom with "flush" steel channels of not less than 16 gauge. ▪ Door core shall be proprietary acoustic composite core as tested by manufacturer to meet specified STC rating. ▪ Frames shall be minimum 16 gauge, face welded and ground smooth construction or KD frames on STC 40 or 42 only. Provide frames with minimum of three anchors per jamb suitable for adjoining wall construction. Provide anchors of not less than 0.042" in thickness or 0.167" diameter wire. ▪ All frames shall be fully prepared for mortised hardware and reinforced only for surface mounted hardware. Drilling and/or tapping shall be completed by others. ▪ Acoustical Seals shall be manufactured by Zero International or Pemko. 	
Approved Manufacturers			
Republic Doors and Frames 155 Republic Drive McKenzie TN 38201 Phone: 800-733-3667 Fax: 800-723-6677			

INSTALLATION INSTRUCTIONS FOR ACOUSTIC GASKETS

Republic's tested STC system included: R-564 threshold, R-485 head and jamb seals, R-119 spring bronze head and jamb seals.

1. The R-119 spring bronze should be installed on the bottom of the door before hanging.
2. Install the R-564 threshold to suit floor condition. Caulk round the bottom of threshold along with the entire perimeter of frame and at meeting edges of threshold and frame.
3. Close the door and measure the frame opening width and height. Install the R-485 head piece first (trim as necessary). Place the piece against the face of the door, making gentle contact between the "rubber extrusion" seal and the door, then fasten in place. Place the hinge side seal against the face of the door, making gentle contact between the "rubber extrusion" seal and the door, then fasten in place. Place the strike side seal against the face of the door, making gentle contact between the rubber extrusion seal and the door, then fasten in place.
4. Install the R-119, head piece first, then the hinge side and finally the lock side using the pressure sensitive tape to fasten the spring bronze to the frame.
5. Check operation of the door after each piece of material is installed to make sure that no binding is taking place.

SOUND TRANSMISSION CONTROL (STC) 40, 42, 43 and 47 DOORS DL Series Sound Transmission Control (STC) Doors shall be as manufactured or furnished by Republic Doors and Frames, McKenzie, Tennessee 38201.



SINGLES - UNIVERSAL X 7/16" SINGLE RETURN											
Flush				16 Gauge				14 Gauge			
STC	Width	Height	Door	5-3/4"	5-7/8" thru 8-3/4"	8-7/8" thru 14-3/4"	14-7/8" thru 20"	5-3/4"	5-7/8" thru 8-3/4"	8-7/8" thru 14-3/4"	14-7/8" thru 20"
42	2'0" - 3'0"	7'0"	\$2,415	\$445	\$561	\$673	\$820	\$520	\$648	\$771	\$915
	Over 3'0" - 4'0"		\$2,803	\$461	\$568	\$683	\$828	\$536	\$664	\$779	\$921
43 or 47	Thru 3'0"		\$3,303	\$445	\$561	\$673	\$820	\$520	\$648	\$771	\$915
	Over 3'0" - 4'0"		\$3,664	\$461	\$568	\$683	\$828	\$536	\$664	\$779	\$921
42	Thru 3'0"	8'0"	\$2,790	\$520	\$624	\$734	\$882	\$604	\$718	\$771	\$985
	Over 3'0" - 4'0"		\$3,089	\$535	\$628	\$742	\$889	\$620	\$734	\$779	\$991
43 or 47	Thru 3'0"		\$3,646	\$520	\$561	\$734	\$882	\$604	\$718	\$771	\$985
	Over 3'0" - 4'0"		\$3,950	\$535	\$628	\$742	\$889	\$620	\$734	\$779	\$991

STC Frames are priced 7/16" Single Return, CRS, Face Welded construction. Frames must be fully grouted or filled with sound deadening insulation (by others.) Doors are priced 16 gauge, CRS, Steel Stiffened core and 3/8" undercut. STC 42 units available with knock down frame, deduct \$58.00 per frame from above price, and are honeycomb core as standard.

SINGLES - 1/2" DOUBLE RETURN											
Flush				16 Gauge				14 Gauge			
STC	Width	Height	Door	5-7/8"	6" thru 8-1/4"	8-3/8" thru 13-7/8"	14" thru 20"	5-7/8"	6" thru 8-1/4"	8-3/8" thru 13-7/8"	14" thru 20"
42	2'0" - 3'0"	7'0"	\$2,415	\$460	\$609	\$731	\$893	\$562	\$705	\$840	\$997
	Over 3'0" - 4'0"		\$2,803	\$474	\$616	\$737	\$903	\$580	\$719	\$847	\$1,005
43 or 47	Thru 3'0"		\$3,303	\$460	\$609	\$731	\$893	\$562	\$705	\$840	\$997
	Over 3'0" - 4'0"		\$3,664	\$474	\$616	\$737	\$903	\$580	\$719	\$847	\$1,005
42	Thru 3'0"	8'0"	\$2,790	\$544	\$675	\$798	\$958	\$653	\$781	\$915	\$1,072
	Over 3'0" - 4'0"		\$3,089	\$559	\$683	\$805	\$969	\$670	\$797	\$921	\$1,080
43 or 47	Thru 3'0"		\$3,646	\$544	\$675	\$798	\$958	\$653	\$781	\$915	\$1,072
	Over 3'0" - 4'0"		\$3,950	\$559	\$683	\$805	\$969	\$670	\$797	\$921	\$1,080

1. STC Frames are priced 1/2" Double Return, CRS, Face Welded construction. Frames must be fully grouted or filled with sound deadening insulation (by others.) Doors are priced 16 gauge, CRS, Steel Stiffened core and 3/8" undercut.
2. STC 42 units available with knock down frame, deduct \$58.00 per frame from above price, and are honeycomb core as standard.
3. STC 42 to 47 Hardware Package (Included in price)

SINGLE (EMBOSSED 6 PANEL)			
STC	Width	Height	Door
40	Thru 3'0"	7'0"	\$3,334
	Over 3'0" - 3'6"		\$3,466
40	Thru 3'0"	8'0"	\$3,586
	Over 3'0" - 3'6"		\$3,747

STC 40 EMBOSSED 6 PANEL NOTES
Temperature Rise core included in price
Does not require or include hardware package
Standard 3/4" undercut

Testing and Qualifications:

All door systems tested in accordance with:

- ASTM E 90-04
- ASTM E 413-04
- ASTM E 1332-90
- ASTM E 2235-04

Testing was performed by:

Architectural Testing Inc. and
Riverbank Acoustical Laboratories

- Doors are available from STC 33 to STC 47
- Standard hollow metal frames (min. 5-3/4" frame depth) - welded. KD available on 40 and 42.
- SDI Level 3 - Maximum Duty - Performance Level A
- Fire rated available 40, 42 only
- Sound resistant septum (proprietary construction)
- All doors tested in fully operable conditions

STEEL TYPES		
Description	Door	Frame
Cold rolled steel	Included	Included
A60 Galvanized steel	\$111.00	\$61.00
G90 Galvanized steel (14 and 16 gauge only)	\$445.00	\$108.00

LABEL PREPARATIONS		
Description	Door	Frame
Mark numbers	No charge	No charge
U.L. Metal Fire label ¹	\$51.00	\$31.00
ITS/Warnock Hersey Metal Fire label ¹	\$51.00	\$31.00

1. STC 40 and 42 only.

HINGE PREPARATIONS		
Description	Door	Frame
Special hinge locations	No charge	No charge
4-1/2" or 5" Universal hinge prep	No charge	No charge
Additional hinge prep (per hinge)	\$27.00	\$25.00
Electric hinge	\$27.00	\$25.00
▪ Cutout in one hinge reinf. ▪ No junction box or conduit		
Power transfer (no junction box or conduit)	\$145.00	\$111.00
8" Junction box welded in	N/A	\$34.00
10" Junction box welded in soffit	N/A	\$34.00
14" Junction box welded in soffit	N/A	\$34.00

CLOSER PREPARATIONS		
Description	Door	Frame
Closer reinforcement	\$40.00	\$33.00
Concealed overhead door closer, holder or stop	\$394.00	\$307.00

DOOR - LOCK/FRAME - STRIKE PREPARATIONS		
Description	Door	Frame
Standard lock (strike) at non-standard location	No charge	No charge
Cylindrical dead lock (2-3/4" strike)	\$65.00	\$25.00
Mortise dead lock (3-1/2" strike)	\$65.00	\$25.00
Electric strike (no junction box or conduit)	\$143.00	\$107.00
Rim reinforcement only ¹	\$54.00	\$33.00
Rim reinforcement with function prep	\$60.00	N/A
Mortise exit device reinforcement with function prep	\$95.00	N/A
Surface vertical rod reinforcement only ¹	\$87.00	\$33.00
Concealed vertical rod (strike) (per prep)	\$648.00	N/A
Exit alarm reinforcement only ¹	\$66.00	\$33.00

1. Republic Tested Acoustical Systems: tested with standard hardware applications. Surface applied hardware not recommended due to possible interference with seals and gaskets. Any break or tear in seals and gaskets may affect performance.

FRAME PROFILE OPTIONS		
Description	Door	Frame
Single rabbet (minimum depth on STC is 5-3/4")	N/A	No charge
4" Face heads (through 4'0")	N/A	\$64.00
4" Face heads (over 4'0")	N/A	\$89.00

See [Engineering Section](#) for further options and/or details.

SPECIAL FINISH		
Description	Door	Frame
Second coat of primer	\$132.00	\$123.00
Finish paint setup charge	\$1,433.00	\$1,433.00
Finish paint	\$360.00	\$360.00
▪ Minimum quantity 20 doors or 20 (3pc) frames per color		
▪ Price includes full carton wrap		

ANCHOR OPTIONS		
Description	Door	Frame
Welded in prepared opening anchor (per anchor)	N/A	\$17.00
Welded in anchor (per anchor)	N/A	\$7.50
Punch and dimple only (per prep)	N/A	\$6.00

FRAME CONSTRUCTION		
Description	Door	Frame
Unit bundle (3pc)	N/A	\$7.00
Standard face weld (3pc)	N/A	Included
Full profile weld (3pc)	N/A	\$220.00

SPECIAL CONSTRUCTIONS		
Description	Door	Frame
10 Gauge hinge and 14 gauge lock channels	\$166.00	N/A
Seal top or bottom channel and finish smooth each	\$150.00	N/A
Mag switch/DPS - Hole only	\$25.00	\$25.00
Mag switch/DPS - Prep and reinf. (no junction box)	\$131.00	\$97.00
Bondo filled edge	\$128.00	N/A
Continuous welded edge	\$192.00	N/A
Beveled lock edge (1/8" in 2")	\$23.00	N/A
Door viewer	\$32.00	N/A
Conduit/raceway - includes wire pull	\$202.00	N/A

DOOR TEST PERFORMANCE CHARACTERISTICS PER ASTM E90 & E413																		
	Transmission Loss in db/Hertz																	
STC	100	125	160	200	250	315	400	500	630	800	1000	1250	1600	2000	2500	3150	4000	5000
38	26	23	27	33	36	35	34	34	39	41	42	44	45	47	45	45	45	45
42	32	28	32	36	35	37	36	38	38	40	42	43	44	45	49	54	56	54

SOUND TRANSMISSION CONTROL (STC) 48 - 50 - 52 AND STC 47 PAIRS

Specialty

Refer to technical data sheet on page 16

SOUND TRANSMISSION CONTROL (STC) 48

- Thickness: 1-3/4" (+/- 1/16")
- Actual Door Size: Door undersized from nominal by 1/4" in width and 3/8" in height. Standard undercut is 1/4". Undercut is contingent on threshold.
- Hinge Rail and Reinforcement: Hinge edge is non-beveled and reinforced with a continuous 16 gauge steel channel projection welded to each skin at a maximum of 5" on center. Hinge channels have an additional 9 gauge reinforcement at each hinge location, providing over 3/16" reinforcement (Backset 1/4")
- Core: Special Sound Core
- Closer Reinforcement (Req'd): 14 gauge std

- Lock Rail: Lock edge is non-beveled and reinforced with a continuous 16 gauge steel channel. 16 gauge reinforcements for mortised or cylindrical locks are of an integral type in accordance with ANSI A115 standards.
- Top Channel: Top channel is flush 16 gauge channel, projection welded at a maximum of 2-1/2" on center
- Bottom Channel: Bottom channel is 16 gauge flush, projection welded at a maximum of 2-1/2" on center
- Face Skin: 16 gauge, Cold Roll Steel, A60 Galvanneal or G90 Galvanized
- Size Availability: Maximum 4'0" x 8'0"

- SDI 100 Grade/Model: Grade 3/Model 2 (Physical Performance Level A)
- Edge Seam Construction: Intermittently welded edge seam (Optional - Continuous welded edge seam)
- Universal Standard/Heavy Weight Hinge: Hinge fillers are used allowing for an easy modification from standard to heavy weight hinge Prep: 5" hinges standard
- Handing Design: Non-Handed standard/Optional Handed design

SOUND TRANSMISSION CONTROL (STC) 50 and 52

- Thickness: 1-13/16" (+/- 1/16")
- Actual Door Size: Door undersized from nominal by 1/4" in width and 3/8" in height. Standard undercut is 1/4". Undercut is contingent on threshold.
- Hinge Rail and Reinforcement: Hinge edge is non-beveled and reinforced with a continuous 10 gauge steel channel projection welded to each skin at a maximum of 5" on center.
- Core: Special Sound Core

- Lock Rail: Lock edge is non-beveled and reinforced with a continuous 14 gauge steel channel projection welded at a maximum of 5" on center.
- Top Channel: Top channel is flush 16 gauge channel, projection welded at a maximum of 2-1/2" on center
- Bottom Channel: Bottom channel is 16 gauge flush, projection welded at a maximum of 2-1/2" on center

- Face Skin: 14 gauge, Cold Roll Steel, A60 Galvanneal or G90 Galvanized
- Closer Reinforcement (Req'd): 14 gauge std
- Size Availability: Maximum 4'0" x 8'0"
- SDI 100 Grade/Model: Grade 4/Model 2 (Physical Performance Level A)
- Edge Seam Construction: Intermittently welded edge seam standard. (Optional - continuous welded edge seam)

Note: STC Pairs available - Maximum rating 47



SECTION 08348 ACOUSTIC STEEL DOOR & FRAME ASSEMBLY

PART 1 - GENERAL		PART 2 - PRODUCTS
Quality Assurance	Materials	
Sound Rating: Certify that the construction is identical to the Sound Transmission Classification (STC) assembly tested at an independent acoustical laboratory qualified under NVLAP by the National Institute for Science and Technology (NIST) according to ASTM E90 and that the STC rating according to ASTM E413 is not less than that specified or scheduled. Minimum STC rating shall be one of the following: 48, 50, 52.	<ul style="list-style-type: none"> ▪ All steels used to manufacture doors, frames, anchors and accessories shall be in accordance with SDI-100/ANSI A250.8. ▪ Door Core shall be manufacturer's proprietary standard core to achieve specified ratings. ▪ Shop primer shall be manufacturer's standard rust inhibitive baked on or air dried shop primer. ▪ Door seals shall be manufacturer's standard adjustable sound seals. ▪ Hardware shall be manufacturer's standard Cam-Lift hinges, door bottom, threshold, seals and gaskets (when required). 	
Warranty	Fabrication	
Material and workmanship shall be warranted by manufacturer for a period of one (1) year from the date of shipment. Warranty shall apply to replacement or retrofit of product only.	<ul style="list-style-type: none"> ▪ Doors shall be minimum 14 gauge (STC 50 and 52 = 1-13/16"), 16 gauge (STC 48 = 1-3/4"), (nominal), without visible joints on exposed faces. Reinforce top and bottom with "flush" steel channels of no less than 16 gauge. ▪ Door core shall be proprietary acoustic composite core as tested by manufacturer to meet specified STC rating. ▪ Frames shall be minimum 16 gauge for STC 48, 14 gauge for STC 50 and 52, face welded and ground smooth construction. Provide frames with minimum of three anchors per jamb suitable for adjoining wall construction. ▪ All frames shall be fully prepared for mortised hardware and reinforced only for surface mounted hardware. Drilling and/or tapping shall be completed by others. ▪ Acoustical Seals shall be manufactured by Zero International or Pemko. 	
Approved Manufacturers		
Republic Doors and Frames 155 Republic Drive McKenzie TN 38201 Phone: 800-733-3667 Fax: 800-723-6677		

INSTALLATION INSTRUCTIONS FOR ACOUSTIC GASKETS

Republic's tested STC system included: R-566 threshold, R-870 adjustable head and jamb seals, R-119 spring bronze head and jamb seals.

1. The R-119 spring bronze should be installed on the bottom of the door before hanging.
2. Install the R-566 threshold to suit floor condition. Caulk round the bottom of threshold along with the entire perimeter of frame and at meeting edges of threshold and frame.
3. Close the door and measure the frame opening width and height. Install the R-870 head piece first (trim as necessary). Place the piece against the face of the door, making gentle contact between the "rubber extrusion" seal and the door, then fasten in place. Place the hinge side seal against the face of the door, making gentle contact between the "rubber extrusion" seal and the door, then fasten in place. Place the strike side seal against the face of the door, making gentle contact between the rubber extrusion seal and the door, then fasten in place.
4. Install the R-119, head piece first, then the hinge side and finally the lock side using the pressure sensitive tape to fasten the spring bronze to the frame.
5. Adjust the R-870 with the adjustment screws for the desired seal and operation of the door.
6. Check operation of the door after each piece of material is installed to make sure that no binding is taking place.





SINGLES - 14 GAUGE ¹												
Flush				Universal x 7/16" Single Return ²				DW x 1/2" Double Return ³				
STC	Width	Height	Door	5-3/4"	5-7/8" thru 8-3/4"	8-7/8" thru 14-3/4"	14-7/8" thru 20"	5-3/4"	5-7/8" thru 8-3/4"	8-7/8" thru 14-3/4"	14-7/8" thru 20"	
48	Thru 3'0"	7'0"		\$5,001	\$590	\$719	\$842	\$986	\$632	\$776	\$909	\$1,067
	Over 3'0" - 4'0"			\$5,389	\$606	\$734	\$849	\$991	\$650	\$791	\$918	\$1,075
50	Thru 3'0"	8'0"		\$5,492	\$590	\$719	\$842	\$986	\$632	\$776	\$909	\$1,067
	Over 3'0" - 4'0"			\$5,835	\$606	\$734	\$849	\$991	\$650	\$791	\$918	\$1,075
52	Thru 3'0"	8'0"		\$5,567	\$590	\$719	\$842	\$986	\$632	\$776	\$909	\$1,067
	Over 3'0" - 4'0"			\$5,909	\$606	\$734	\$849	\$991	\$650	\$791	\$918	\$1,075
48	Thru 3'0"	8'0"		\$5,402	\$695	\$813	\$933	\$1,076	\$749	\$874	\$1,009	\$1,166
	Over 3'0" - 4'0"			\$5,704	\$713	\$826	\$942	\$1,086	\$765	\$890	\$1,017	\$1,174
50	Thru 3'0"	8'0"		\$6,027	\$695	\$813	\$933	\$1,076	\$749	\$874	\$1,009	\$1,166
	Over 3'0" - 4'0"			\$6,370	\$713	\$826	\$942	\$1,086	\$765	\$890	\$1,017	\$1,174
52	Thru 3'0"	8'0"		\$6,104	\$695	\$813	\$933	\$1,076	\$749	\$874	\$1,009	\$1,166
	Over 3'0" - 4'0"			\$6,444	\$747	\$865	\$988	\$1,137	\$802	\$933	\$1,065	\$1,232

1. Frames must be fully grouted or filled with sound deadening insulation (by others.) Doors are priced CRS, Steel Stiffened core, Seamless edge design, 16 gauge for STC rating 48 - STC 50 and 52 are 14 gauge. Materials are prepped for 5.0" Heavy Weight hinges. Doors have a 1/4" undercut due to threshold requirements. STC units prepped at 5-10-Equal hinge spacing.
2. STC 48 to 52 frames are priced 7/16" Single Return, CRS, Face Welded construction.
3. STC 48 to 52 frames are priced 1/2" Double Return, 14 gauge, CRS, Face Welded construction.

DOUBLES - 14 GAUGE (MAXIMUM STC RATING 47)												
Flush				Univ x 7/16" Single Return				DW x 1/2" Double Return				
STC	Width	Height	Door	5-3/4"	5-7/8" thru 8-3/4"	8-7/8" thru 14-3/4"	14-7/8" thru 20"	5-7/8"	6" thru 8-1/4"	8-3/8" thru 13-7/8"	14" thru 20"	
47	Thru 6'0"	7'0"		\$10,985	\$693	\$825	\$945	\$1,088	\$749	\$890	\$1,026	\$1,178
	Over 6'0" - 8'0"			\$11,668	\$705	\$847	\$964	\$1,108	\$758	\$917	\$1,048	\$1,203
47	Thru 6'0"	8'0"		\$12,054	\$813	\$933	\$1,052	\$1,196	\$879	\$1,009	\$1,139	\$1,297
	Over 6'0" - 8'0"			\$12,739	\$824	\$955	\$1,072	\$1,214	\$886	\$1,033	\$1,163	\$1,317

- Doors are available from STC 48 to STC 52
- Standard hollow metal frames (min. 5-3/4" frame depth - welded)
- Flush top and bottom channel
- SDI Level 3 and 4 - Maximum Duty - Performance Level A
- Sound-resistant septum (proprietary construction)
- STC 48 and above furnished complete with all perimeter seals, 5" Cam-lift hinges and threshold and door bottom
- Pairs available up to STC 47
- All doors tested in fully operable conditions

Testing and Qualifications:

All door systems tested in accordance with:

- ASTM E 90-04
- ASTM E 413-04
- ASTM E 1332-90
- ASTM E 2235-04

Testing was performed by:

Architectural Testing Inc. and
Riverbank Acoustical Laboratories

STEEL TYPES		
Description	Door	Frame
Cold rolled steel	Included	Included
A60 Galvanized steel	\$111.00	\$61.00
G90 Galvanized steel (14 and 16 gauge only)	\$445.00	\$108.00

HINGE PREPARATIONS		
Description	Door	Frame
Special hinge locations	No charge	No charge
Additional hinge prep (per hinge)	\$27.00	\$25.00
5" Standard or heavy weight hinge prep (each)	Included	Included
Electric hinge	\$27.00	\$25.00
▪ Cutout in one hinge reinf. ▪ No junction box or conduit		
Power transfer (no junction box or conduit)	\$145.00	\$111.00
8" Junction box welded in	N/A	\$34.00
14" Junction box welded in	N/A	\$34.00
10" Junction box welded in soffit	N/A	\$34.00

DOOR - LOCK/FRAME - STRIKE PREPARATIONS		
Description	Door	Frame
Standard lock (strike) at non-standard location	No charge	No charge
Cylindrical dead lock (2-3/4" strike)	\$65.00	\$25.00
Mortise dead lock (3-1/2" strike)	\$65.00	\$25.00
Electric strike (no junction box or conduit)	\$143.00	\$107.00
Rim reinforcement only ¹	\$54.00	\$33.00
Mortise exit device reinforcement with function prep	\$95.00	N/A
Surface vertical rod reinforcement only ¹	\$87.00	\$33.00
Concealed vertical rod (strike)	\$648.00	N/A
Exit alarm reinforcement only ¹	\$66.00	\$33.00

1. Republic Tested Acoustical Systems: tested with standard hardware applications. Surface-applied hardware not recommended due to possible interference with seals and gaskets. Any break or tear in seals and gaskets may affect performance.

FRAME PROFILE OPTIONS		
Description	Door	Frame
Single rabbet (minimum depth on STC is 5-3/4")	N/A	No charge
4" Face heads (through 4'0")	N/A	\$64.00
4" Face heads (over 4'0")	N/A	\$89.00

See [Engineering Section](#) for further options and/or details.

LABEL PREPARATIONS		
Description	Door	Frame
Mark numbers	No charge	No charge
U.L. Mylar label (std unless specified otherwise)	N/A	N/A
U.L. Metal label	N/A	N/A
Warnock Hersey Metal label	N/A	N/A
STC labels with gasketing (lab tested)	Included	Included

CLOSER PREPARATIONS		
Description	Door	Frame
Closer reinforcement	\$40.00	\$33.00
Concealed overhead door closer, holder or stop	\$394.00	\$307.00

SPECIAL FINISH		
Description	Door	Frame
Second coat of primer	\$132.00	\$123.00
Finish paint setup charge	\$1,433.00	\$1,433.00
Finish paint	\$360.00	\$360.00
▪ Minimum quantity of 20 doors or 20 (3pc) frames per color		
▪ Price includes full carton wrap		

ANCHOR OPTIONS		
Description	Door	Frame
Welded in prepared opening anchor (per anchor)	N/A	\$17.00
Welded in anchor (per anchor)	N/A	\$7.50
Punch and dimple only (per P&D)	N/A	\$6.00

FRAME CONSTRUCTION		
Description	Door	Frame
Unit bundle (3pc)	N/A	\$7.00
Standard face weld (3pc)	N/A	Included
Full profile weld (3pc)	N/A	\$220.00

SPECIAL CONSTRUCTIONS		
Description	Door	Frame
10 Gauge hinge and 14 gauge lock channels	N/A	N/A
Seal top or bottom channel and finish smooth each	\$150.00	N/A
Mag switch/DPS - Hole only	\$25.00	\$25.00
Mag switch/DPS - Prep and reinf. (no junction box)	\$131.00	\$97.00
Bondo filled edge	Included	N/A
Continuous welded edge	\$192.00	N/A
Beveled lock edge (1/8" in 2") STC 48 only	\$23.00	N/A
Door viewer	\$32.00	N/A
Conduit/raceway - includes wire pull	\$202.00	N/A

DOOR TEST PERFORMANCE CHARACTERISTICS PER ASTM E90 & E413																		
	Transmission Loss in db/Hertz																	
STC	100	125	160	200	250	315	400	500	630	800	1000	1250	1600	2000	2500	3150	4000	5000
48	24	29	34	40	37	41	43	42	45	50	50	53	53	54	53	54	55	54
50	19	30	36	40	42	45	46	42	49	50	50	51	53	54	56	57	55	55
52	21	29	36	40	44	46	47	44	53	54	54	55	55	56	57	59	59	58

LEADLINED

BULLET RESISTANT

PALADIN™ SERIES

HURRICANE/WIND RESISTANT

SOUND TRANSMISSION CONTROL

this page intentionally blank

SE SERIES

Universal Sticks

Refer to technical data sheet on page 15

Republic pre-engineered steel frame components called "sticks" provide unlimited flexibility for opening systems. Stick components are used to fabricate even the most complex entrance fronts, partitions and window wall designs. The variety of jamb depths and sizes permit greater design freedom. Because stick assemblies are normally welded, they offer strength without seams showing between vertical and horizontal members.

These openings can be designed for any job requirement, fabricated from factory components, assembled and welded by factory trained Republic Distributors. Because sticks can be shipped as components and fabricated locally, shipping costs, job delays and design limitations are greatly reduced.

Frame assemblies shall be made of standard stick components, fabricated from prime quality 16, 14 or 12 gauge, cold-rolled or galvannealed steel. Where sticks are used at door openings in the frame assemblies, they shall be prepared for all hardware specified. Frame assemblies shall be fabricated from three basic components: Open sections (perimeter members), Mullion sections (intermediate members) and Sill sections (bottom members).

Mullion sections shall have identical jamb depths and stops as open sections. Mullion sections are only available in 16 and 14 gauge.

Sill sections shall be flush with both faces of adjacent vertical members. The individual sticks shall be cut to length and notched to assure square joints and corners. All joints and corners of the frame assembly available welded and ground smooth at the face of the sections.



When specified, steel panels shall be furnished 1-3/8" or 1-3/4" thick as required.

All stick components, steel panels and frame assemblies shall be phosphatized and receive one coat of force-cured rust inhibiting prime paint. Steel channel glazing beads shall be provided with the assemblies for all areas in which glass is to be installed.


Frame assemblies may be shipped to jobsite completely welded. Field joints shall be permitted only when the size of the total assembly exceeds shipping limitations. When frame assemblies are subjected to windloads, vertical members shall be free of field splices.

Sticks are manufactured in 10'3" maximum lengths. Other lengths are available. Consult factory.


Other profiles are available upon request.




Section Details of Typical Field Splice Connections

Jambs (Open Sections)


Blank Jamb





Blank Jamb Single Rabbet




Blank Jamb Drywall Return



Blank Jamb Non Standard Face

Bases (Sill Section)**Mullions (Closed Sections)**

Blank Mullion




Blank Mullion Single Rabbet



Blank Jamb Filler No Stop



Blank Jamb Filler With Stop

Mullions (Closed Sections)

2 Way

3 Way

UNIVERSAL (SE) STICKS 7/16" SINGLE RETURN

Description	Height	16 Gauge						14 Gauge					
		4-5/8" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"	4-5/8" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"
Blank jamb	10'3"	\$182	\$198	\$252	\$300	\$364	\$455	\$214	\$247	\$313	\$353	\$435	\$544
Hinge jamb 4.5" Hng preps	10'3"	\$257	\$273	\$327	\$375	\$439	\$530	\$289	\$322	\$388	\$428	\$510	\$619
Strike jamb asa/4-7/8" stk	10'3"	\$207	\$223	\$277	\$325	\$389	\$480	\$239	\$272	\$338	\$378	\$460	\$569
Filler w/stop	10'3"	\$204	\$224	\$237	\$264	\$319	\$399	\$235	\$251	\$266	\$313	\$393	\$491
Filler w/o stop	10'3"	\$131	\$163	\$175	\$201	\$228	\$315	\$162	\$201	\$211	\$247	\$282	\$371
Blank jamb 4" face	10'3"	\$245	\$264	\$335	\$393	\$479	\$598	\$284	\$308	\$396	\$443	\$559	\$699
Blank jamb 6" face	10'3"	\$425	\$532	\$574	\$610	\$674	\$862	\$528	\$628	\$715	\$751	\$839	\$1,076
Blank jamb 8" face	10'3"	\$425	\$532	\$574	\$610	\$674	\$862	\$528	\$628	\$715	\$751	\$839	\$1,076
Blank jamb 10" face	10'3"	\$502	\$594	\$636	\$721	\$831	\$1,039	\$589	\$667	\$743	\$815	\$1,010	\$1,269
Blank jamb 12" face	10'3"	\$502	\$594	\$636	\$721	\$831	\$1,039	\$589	\$667	\$743	\$815	\$1,010	\$1,269
Blank jamb cased open	10'3"	\$182	\$198	\$252	\$300	\$364	\$455	\$214	\$247	\$313	\$353	\$435	\$544
Dbl egress blank jamb minimum JD 4-3/4"	10'3"	\$245	\$282	\$291	\$340	\$392	\$481	\$313	\$355	\$375	\$425	\$479	\$568
Dbl egress hinge jamb 4.5" Hng preps minimum JD 4-3/4"	10'3"	\$320	\$357	\$366	\$415	\$467	\$556	\$385	\$430	\$450	\$500	\$554	\$643
Blank mullion 2" face	10'3"	\$404	\$461	\$512	\$598	\$717	\$896	\$467	\$569	\$620	\$704	\$836	\$1,045
Blank mullion 4" face	10'3"	\$524	\$607	\$674	\$781	\$893	\$1,116	\$599	\$722	\$783	\$904	\$1,039	\$1,299
Blank mullion 6" face	10'3"	\$670	\$761	\$825	\$936	\$1,117	\$1,396	\$759	\$839	\$928	\$1,041	\$1,263	\$1,579
Blank mullion 8" face	10'3"	\$670	\$761	\$825	\$936	\$1,117	\$1,396	\$759	\$839	\$928	\$1,041	\$1,263	\$1,579
Blank mullion 10" face	10'3"	\$719	\$815	\$883	\$1,002	\$1,194	\$1,492	\$780	\$904	\$993	\$1,062	\$1,329	\$1,662
Blank mullion 12" face	10'3"	\$719	\$815	\$883	\$1,002	\$1,194	\$1,492	\$780	\$904	\$993	\$1,062	\$1,329	\$1,662
Hinge mullion 4.5" Hng preps	10'3"	\$479	\$536	\$587	\$673	\$792	\$971	\$524	\$626	\$677	\$761	\$893	\$1,102
Strike mullion	10'3"	\$429	\$486	\$537	\$623	\$742	\$921	\$491	\$588	\$639	\$723	\$855	\$1,064
2 Way corner post	10'3"	\$768	\$810	\$846	\$987	\$1,168	\$1,460	\$835	\$897	\$999	\$1,117	\$1,313	\$1,639
3 Way corner post	10'3"	\$768	\$810	\$846	\$987	\$1,168	\$1,460	\$835	\$897	\$999	\$1,117	\$1,313	\$1,639

FRAME PROFILE OPTIONS

No returns	No charge
Cased open	No charge
Single rabbet	No charge
Non-standard face (per piece) (1"-3-7/8" uniform)	\$79.00
Non-standard face (per piece) (1"-3-7/8" unequal)	\$79.00
Non-standard rabbet (per piece)	\$65.00
Kerf (includes weather-stripping)	\$194.00
Non-standard returns (uniform)	\$79.00

STEEL TYPES

Cold rolled steel	Included
A60 Galvanized steel - Jamb/Stick	\$61.00
A60 Galvanized steel - Mullion	\$61.00
G90 Galvanized steel (14 and 16 gauge only) - Jamb/Stick	\$108.00
G90 Galvanized steel (14 and 16 gauge only) - Mullion	\$108.00
12 Gauge - Jamb/Stick (N/A on mullions or drywall) (Add to 14 gauge) *5/8 returns	\$398.00

FRAME - STRIKE PREPARATIONS

Special strike location	No charge
Standard strike at non-standard location	No charge
Cylindrical dead lock (2-3/4" strike)	\$25.00
Mortise dead lock (3-1/2" strike)	\$25.00
ANSI 4-7/8" Strike - any location	\$25.00

See [Engineering Section](#) for further options and/or details.




ME/MH SERIES


Borrowed Lites

ME SERIES


- Gauges: 16 and 14
- Faces: 1" to 4"
- Standard Rabbets: 1-9/16" and 1-15/16"
- Stop: 5/8" standard
- Single Return: 7/16" x Universal/Masonry profile
- Anchors: See Details
- Profiles: Equal Rabbet, Unequal Rabbet, Single Rabbet




ME Corner Connection




Prepared Opening Anchor




Wire Anchor



Wood Stud Anchor




"T" Anchor




"Z" Anchor

MH SERIES


- Gauges: 16 and 14
- Faces: 1" to 4"
- Standard Rabbets: 1-9/16" and 1-15/16"
- Stop: 5/8" standard
- Double Return: 1/2" x Drywall profile
- Anchors - Drywall: Welded in compression anchors 3-1/2" in from each end standard
- Profiles: Equal Rabbet, Unequal Rabbet, Single Rabbet




MH Corner Connection



Compression Anchor (Standard)



L Strap Anchor (Optional)



"Z" Anchor (Optional)
Must be welded in

COMPONENTS UNIVERSAL FRAMES 7/16" SINGLE RETURN												
Header (Borrowed Lites require 2 each)	16 Gauge						14 Gauge					
	4-5/8" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"	4-5/8" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"
Thru 3'0"	\$56	\$66	\$79	\$96	\$122	\$189	\$76	\$85	\$103	\$118	\$148	\$215
Thru 4'0"	\$72	\$83	\$96	\$114	\$138	\$205	\$88	\$100	\$116	\$135	\$159	\$226
Thru 5'0"	\$103	\$112	\$127	\$148	\$172	\$239	\$124	\$139	\$154	\$176	\$197	\$264
Thru 6'0"	\$113	\$125	\$144	\$164	\$190	\$257	\$139	\$154	\$169	\$186	\$215	\$282
Thru 8'0"	\$137	\$152	\$177	\$197	\$226	\$293	\$167	\$184	\$205	\$227	\$255	\$322
Thru 10'0"	\$176	\$194	\$230	\$259	\$288	\$355	\$215	\$242	\$272	\$298	\$330	\$397

COMPONENTS UNIVERSAL FRAMES 7/16" SINGLE RETURN												
Jamb Pair	16 Gauge						14 Gauge					
Height	4-5/8" thru 5-3/4"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"	4-5/8" thru 5-3/4"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"
	Thru 3'0"	\$180	\$190	\$224	\$253	\$293	\$349	\$200	\$220	\$261	\$286	\$337
Over 3'0" - 4'0"	\$216	\$229	\$273	\$312	\$364	\$438	\$242	\$268	\$322	\$355	\$422	\$510
Over 4'0" - 6'0"	\$244	\$272	\$322	\$364	\$420	\$554	\$298	\$330	\$362	\$406	\$466	\$600
Over 6'0" - 8'0"	\$342	\$360	\$408	\$462	\$532	\$666	\$406	\$434	\$460	\$506	\$586	\$720
Over 8'0" - 10'0"	\$446	\$486	\$546	\$608	\$696	\$830	\$536	\$580	\$616	\$672	\$762	\$896


COMPONENTS DRYWALL FRAMES 1/2" DOUBLE RETURN												
Header (Borrowed Lites require 2 each)	16 Gauge						14 Gauge					
	4-1/2" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"	4-1/2" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"
Thru 3'0"	\$61	\$77	\$90	\$103	\$131	\$198	\$85	\$97	\$107	\$119	\$149	\$216
Over 3'0" - 4'0"	\$76	\$95	\$102	\$119	\$142	\$209	\$95	\$111	\$116	\$141	\$158	\$225
Over 4'0" - 6'0"	\$116	\$126	\$140	\$153	\$179	\$246	\$153	\$166	\$174	\$192	\$212	\$279
Over 6'0" - 8'0"	\$140	\$151	\$167	\$183	\$212	\$279	\$186	\$199	\$209	\$225	\$254	\$321
Over 8'0" - 9'0"	\$161	\$183	\$207	\$226	\$254	\$321	\$199	\$216	\$238	\$256	\$285	\$352
Over 9'0" - 10'0"	\$203	\$240	\$269	\$290	\$324	\$391	\$269	\$288	\$311	\$330	\$359	\$426

COMPONENTS DRYWALL FRAMES 1/2" DOUBLE RETURN												
Jamb Pair	16 Gauge						14 Gauge					
Height	4-1/2" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"	4-1/2" thru 5-7/8"	6" thru 7-7/8"	8" thru 9-7/8"	10" thru 11-7/8"	12" thru 14-3/4"	14-7/8" thru 20"
	Thru 3'0"	\$244	\$254	\$288	\$317	\$357	\$413	\$264	\$284	\$325	\$350	\$401
Over 3'0" - 4'0"	\$280	\$293	\$337	\$375	\$428	\$502	\$306	\$332	\$386	\$419	\$485	\$574
Over 4'0" - 6'0"	\$272	\$314	\$344	\$378	\$438	\$572	\$344	\$402	\$416	\$472	\$550	\$684
Over 6'0" - 8'0"	\$368	\$410	\$440	\$486	\$552	\$686	\$448	\$496	\$530	\$568	\$642	\$776
Over 8'0" - 10'0"	\$524	\$552	\$604	\$626	\$702	\$836	\$608	\$664	\$700	\$740	\$816	\$950


Drywall Borrowed Lite jamb pairs include 2 each compression anchors - welded in jamb(s). One at approximately 3.5" in from each end.

**FRAME PROFILE OPTIONS**

No returns	No charge
Cased open	No charge
Single rabbet	No charge
4" Face heads (through 4'0")	\$64.00
4" Face heads (over 4'0")	\$89.00
Non-standard face (per frame) 1" to 3-7/8" uniform	\$79.00
Non-standard rabbet	\$261.00
Non-standard returns (uniform)	\$79.00
Cold rolled steel	Included
A60 Galvanized steel	\$61.00
G90 Galvanized steel (available in 14 and 16 gauge only)	\$108.00
12 Gauge (See Stick Section)	N/A
Second coat of primer	\$123.00
Finish paint setup charge (N/A Welded)	\$1,433.00
Finish paint (minimum qty 20 units color)	\$360.00
Welded in prepared opening anchor (per anchor)	\$17.00
Welded in anchor (per anchor)	\$7.50
Punch and dimple only (per prep)	\$6.00
Unit bundle (elevation)	\$20.00
Standard face weld (4pc)	\$242.00
Full profile weld (4pc)	\$440.00



ME Borrowed Lite



MH Borrowed Lite

See [Engineering Section](#) for further options and/or details.

CUT-N-NOTCH AND PANELS

Sticks

The information contained herein has been prepared to permit architects, engineers and other qualified persons to design and select the proper Republic standard stick components for use in fabricated frame assemblies when subjected to structural or wind loads.


Physical properties and wind load tables were calculated by a registered engineer and are based on the "Specifications for the Design of Cold-Formed Steel Structural Members", 1969 Edition, published by the American Iron and Steel Institute.

Table I (See Technical Data) lists the physical properties of open sections. These sections are usually used as perimeter components in any frame assembly and are not critical components of that assembly because perimeter components must be securely anchored to building walls.

Table II (See Technical Data) lists the physical properties of the closed sections. These sections are usually used as the intermediate horizontal and vertical components and are usually found to be the critical sections in any frame assembly. The critical component in any frame assembly is usually the component having the longest unsupported length or supporting the largest frame area in wind loading.


The most frequently encountered problem is that of designing an intermediate component to resist wind loading only. For this reason, Table III (See Technical Data) is included. This table allows the designer to calculate the wind load on the component in pounds per linear foot and then select the proper section directly from the table.

CUT-N-NOTCH & WELDED UNIT				
Gauge (14 or 16)	16	EXAMPLE PRICE SHEET -- 4040 BORROWED LITE		
Material (CRS or A60)	CRS	Overall width and height using Cut-N-Notch		
Jamb depth: (3.00"-20")	5-3/4"	May price as BL Components (see page 75), not shown here		
QTY	DESCRIPTION	LIST	TOTAL	PAGE
(in inches)	Cut-N-Notch Stick Material, 2" Face (may use BL in Cut-N-Notch)	Subtotal	\$284.21	
48	4'0" Blank jamb - Open section, top	\$1.48	\$71.05	See page 81
48	4'0" Blank jamb - Open section, bottom	\$1.48	\$71.05	
48	4'0" Blank jamb - Open section, left	\$1.48	\$71.05	
48	4'0" Blank jamb - Open section, right	\$1.48	\$71.05	
(each)	Joints	Subtotal	\$136.00	
8	Mitered corners (per end)	\$17.00	\$136.00	See page 82
(in inches)	Glazing bead	Subtotal	\$158.40	
176	3/4" x 5/8" tall Glazing bead (cut to length, loose)	\$0.69	\$121.44	See page 82
	Installed (taped or screwed in for shipping)	\$0.21	\$36.96	
(each)	Anchors	Subtotal	\$30.00	
4	Welded in (see page 86) Anchor (jamb anchor loose, see page 100)	\$7.50	\$30.00	See page 86
(each)	Welding	Subtotal	\$244.00	
4	Face welding - Tab and slot corner connection	\$61.00	\$244.00	See page 82
			Total	\$852.61






CUT-N-NOTCH & WELDED UNIT				
Gauge (14 or 16)		14	EXAMPLE PRICE SHEET -- 6440 BORROWED LITE	
Material (CRS or A60)		A60	Overall width and height using Cut-N-Notch	
Jamb depth: (3.00"-20")		7-3/4"	May price as BL Components (see page 75), not shown here	
QTY	DESCRIPTION		LIST	TOTAL
(in inches)	Cut-N-Notch Stick Material, 2" Face (may use BL with Cut-N-Notch)	Subtotal	\$773.29	
76	6'4" Blank jamb - Open section, top		\$2.20	\$167.26
76	6'4" Blank jamb - Open section, bottom		\$2.20	\$167.26
48	4'0" Blank jamb - Open section, left		\$2.20	\$105.64
48	4'0" Blank jamb - Open section, right		\$2.20	\$105.64
44	3'8" Blank jamb - Mullion section		\$5.17	\$227.51
(each)	Joints	Subtotal	\$180.00	
8	Mitered corner (per end)		\$17.00	\$136.00
2	Notched closed section (per end)		\$22.00	\$44.00
(in inches)	Glazing bead	Subtotal	\$284.40	
316	3/4" x 5/8" tall Glazing bead (cut to length, loose)		\$0.69	\$218.04
	Installed (taped or screwed in for shipping)		\$0.21	\$66.36
(each)	Anchors	Subtotal	\$30.00	
4	Welded in (see page 86) Anchor (jamb anchor loose, see page 100)		\$7.50	\$30.00
(each)	Welding	Subtotal	\$436.00	
4	Face welding - Tab and slot corner connection		\$61.00	\$244.00
2	Face welding - 2" or less (at mullion notches)		\$96.00	\$192.00
		Total	\$1,703.69	




CUT-N-NOTCH & WELDED UNIT				
Gauge (14 or 16)	16	EXAMPLE PRICE SHEET -- 5672 ELEV WITH PARTIAL SIDE LITE Overall width and height using Cut-N-Notch (May be priced as ME with sticks, not shown here)		
Material (CRS or A60)	CRS			
Jamb depth: (3.00"-20")	7-3/4"			
QTY	DESCRIPTION	LIST	TOTAL	PAGE
(in inches)	Cut-N-Notch Stick Material, 2" Face (may use ME with Cut-N-Notch)	Subtotal	\$659.51	
86	7'2" Blank jamb - Open section, left	\$1.61	\$138.57	See page 81
66	5'6" Blank jamb - Open section, head	\$1.61	\$106.34	
36	3'0" Blank jamb - Open, right	\$1.61	\$58.01	
26	2'2" Blank jamb - Open, bottom	\$1.61	\$41.89	
84	7'0" Blank mullion - Closed section (see Cut open back)	\$3.75	\$314.71	
(each)	Joints	Subtotal	\$146.00	
6	Mitered corner (per end)	\$17.00	\$102.00	See page 82
2	Notched closed section (per end)	\$22.00	\$44.00	
(each)	Hardware preps	Subtotal	\$190.00	
1	ASA 4-7/8" Strike prep	\$25.00	\$25.00	See page 82
3	4-1/2" x 4-1/2" Hinge prep (per hinge)	\$25.00	\$75.00	
1	Cut Open Back/weld in sill anchor (for closed sect)	\$90.00	\$90.00	
(in inches)	Glazing bead	Subtotal	\$100.80	
112	3/4" x 5/8" tall Glazing bead (cut to length, loose)	\$0.69	\$77.28	See page 82
	Installed (taped or screwed in for shipping)	\$0.21	\$23.52	-
(each)	Anchors	Subtotal	\$59.50	
7	Welded in (see page 86) Anchor (jamb anchor loose, see page 100)	\$7.50	\$52.50	See page 86
2	One piece sill anchor (loose base anchor)	\$3.50	\$7.00	
(each)	Welding	Subtotal	\$375.00	
3	Face welding - Tab and slot corner connection	\$61.00	\$183.00	See page 82
2	Face welding - 2" or less (at mullion notches)	\$96.00	\$192.00	
Total			\$1,530.81	



Overall 5672 Elevation with Partial side light



CUT-N-NOTCH & WELDED UNIT				
Gauge (14 or 16)	16	EXAMPLE PRICE SHEET -- 5674 ELEVATION WITH SIDE LITE		
Material (CRS or A60)	A60	Overall width and height using Cut-N-Notch		
Jamb depth: (3.00"-20")	8-3/4"	(May be priced as ME with sticks, not shown here)		
QTY	DESCRIPTION	LIST	TOTAL	PAGE
(in inches)	Cut-N-Notch Stick Material, 2" Face (may use ME with Cut-N-Notch)	Subtotal	\$1,129.55	
86	7'2" Blank jamb - Open section, left	\$2.23	\$191.52	
86	7'2" Blank jamb - Open section, right	\$2.23	\$191.52	
84	7'0" Blank mullion - Closed section, vertical	\$4.47	\$375.23	
24	7'0" Blank mullion - Closed section, horizontal	\$4.47	\$107.21	
66	5'6" Blank jamb - Open section, 4" face head	\$2.93	\$193.66	
24	2'0" Blank jamb - Open section, 4" face sill	\$2.93	\$70.42	
(each)	Joints	Subtotal	\$166.00	
4	Mitered corner (per end)	\$17.00	\$68.00	
2	Notched open section (per end)	\$16.00	\$32.00	
3	Notched closed section (per end)	\$22.00	\$66.00	
(each)	Hardware preps	Subtotal	\$100.00	
1	ASA 4-7/8" Strike prep	\$25.00	\$25.00	
3	4-1/2" x 4-1/2" Hinge prep (per hinge)	\$25.00	\$75.00	
(in inches)	Glazing bead	Subtotal	\$226.80	
252	3/4" x 5/8" tall Glazing bead (cut to length, loose)	\$0.69	\$173.88	
	Installed (taped or screwed in for shipping)	\$0.21	\$52.92	
(each)	Anchors	Subtotal	\$65.00	
6	Welded in (see page 86) Anchor (jamb anchor loose, see page 100)	\$7.50	\$45.00	See page 82
2	One piece sill anchor (loose base anchor)	\$3.50	\$7.00	See page 100
1	Base anchor for sticks (loose)	\$13.00	\$13.00	See page 100
(each)	Welding	Subtotal	\$638.00	
2	Face welding - Tab and slot corner connection	\$61.00	\$122.00	
3	Face welding - 2" or less (at mullion notches)	\$96.00	\$288.00	
2	Face welding - Over 2" up to 4" (at sill notches)	\$114.00	\$228.00	
		Total	\$2,325.35	




Overall 5674 Elevation with Side light

CUT-N-NOTCH/PER INCH						
Components	Jamb depth	16 Gauge		14 Gauge		
		CRS	A60	CRS	A60	
Blank Jamb 2" Face	4-5/8" — 5-7/8"	\$1.48	\$1.76	\$1.74	\$2.05	
	6" — 7-7/8"	\$1.61	\$1.78	\$2.00	\$2.20	
	8" — 9-7/8"	\$2.05	\$2.23	\$2.54	\$2.75	
	10" — 11-7/8"	\$2.44	\$2.74	\$2.87	\$3.07	
	12" — 14-3/4"	\$2.96	\$3.26	\$3.54	\$3.80	
	14-7/8" — 20"	\$3.70	\$4.08	\$4.42	\$4.75	
BJ/1"-4" Face	4-5/8" — 5-7/8"	\$1.99	\$2.21	\$2.31	\$2.58	
	6" — 7-7/8"	\$2.15	\$2.33	\$2.50	\$2.74	
	8" — 9-7/8"	\$2.72	\$2.93	\$3.22	\$3.41	
	10" — 11-7/8"	\$3.20	\$3.42	\$3.60	\$3.80	
	12" — 14-3/4"	\$3.89	\$4.09	\$4.55	\$4.74	
	14-7/8" — 20"	\$4.86	\$5.11	\$5.68	\$5.93	
BJ/4-1/8"-8-1/8" Face	4-5/8" — 5-7/8"	\$3.45	\$3.92	\$4.29	\$4.64	
	6" — 7-7/8"	\$4.32	\$4.74	\$5.10	\$5.59	
	8" — 9-7/8"	\$4.67	\$5.09	\$5.82	\$6.28	
	10" — 11-7/8"	\$4.96	\$5.45	\$6.10	\$6.71	
	12" — 14-3/4"	\$5.48	\$6.03	\$6.82	\$7.42	
	14-7/8" — 20"	\$7.01	\$7.53	\$8.75	\$9.28	
BJ/8-1/4"-12" Face	4-5/8" — 5-7/8"	\$4.08	\$4.45	\$4.79	\$5.27	
	6" — 7-7/8"	\$4.83	\$5.14	\$5.43	\$5.94	
	8" — 9-7/8"	\$5.17	\$5.43	\$6.04	\$6.59	
	10" — 11-7/8"	\$5.86	\$6.14	\$6.63	\$7.18	
	12" — 14-3/4"	\$6.75	\$6.82	\$8.21	\$9.00	
	14-7/8" — 20"	\$8.45	\$8.53	\$10.32	\$11.25	
Blank Mullion 2" Face	4-5/8" — 5-7/8"	\$3.29	\$3.64	\$3.80	\$4.11	
	6" — 7-7/8"	\$3.75	\$4.14	\$4.62	\$4.87	
	8" — 9-7/8"	\$4.17	\$4.47	\$5.04	\$5.29	
	10" — 11-7/8"	\$4.86	\$5.42	\$5.72	\$6.05	
	12" — 14-3/4"	\$5.83	\$6.39	\$6.80	\$7.11	
	14-7/8" — 20"	\$7.29	\$7.97	\$8.50	\$8.89	
Blank Mullion 2-1/8"-4"	4-5/8" — 5-7/8"	\$4.26	\$4.58	\$4.87	\$5.17	
	6" — 7-7/8"	\$4.93	\$5.13	\$5.87	\$6.12	
	8" — 9-7/8"	\$5.48	\$5.53	\$6.37	\$6.60	
	10" — 11-7/8"	\$6.35	\$6.75	\$7.35	\$7.61	
	12" — 14-3/4"	\$7.26	\$7.89	\$8.45	\$9.18	
	14-7/8" — 20"	\$9.07	\$9.86	\$10.56	\$11.46	

CUT-N-NOTCH/PER INCH						
Components	Jamb depth	16 Gauge		14 Gauge		
		CRS	A60	CRS	A60	
Blank Mullion 4-1/8"-8-1/8"	4-5/8" — 5-7/8"	\$5.45	\$5.70	\$6.17	\$6.46	
	6" — 7-7/8"	\$6.19	\$6.41	\$6.82	\$7.15	
	8" — 9-7/8"	\$6.71	\$6.90	\$7.55	\$7.83	
	10" — 11-7/8"	\$7.61	\$8.44	\$8.46	\$8.70	
	12" — 14-3/4"	\$9.08	\$9.55	\$10.27	\$10.85	
	14-7/8" — 20"	\$11.35	\$11.94	\$12.84	\$13.56	
Blank Mullion 8-1/4"-12"	4-5/8" — 5-7/8"	\$5.84	\$6.10	\$6.34	\$6.73	
	6" — 7-7/8"	\$6.62	\$6.86	\$7.35	\$7.65	
	8" — 9-7/8"	\$7.18	\$7.39	\$8.08	\$8.33	
	10" — 11-7/8"	\$8.15	\$9.03	\$8.63	\$8.83	
	12" — 14-3/4"	\$9.71	\$10.22	\$10.81	\$11.00	
	14-7/8" — 20"	\$12.13	\$12.77	\$13.51	\$13.75	
Filler Section	4-5/8" — 5-7/8"	\$1.66	\$1.85	\$1.91	\$2.16	
	6" — 7-7/8"	\$1.82	\$2.02	\$2.04	\$2.28	
	8" — 9-7/8"	\$1.93	\$2.12	\$2.16	\$2.42	
	10" — 11-7/8"	\$2.14	\$2.32	\$2.54	\$2.79	
	12" — 14-3/4"	\$2.59	\$2.79	\$3.20	\$3.44	
	14-7/8" — 20"	\$3.24	\$3.49	\$4.00	\$4.29	
Corner Posts 2/3 Way	4-5/8" — 5-7/8"	\$6.24	\$6.55	\$6.79	\$7.06	
	6" — 7-7/8"	\$6.59	\$6.85	\$7.29	\$7.53	
	8" — 9-7/8"	\$6.88	\$7.20	\$8.12	\$8.51	
	10" — 11-7/8"	\$8.02	\$8.34	\$9.08	\$9.43	
	12" — 14-3/4"	\$9.50	\$9.71	\$10.67	\$10.94	
	14-7/8" — 20"	\$11.87	\$12.13	\$13.33	\$13.67	



PANELS			
			
Non-label panels			
20 Gauge base price	\$376.00	Add per sq. ft.	\$37.00
18 Gauge base price	\$376.00	Add per sq. ft.	\$48.00
16 Gauge base price	\$376.00	Add per sq. ft.	\$50.00
14 Gauge base price	\$376.00	Add per sq. ft.	\$62.00
Label panels			
20 Gauge base price	\$470.00	Add per sq. ft.	\$37.00
18 Gauge base price	\$470.00	Add per sq. ft.	\$48.00
16 Gauge base price	\$470.00	Add per sq. ft.	\$50.00
14 Gauge base price	\$470.00	Add per sq. ft.	\$67.00
Options			
A60 Galvanized steel			\$111.00
G90 Galvanized steel (14 and 16 gauge only)			\$445.00
Flat bar astragal attached to bottom of panel			\$116.00
Polystyrene core			\$41.00
Flush bolt strike			\$101.00

FRAME PROFILE OPTIONS / PER INCH	
No returns	No charge
Cased open	No charge
Single rabbet	No charge
Non-standard rabbet	\$0.47
Kerf (includes weather-stripping) (16 gauge only)	\$0.71
Non-standard returns (uniform)	\$0.76
Weld in filler	\$2.75

STEEL TYPES / PER INCH	
Cold rolled steel and A60 Galvanized steel	Included
G90 Galvanized steel - Stick ¹	\$0.34
G90 Galvanized steel - Mullion ¹	\$0.34
12 Gauge - Jamb/Stick ²	\$4.38

1. Available in 14 and 16 gauge only.
2. Not available on mullions/add to 14 gauge.

HINGE PREPARATIONS	
Special hinge locations	No charge
4.5" x 4.5" Hinge prep (per hinge)	\$25.00
5" Universal hinge prep (per hinge)	\$25.00

FRAME - STRIKE PREPARATIONS	
Special strike location	No charge
ANSI 4-7/8" ASA strike	\$25.00
Cylindrical dead lock (2-3/4" strike)	\$25.00
Mortise dead lock (3-1/2" strike)	\$25.00
Cut open backside of mullion/weld in sill anchor	\$90.00

See [Engineering Section](#) for further options and/or details.

NOTCHING / WELDING	
Mitered corner - Jamb (per end) (N/A in 12 gauge)	\$17.00
Notched end - Jamb/Sill (per end)	\$16.00
Notched end - Mullion (per end)	\$22.00
Glazing bead 3/4" wide - cut to length/bundled (per inch)	\$0.69
Glazing bead 1/2" wide - cut to length/bundled (per inch)	\$1.02
Glazing bead - installed (add to above) (per inch)	\$0.21
Full profile welding - Tab and slot corner connection	\$107.00
Face welding - Tab and slot corner connection	\$61.00
Face welding - 2" or less intersection	\$96.00
Face welding - over 2" up to 4" intersection	\$114.00
Face welding - over 4" up to 6" intersection	\$144.00
Face welding - over 6" up to 8" intersection	\$173.00
Face welding - over 8" up to 10" intersection	\$173.00
Face welding - over 10" up to 12" intersection	\$173.00
Field splicing - per connection (clips sold separately)	\$115.00
Splice/weld over 10' length	\$153.00

SPECIALTY OPTIONS / PER INCH	
1/16" Lead Installed, open section frames only	\$23.06
Bullet resistant (Level 1)	\$1.09

ENGINEERING

Please refer to individual product series pages to verify feature or prep is available in product series.

STEEL TYPES		
Description	Door	Frame
Cold rolled steel	Included	Included
A60 Galvanized steel	\$111.00	\$61.00
G90 Galvanized steel ¹	\$445.00	\$108.00
12 Gauge ²	N/A	N/A

1. Available in 14 and 16 gauge only.
2. See [Stick Section](#) for frames. Frames must be square cut or Cut-N-Notch connection(s). Welding required (not included) *5/8" returns

CORE OPTIONS		
Description	Door	Frame
Honeycomb	Included	N/A
Polystyrene insulated	\$41.00	N/A
▪ "U" Factor = .41		
▪ "R" Factor = 2.43 (Per ASTM C1363)		
Polyurethane insulated	\$206.00	N/A
▪ "U" Factor = .39		
▪ "R" Factor = 2.56 - (Per ASTM C1363) ³		
Steel stiffened (20 gauge standard)	\$319.00	N/A
▪ "U" Factor = .61		
▪ "R" Factor = 1.65 (Per ASTM C1363)		
Steel stiffened (18 gauge option)	\$398.00	N/A
Steel stiffened (16 gauge option)	\$558.00	N/A
Steel stiffened with 20 gauge stiffeners and Polystyrene insulation between stiffeners	\$398.00	N/A
Temperature rise 250°, to insulated DL/DE price	\$1,087.00	N/A

3. Not available as Fire rated.

PIVOT OPTIONS		
Description	Door	Frame
Offset or intermediate - per prep ⁴	\$187.00	\$114.00
Center hung - per prep ⁴	N/A	\$114.00
Rescue hardware prep - one pivot prep and emergency stop ⁴	N/A	\$305.00
Double lipped strike - per prep	N/A	\$152.00
Pocket pivot - per prep ⁵	\$206.00	\$173.00

4. No drilling or tapping.
5. No drilling or tapping in door.

HINGE PREPARATIONS		
Description	Door	Frame
Special hinge locations	No charge	No charge
4-1/2" Universal hinge prep (1) prep for every 30" in height	No charge	No charge
Additional hinge prep (per hinge)	\$27.00	\$25.00
4" Template hinge prep (square corner only) (per hinge)	\$62.00	\$62.00
5" Universal weight hinge prep (per hinge)	No charge	No charge
Non-standard height 6"-8" hinge (per hinge)	\$107.00	\$79.00
Double mortise hinge (per hinge)	\$57.00	N/A
Invisible hinge prep (SOSS) (per hinge) (includes drilling and tapping)	\$288.00	\$288.00
Anchor hinge prep (per hinge) (no drilling or tapping)	\$518.00	\$305.00
Electric hinge	\$27.00	\$25.00
▪ No junction box or conduit, no wiring included		
▪ One 1/2" dia. hole in one hinge reinf.		
Surface mounted hinges (reinforcement only)	\$121.00	N/A
Continuous hinge reinforcement	\$94.00	\$88.00
▪ Frame, located either on rabbet or face		
▪ Door, located on either hinge edge or approx 4" on face of hinge side		
High frequency hinge reinforcement (per hinge (typical top hinge only)	N/A	\$30.00
Double acting hinge reinforcement (Eliason) 12 gauge - 24" up x JD @ bottom/12" down x JD @ top (per jamb)	N/A	\$116.00
Double acting hinge reinforcement 12 gauge - 12" x JD (per location)	N/A	\$65.00
Full jamb height hinge reinforcement 12 gauge - 2" x Hgt.	N/A	\$90.00
Power transfer	\$145.00	\$111.00
▪ No junction box or conduit		
▪ Cutout with reinforcement/tap plate(s)		
Special backset (per hinge)	\$139.00	\$78.00
Handed hinge prep	\$21.00	N/A

STRIKE/LOCK PREPARATIONS

Description	Door	Frame
Special strike or lock location	No charge	No charge
ANSI 4-7/8" Strike prep	\$63.00	\$25.00
Mortise lock prep - Gov't 86 edge with function holes	No charge	N/A
Mortise lock prep for 1-3/8" thick door	\$75.00	N/A
Cylindrical dead lock prep	\$65.00	\$25.00
▪ Frame: 2-3/4" or 4-7/8" strike (lipped or non-lipped)		
▪ Door: Gov't 160 or 161 prep		
Mortise dead lock prep	\$65.00	\$25.00
▪ Frame: 3-1/2" or 4-7/8" strike (lipped or non-lipped)		
▪ Door: Gov't 86 mortise lock prep		
Card reader lock prep (ex. Vingcard)	\$57.00	N/A
Special backset (over 5")	\$52.00	N/A
Rim reinforcement only	\$54.00	\$33.00
Rim reinforcement with function prep	\$60.00	N/A
Mortise exit device reinforcement only	\$39.00	N/A
Mortise exit device reinforcement with function prep	\$95.00	N/A
Allegion Mortise exit device reinforcement with function prep	\$76.00	N/A
Surface vertical rod reinforcement only	\$87.00	\$33.00
Surface vertical rod reinforcement with function prep	\$105.00	N/A
Allegion Surface vertical rod reinforcement with function prep	\$93.00	N/A
Concealed vertical rod	\$648.00	\$73.00
▪ Frame mortise strike (per prep)		
▪ Door per template		
Allegion Concealed vertical rod	\$515.00	\$73.00
▪ Frame mortise strike (per prep)		
▪ Door per template		
Exit alarm reinforcement only	\$66.00	\$33.00
Inset exit device (14 and 16 gauge doors only)/ Frame Non ASA strike	\$505.00	N/A
Push pull reinforcement	\$42.00	N/A
Electric strike mortise prep (no junction box or conduit)	\$143.00	\$107.00
Flush bolt	\$101.00	\$63.00
▪ Strike prep Frame, reversible or automatic		
▪ Door - Edge, top and bottom prep - ANSI A115.4		
Surface bolt reinforce only	\$38.00	\$33.00
Detention/security lock (ex. FA NS400/Brinks 3526)	\$163.00	\$151.00
Non-standard gauge/special thickness strike reinforcement (standard prep)	N/A	\$71.00
Flush cup pull prep (per side)	\$137.00	N/A
Roller latch (per prep top or lock edge)	\$94.00	\$46.00
Fire bolt/popper (each prep)	\$46.00	N/A

CLOSER PREPARATIONS

Description	Door	Frame
Closer reinforcement	\$40.00	\$33.00
▪ Frame 14 gauge x 14" Plate - RA or PA		
▪ Door 14 gauge x 18" x 6"		
Door - optional 12 gauge reinforcement	\$75.00	N/A
Door - full width reinforcement (price per 18")	\$40.00	N/A
Frame - full depth reinforcement (price per foot)	N/A	\$35.00
Coordinator reinforcement	N/A	\$33.00
Concealed overhead door closer, holder, or stop	\$394.00	\$307.00
Allegion Concealed overhead door closer, holder, or stop	\$343.00	\$278.00
Surface mounted overhead stop/holder reinforcement	N/A	\$307.00

INACTIVE LEAF PREPARATIONS

Description	Door	Frame
Flush bolt embossment in top/bottom channel	No charge	N/A
ANSI (4-7/8") Strike only	\$63.00	N/A
Cylindrical (2-3/4") or mortise (3-1/2") dead lock strike	\$65.00	N/A
Attaching astragal (includes astragal)	\$116.00	N/A
Open back strike	\$171.00	N/A

LABEL PREPARATIONS

Description	Door	Frame
Mark numbers	No charge	No charge
U.L. Mylar label ¹	\$22.00	\$24.00
U.L. Metal label	\$51.00	\$31.00
ITS/Warnock Hersey Metal label	\$51.00	\$31.00
Hurricane FBC or E330 label	\$22.00	\$24.00

1. Standard unless specified otherwise.

SPECIAL CONSTRUCTIONS		
Description	Door	Frame
Special width (use next larger size) (max 4'10" on doors)	No charge	No charge
Special height (use next larger size) (max 10'0" on doors)	No charge	No charge
Undercut - under 3/8" price next larger size	No charge	N/A
Inverted top channel (standard flush)	No charge	N/A
Flush bottom channel (standard inverted)	No charge	N/A
Seal top or bottom channel and finish smooth (per each)	\$150.00	N/A
Bondo filled edge (includes both hinge and lock edge)	\$128.00	N/A
Continuous welded edge (includes hinge and lock edge) ¹	\$192.00	N/A
Unifit channel - consult factory for availability	\$95.00	N/A
Communicating (6) 4.5" hinge preps x (2) 4-7/8" ASA preps, or (2) 2-3/4" strike preps	N/A	\$88.00
Dutch prep (4) 4.5" hinge preps x (1) ASA preps ²	\$353.00	\$91.00
Cap top of jamb (each)	N/A	\$147.00
Mag switch/DPS - Hole only	\$25.00	\$25.00
Mag switch/DPS - Prep and reinf. (no junction box)	\$131.00	\$97.00
Magnetic/shear lock - mortised prep in top of door	\$343.00	\$219.00
Hospital stop (galv) up to 6" (N/A on double egress)	N/A	\$238.00
8" Junction box welded in	N/A	\$34.00
14" Junction box welded in	N/A	\$34.00
10" Junction box welded in soffit	N/A	\$34.00
Removeable HM mullion prep - notch (1) end of piece, weld in angle clip(s)	N/A	\$90.00
Removeable HM mullion reinforcement only	N/A	\$25.00
removeable hardware mullion reinforcement only	N/A	\$25.00
Beveled lock edge (1/8" in 2") ³	\$23.00	N/A
10 Gauge hinge and 14 gauge lock channels DE Series (standard on 14 gauge door)	\$166.00	N/A
1-3/8" Thick door - DE Series - Polystyrene core only (no DE price adder required) ^{4,5}	\$166.00	N/A
Non-standard rabbet 2" thick door	N/A	\$261.00
14 GA Top or bottom channel (per each)	\$74.00	N/A
Rabbeted door or panel (per edge)	\$797.00	N/A
Wicket door prep (consult factory)	Inquiry**	N/A
Door viewer	\$32.00	N/A
Mail slot/food service pass thru (up to 100 sq. In.) - Cutout only	\$91.00	N/A
Monorail prep (per leaf)	\$487.00	N/A
Automatic door bottom (mortise type)	\$239.00	N/A
Conduit/raceway installed in door - Includes wire pull (N/A in DP)	\$202.00	N/A
Factory installed Allegion Connect wiring harness (N/A in DP doors, see Tech Manual for details)	\$187.00	N/A

1. Not available in 20 gauge.
2. Refer to inactive options for ASA in either top or bottom leaf.
3. Not available in 14 gauge and Inactive leafs with strike(s).
4. 6'8" door - standard (2) 3.5" hinges, (1) CH lock prep
(2-1/8" Bore x 2-3/4" Backset/1" x 2-1/4" Edge)
5. Fire Rated 6'8" requires (3) hinge preps - ADD (1) hinge prep.

****Email Estimating requests for quote prior to order submission.**

Note:

Please include Job Name.

Product is produced off-site and ships separately.

Email: republic.estimating@allegion.com

SPECIAL FINISH PREPARATIONS		
Description	Door	Frame
Second coat of Republic primer	\$132.00	\$123.00
Finish paint setup charge (never waived)	\$1,433.00	\$1,433.00
Finish paint - min. qty. 20 doors or 3pc frames per color (price includes full carton wrap)	\$360.00	\$360.00

Finish paint not available with welded frames.

ANCHOR OPTIONS		Price adjustment	
Description	Door	Frame	
Welded in prepared opening anchor - Punch and dimple with anchor (per anchor)	N/A	\$17.00	
Welded in anchor (per anchor)	N/A	\$7.50	
Punch and dimple only (per prep)	N/A	\$6.00	
Deduct for omit drywall compression anchor (Per frame)	N/A	-\$6.00	
Embossed hole - 3/16" in face for (#10 bugle head screw) approx 3/4" from bottom	N/A	No charge	
3/8" x 5" Sleeve anchor (each) (sold separately)	N/A	\$9.00	

For loose anchors, refer to [Frame Parts](#).

Prepared Opening Frames up 7'1" require 8 anchors (max 8-3/4" depth). Over 7'2" thru 10'0" require 10 (max 8-3/4" depth). Frames over 8-3/4" receive double the quantity and price.

FRAME CONSTRUCTION		
Description	Door	Frame
Mark numbers	No charge	No charge
Unit bundle (3pc)	N/A	\$7.00
Unit bundle (Elevation)	N/A	\$20.00
Standard face weld (3pc)	N/A	\$121.00
Full profile weld (3pc)	N/A	\$220.00

FRAME PROFILE OPTIONS		
Description	Door	Frame
No returns	N/A	No charge
Equal rabbet - standard unequal rabbet	N/A	No charge
Cased open	N/A	No charge
Single rabbet	N/A	No charge
4" Face heads (through 4'0")	N/A	\$64.00
4" Face heads (over 4'0")	N/A	\$89.00
Non standard face - per frame (1" - 3-7/8" Uniform)	N/A	\$79.00
Non standard rabbet - per frame	N/A	\$261.00
Drywall (second) return (1/2") (both sides)	N/A	\$57.00
Kerf (includes weather-stripping)	N/A	\$194.00
Non standard returns (uniform)	N/A	\$79.00
Nailer flange (per frame/both faces)	N/A	\$142.00
Casement ready (MN Series - nailer holes) (per frame)	N/A	\$93.00

GLASS KIT OPTIONS			
	Vision/ Narrow Lite up to 100 inch ²	Half Glass over 100 inch ² up to 800 inch ²	Full Glass over 800 inch ²
Cutout with kit installed	\$245	\$290	N/A
Cutout with kit and reinforcement	\$332	\$377	\$421
Sunburst kit (cutout and 1/2" glass included)	\$594	N/A	N/A
Muntin bar (each)	\$160	\$160	\$160
Galvanized kit add	\$131	\$131	\$131
Glass pocket add (other than 1/4")	\$221	\$221	\$221
Hurricane approved light kits - Air louvers VLFIGHRC or VLFEZHRC (Add to Cutout price above)	\$1,744	\$3,160	\$3,160

Prices are based on Republic standard lite kit (No glass unless noted otherwise). For Bullet Resistant Options, see [Specialty Section](#).

CUTOUT ONLY OPTIONS (GLASS KITS & LOUVERS)			
	Up to 100 inch ²	Over 100 inch ² up to 800 inch ²	Over 800 inch ²
Panel in place	\$91	\$91	N/A
Cutout only	\$91	\$91	N/A
Cutout with reinforcement	\$181	\$181	\$181
Round cutout only (no reinf)	\$345	\$345	N/A
Hurricane Approved Insert / Air Louver 1500 (call for other sizes)	\$797	\$1,568	\$3,677

LOUVER OPTIONS		
Description	Size	Price
Louver installed no reinf	12" x 12"	\$424.00
Louver installed no reinf	18" x 12"	\$481.00
Louver installed no reinf	24" x 12"	\$568.00
Louver installed no reinf	24" x 18"	\$640.00
Louver installed no reinf	24" x 24"	\$779.00
Louver installed no reinf	24" x 60"	\$1,670.00
Special size louvers	Consult Factory	
Galvanized louver add	-	\$58.00
Fusible link louver add	-	\$426.00
Insect screen add	Consult Factory	

Prices are based on Republic standard louver.

SPECIAL PACKAGING		
Description	Door	Frame
Generic door carton (each full carton) packaged over standard carton	\$62.00	N/A
Crating - special materials, sizes, etc.	Consult Factory	

VALU-PAC

DP VALU-PAC DOORS - 418			
418 CRS/HC CR			
Description	Qty	Weight	20
3068 F CH CR	20	1900	\$13,555
3068 F MOL CR	20	1900	\$13,555
3070 F CH CR	20	1980	\$13,939
3070 F MOL CR	20	1980	\$13,939
3070 F DT CR	20	1980	\$13,939
3070 F OL CR	20	1980	\$13,939
3670 F CH CR	20	2320	\$16,243
4070 F CH CR	20	2640	\$17,510

DP VALU-PAC DOORS - 420			
420 CRS/HC CR			
Description	Qty	Weight	20
3068 F CH CR	20	1600	\$12,038
3070 F CH CR	20	1640	\$12,499

420 CRS/HC NO CR			
420 CRS/HC NO CR			
Description	Qty	Weight	20
3068 F CH	20	1440	\$11,270
3070 F CH	20	1500	\$11,731

420 CRS/INSUL (STY) CR			
420 CRS/INSUL (STY) CR			
Description	Qty	Weight	20
3068 F CH CR INS*	20	1660	\$12,826
3070 F CH CR INS*	20	1720	\$13,286

420 CRS/INSUL (STY) NO CR			
420 CRS/INSUL (STY) NO CR			
Description	Qty	Weight	20
3068 F CH INS*	20	1500	\$12,058
3070 F CH INS*	20	1560	\$12,518

418 CRS/HC NO CR			
Description	Qty	Weight	20
3068 F CH	20	1740	\$12,787
3070 F CH	20	1820	\$13,171

418 CRS/INSUL (STY) CR			
Description	Qty	Weight	20
3068 F CH CR INS*	20	1960	\$14,342
3070 F CH CR INS*	20	2120	\$14,726
3070 F MOL CR INS*	20	2120	\$14,726

418 CRS/INSUL (STY) NO CR			
Description	Qty	Weight	20
3068 F CH INS*	20	1800	\$13,574
3070 F CH INS*	20	1960	\$13,958
3070 F MOL INS*	20	1960	\$13,958

1. Discounts apply only to whole Valu-Pac Units of (20).
2. Broken pallets quantities will be at full list price.
3. Valu-Pac discount pricing not eligible for any other additional pricing discounts.
4. For consideration of additional size or product options, please contact the factory.
5. Standard 90 minute mylar label.

1. Discounts apply only to whole Valu-Pac Units of (20).
2. Broken pallets quantities will be at full list price.
3. Valu-Pac discount pricing not eligible for any other additional pricing discounts.
4. For consideration of additional size or product options, please contact the factory.
5. Standard 90 minute mylar label.

DP VALU-PAC DOORS - 418 - GALVANIZED			
418 GALV/HC - CR			
Description	Qty	Weight	20
3068 F CH CR GLV	20	1900	\$15,686
3068 F MOL CR GLV	20	1900	\$15,686
3070 F CH CR GLV	20	1980	\$16,070
3070 F MOL CR GLV	20	1980	\$16,070
3070 F DT CR GLV	20	1980	\$16,070
3070 F OL CR GLV	20	1980	\$16,070
3670 F CH CR GLV	20	2320	\$18,374
4070 F CH CR GLV	20	2640	\$19,642

418 GALV/HC - NO CR			
Description	Qty	Weight	20
3068 F CH GLV	20	1740	\$14,918
3070 F CH GLV	20	1820	\$15,302

418 GALV/INSUL (STY) - CR			
Description	Qty	Weight	20
3068 F CH CR GLV INS*	20	1960	\$16,474
3070 F CH CR GLV INS*	20	2120	\$16,858
3070 F MOL CR GLV INS*	20	2120	\$16,858

418 GALV/INSUL (STY) - NO CR			
Description	Qty	Weight	20
3068 F CH GLV INS*	20	1800	\$15,706
3070 F CH GLV INS*	20	1960	\$16,090
3070 F MOL GLV INS*	20	1960	\$16,090

1. Discounts apply only to whole Valu-Pac Units of (20).
2. Broken pallets quantities will be at full list price.
3. Valu-Pac discount pricing not eligible for any other additional pricing discounts.
4. For consideration of additional size or product options, please contact the factory.
5. Fire-Rated to 3 Hours UL and ITS Limited.

DP VALU-PAC DOORS - 420 - GALVANIZED			
420 GALV/HC - CR			
Description	Qty	Weight	20
3068 F CH CR GLV	20	1600	\$14,170
3070 F CH CR GLV	20	1640	\$14,630

420 GALV/HC - NO CR			
Description	Qty	Weight	20
3068 F CH GLV	20	1440	\$13,402
3070 F CH GLV	20	1500	\$13,862

420 GALV/INSUL (STY) - CR			
Description	Qty	Weight	20
3068 F CH CR GLV INS	20	1660	\$14,957
3070 F CH CR LGLV INS	20	1720	\$15,418

420 GALV/INSUL (STY) - NO CR			
Description	Qty	Weight	20
3068 F CH GLV INS	20	1500	\$14,189
3070 F CH GLV INS	20	1560	\$14,650

1. Discounts apply only to whole Valu-Pac Units of (20).
2. Broken pallets quantities will be at full list price.
3. Valu-Pac discount pricing not eligible for any other additional pricing discounts.
4. For consideration of additional size or product options, please contact the factory.
5. Fire-Rated to 3 Hours UL and ITS Limited.


UNIVERSAL FRAME COMPONENTS			
▪ Discounting Applies to the Total Number of Frame ValuPac Units Purchased			
ME			
Description	Qty	Weight	Valu-Pac List
68 534 PR LH	26	778	\$5,741
68 534 PR RH	26	778	\$5,741
70 534 PR LH	26	804	\$6,015
70 534 PR RH	26	804	\$6,015
30 534 HD	52	375	\$2,796
30 534 HD 4"	28	289	\$3,226
68 734 RH LH	26	910	\$6,440
68 734 PR RH	26	910	\$6,440
70 734 PR LH	26	988	\$6,889
70 734 PR RH	26	988	\$6,889
30 734 HD	52	520	\$3,295
68 814 PR LH	26	962	\$7,563
68 814 PR RH	26	962	\$7,563
70 814 PR LH	26	1014	\$7,837
70 814 PR RH	26	1014	\$7,837
30 814 HD	52	520	\$3,944
68 834 PR LH	26	1014	\$7,563
68 834 PR RH	26	1014	\$7,563
70 834 PR LH	26	1040	\$7,837
70 834 PR RH	26	1040	\$7,837
30 834 HD	52	520	\$3,944
WELDED			
Description	Qty	Weight	Valu-Pac List
3070 534 LH HD	26	1092	\$10,883
3070 534 RH HD	26	1092	\$10,883
3070 534 LH 4HD	26	1144	\$12,480
3070 534 RH 4HD	26	1144	\$12,480
STICKS & MULLIONS			
Description	Qty	Weight	Valu-Pac List
10'3" 534 BJ	39	925	\$6,814
10'3" 534 BM	24	812	\$9,308

1. Discounts apply only to multiples of Valu-Pac units.
2. Broken pallets quantities will be at full list price.
3. Valu-Pac discount pricing not eligible for any other additional special pricing discounts.
4. For consideration of additional size or product options, please contact the factory.











DRYWALL FRAME COMPONENTS			
▪ Discounting Applies to the Total Number of Frame ValuPac Units Purchased			
MH			
Description	Qty	Weight	Valu-Pac List
68 558 PR LH	26	780	\$6,465
68 558 PR RH	26	780	\$6,465
70 558 PR LH	26	832	\$7,064
70 558 PR RH	26	832	\$7,064
30 558 HD	52	364	\$3,045
68 578 PR LH	26	806	\$6,465
68 578 PR RH	26	806	\$6,465
70 578 PR LH	26	858	\$7,064
70 578 PR RH	26	858	\$7,064
30 578 HD	52	416	\$3,045
70 828 PR LH	26	1014	\$8,387
70 828 PR RH	26	1014	\$8,387
30 828 HD	52	468	\$4,493

1. Discounts apply only to multiples of Valu-Pac units.
2. Broken pallets quantities will be at full list price.
3. Valu-Pac discount pricing not eligible for any other additional special pricing discounts.
4. For consideration of additional size or product options, please contact the factory.







PARTS

HINGE PREPARATIONS				
	Part number	Description	Pkg Qty	List each
	3980920	Uni-Fit 4-1/2" Hinge shim Heavy weight to standard weight	1 Shim	\$3.14
	3980921	Uni-Fit 5" Hinge shim Heavy weight to standard weight	1 Shim	\$3.14
	3981752	Hinge filler 1-3/4" 4-1/2" Hinge (handing plate)	1	\$1.97
	3980316	Hinge filler 1-3/4" 5.0" Hinge (handing plate)	1	\$1.97
	3830001	1-3/4" Hinge filler 4-1/2" Hinge 110 FHMS #12/24	50 Filler plates 110 FHMS #12/24	\$11.21



CYLINDRICAL LOCK PREPARATIONS			
	Part number	Description	List each
	3980641	Drive-in dead bolt sleeve	\$3.00
	3831015	Cylindrical lock filler	\$28.41
	3831004	CH (161) Lock edge filler 110 FHMS #8/32	\$10.93
	3980706	Cylindrical lock punchout CH (Gov't 10 - 161)	\$3.00
	3980309	Cylindrical dead lock Tap plate	\$11.21

PARTS


MORTISE LOCK PREPARATIONS

	Part number	Description	List each
	3980000	Mortise strike adaptor 2 FHMS #12/24	\$9.84
	3980300	MOL (86) Edge adaptor 2 FHMS #12/24	\$38.24
	3980301	MOL (86) Lock edge filler 2 FHMS #12/24	\$17.50
	3980707	Mortise Lock punchout Gov't. 86	\$3.00
	3980310	Mortise dead lock Tap plate 10 -24 Tap .187 offset	\$10.93






DOOR EDGE CHANNELS

	Part number	Description	List each
	3908511	16 Gauge door Modification channel 8'0"	\$55.73
	3986339	16 Gauge blank channel 1-3/4" 8'0"	\$32.78
Type 4 CY Louver (Non-labeled) (Approx 30% free air)			
Part number	Description	List each	
3981042	12" x 12"	\$242.00	
3981043	18" x 12"	\$289.00	
3981044	24" x 12"	\$337.00	
3981045	24" x 18"	\$422.00	
3981046	24" x 24"	\$507.00	

MISCELLANEOUS TAP PLATES

	Part number	Description	List each
	3980302	Concealed vertical rod Guide tap plate 10 -32 Tap	\$15.45
	3980219	Flush bolt tap plate Used with an astragal 8 -32 Tap .085 offset	\$10.30
	3980220	Flush bolt tap plate Used without an astragal 8 -32 Tap .085 offset	\$10.30
	3980311	Auto flush bolt Top and bottom tap plate 8 -32 Tap	\$10.30



PARTS

ASTRAGALS				
	Part number	Description	Includes	List each
	3801276	68 4 RH	Standard "Z" type astragal For inactive leaf Prepared for 4-7/8" strike Embossed reinforcements 1 "Z" astragal #8 x 1" PHIL OVAL HD S.D.S	\$95.00
	3801277	68 4 LH		\$95.00
	3801278	70 4 RH		\$95.00
	3801279	70 4 LH		\$95.00
	3801286	80 4 RH		\$95.00
	3801287	80 4 LH		\$95.00
	3801290	68 4 RH	Standard "Z" type astragal For inactive leaf Prepared for 4-7/8" strike Flush bolts Embossed reinforcements 1 "Z" astragal #8 x 1" PHIL OVAL HD S.D.S	\$100.00
	3801291	68 4 LH		\$100.00
	3801292	70 4 RH		\$100.00
	3801293	70 4 LH		\$100.00
	3801300	80 4 RH		\$100.00
	3801301	80 4 LH		\$100.00
	3199908	68 4 RH	Standard "Z" type astragal For inactive leaf Ch, m or mol lock provision 4-7/8" Strike standard 1 "Z" astragal 1-3980000 Mort str adaptor 2 - 12-24 x 1/2" FHMS #8 x 1" PHIL OVAL HD S.D.S	\$95.00
	3199909	68 4 LH		\$95.00
	3199910	70 4 RH		\$95.00
	3199911	70 4 LH		\$95.00
	3199914	80 4 RH		\$95.00
	3199915	80 4 LH		\$95.00
	3199916	68 4 RH	Flush bolt "Z" type astragal For inactive leaf Ch, m or mol lock provision 4-7/8" Strike standard 1 "Z" flush bolt astragal 1-3980000 Mort str adaptor 2 - 12-24 x 1/2" FHMS #8 x 1" PHIL OVAL HD S.D.S	\$100.00
	3199917	68 4 LH		\$100.00
	3199918	70 4 RH		\$100.00
	3199919	70 4 LH		\$100.00
	3199942	8'0"	Blank astragal For active or inactive leaf 1 "Z" astragal blank #8 x 1" PHIL OVAL HD S.D.S Top of astragal must be notched after height and hand is determined	\$65.00
	3199963	10'0"		\$76.00
	3199949	8'0"	Flat bar astragal	\$65.00
	3199950	10'0"	Flat bar astragal	\$76.00


Galvanized add \$19.00 list to the above prices. Price 1-3/8 same as 1-3/4 Unless otherwise specified, flush bolts will be located 12" top and bottom.

PARTS

DUTCH DOOR SHELVES

	Part number	Description	List each
	N/A	Dutch door full shelf 1-3/4" only Available in standard door widths up to 4'0" (over 4'0" consult factory)	\$739.00
	N/A	Dutch door half shelf 1-3/4" only Available in standard door widths up to 4'0" (over 4'0" consult factory)	\$437.00

PAINT

	Part number	Description	List each
	3933981	Air dried beige Primer paint One can (16 oz)	\$29.17

ALLEGION CONNECT HARNESSES: MOLEX CONNECTORS ON BOTH ENDS

	Part number	Description	List each
	106191-00	12" Wire harness	\$67.00
	106192-00	26" Wire harness	\$78.00
	106196-00	50" Wire harness	\$95.00
	106197-00	192" Wire harness	\$201.00


PARTS

ALL METAL STAMPING LOW PROFILE MODEL 110				
Glass kit size	Door size	Exposed glass	Catalog number	List each
Vision Lite	All sizes	10" x 10"	3927102	\$185.00
Narrow Lite	All sizes	5" x 20"	3927104	\$178.00
Narrow Lite	All sizes	3" x 33"	3927130	\$204.00
Narrow Lite	All widths 7'0", 7'2", 7'10", 8'0" hts.	6" x 33"	3927108	\$221.00
Half Glass	3068, 3268	22" x 29"	3927114	\$299.00
Half Glass	3070, 3072, 30710, 3270, 3272, 32710	22" x 33"	3927120	\$316.00
Full Glass	3068, 3268	22" x 59"	3927122	\$457.00
Full Glass	3070, 3072, 30710, 3270, 3272, 32710	22" x 63"	3927124	\$474.00

The above listed glass kits are for 1-3/4" doors.

No Glazing Compound, Tape or Intumescent is required for most label application

- Reduces cost
- Simplifies installation
- Improves appearance



Note: For exterior applications or where glazing tape is required, kits must be ordered with additional glass pocket space.

- Example: If 1/4" glass + 1/16" glazing tape on both sides, you must order the frame for a 3/8" glass pocket (Glass Thickness).

UL AND WH LISTED

Meets UL10B requirements for NEGATIVE PRESSURE and UL10C & UBC 7-2(1997) for POSITIVE PRESSURE. Refer to AMS Listing Specifications.

Fire tested WITHOUT glazing compound, tape or intumescent.

Broken-lot charge for less-than-package quantities: 50% of package list price. (Charge will be discounted at rate of overall order discount)

Special glass lite sizes available, consult factory.

ORDER INFORMATION

Order Size: Inside dimension of frame (H + W)

Cutout Size: Order Size + 1-1/2"

Glass Size: Order Size + 3/4"

MATERIAL

- 18 gauge CRS frame is standard
- 33% thicker than 20 gauge frames
- Maintains flat appearance

DIMENSIONS

- Standard Frame fits 1/4" glass and 1-3/4" door

NARROW FACE FRAME

- Better proportioned
- Visually appealing
- Suitable for wood, metal or mineral core doors

LOW PROFILE



- Provides less interference for exit hardware



NAIL IN FASTENING METHOD


- Requires only one person to install
- Significantly reduces installation time
- Corridor side is fastener free, secure and attractive

this page intentionally blank



PARTS

HINGE PREPARATIONS			
	Part number	Description	List each
 Hinge reinforcements	3832026	11 Gauge 3-1/2"	\$15.30
	3HR0300A002-GL	7 gauge 4-1/2" Universal	\$10.90
	3HR0350A002-GL	7gauge 5" Universal	\$15.30
 Hinge cover plate	3832033	11 Gauge 3-1/2" Hinge filler	\$12.00
	3832034	10 Gauge 4-1/2" Hinge filler	\$12.00




STRIKE PREPARATIONS			
	Part number	Description	List each
 Strike reinforcements	3832031	2-3/4" Strike	\$7.65
	3832032	4-7/8" Strike	\$7.65
 Strike cover plate	3832035	2-3/4" Strike filler	\$9.00
	3832036	4-7/8" Strike filler	\$9.00
 Mortise dead lock tap plate	3831101	Tap plate	\$4.60

CLOSER PREPARATIONS			
	Part number	Description	List each
 Closer reinforcement	3832008	1-3/8" x 14" x 14 Gauge	\$7.00
	3832018	1-3/8" x 14" x 12 Gauge	\$10.00








PARTS

MORTAR GUARDS, JUNCTION BOXES			
	Part number	Description	List each
	3833008	1-3/4" Mortar guard	\$5.00
	3812503	Junction box 14" with knockouts	\$34.00
	3812504	Junction box 8" with knockouts	\$34.00










FLUSH BOLT STRIKE PREPARATIONS			
	Part number	Description	List each
	3981475	1 Set reinforcing and strike plate	\$22.40
	3981049	Tap plate	\$4.65

ANCHORS			
	Part number	Description	List each
	3832037	4-3/4 " Masonry T anchor	\$3.50
	3832038	5-3/4 " Masonry T anchor	\$3.50
	3832039	6-3/4 " Masonry T anchor	\$3.50
	3832078	7-3/4 " Masonry T anchor	\$3.50
	3832040	8-3/4 " Masonry T anchor	\$3.50
	3AN0156P001	Wire masonry anchor	\$3.50
	3812102 - Strap 3812103 - Yoke (order each for 1 assembly)	Adjustable masonry anchor assembly	\$8.50



PARTS





ANCHORS			
	Part number	Description	List each
	3AN0100P020-GL	4-1/2" thru 4-3/4" Universal stud anchor	\$3.50
	3AN0100P016-GL	5-5/8" thru 5-3/4" Universal stud anchor	\$3.50
	3AN0100P014-GL	6-1/8" thru 6-1/4" Universal stud anchor	\$3.50
	3AN0100P012-GL	6-5/8" thru 6-3/4" Universal stud anchor	\$3.50
	3AN0100P008-GL	7-5/8" thru 7-3/4" Universal stud anchor	\$3.50
	3AN0100P006-GL	8-1/8" thru 8-1/4" Universal stud anchor	\$3.50
	3AN0100P004-GL	8-5/8" thru 8-3/4" Universal stud anchor	\$3.50
	3AN0103P001-GL	4-3/4" Steel stud anchor	\$3.50
	3AN0103P002-GL	5-3/4" Steel stud anchor	\$3.50
	3AN0100P014-GL	6-1/4" Steel stud anchor	\$3.50
	3AN0103P003-GL	6-3/4" Steel stud anchor	\$3.50
	3AN0103P004-GL	7-3/4" Steel stud anchor	\$3.50
	3AN0100P006-GL	8-1/4" Steel stud anchor	\$3.50
	3AN0103P005-GL	8-3/4" Steel stud anchor	\$3.50
	3AN0020P014-GL	Universal frame prepared opening anchor (bolt not included)	\$4.40
	3AN0020P012-GL	Cased opening prepared anchor (bolt not included)	\$4.40
	3980668	Twist-in prepared opening anchor 4-3/4"-5-3/4"	\$9.00
	3981452	5-3/4" Snap-in prepared opening anchor with plastic hole plugs	\$5.75
	3981451	Plastic hole plugs	\$0.28
	3981088	3/8" x 5" Sleeve anchor	\$9.00

PARTS



ANCHORS			
	Part number	Description	List each
	3AN0253P002-GL	4-3/4" to 5-5/8" One piece sill anchor	\$3.50
	3AN0253P003-GL	5-3/4" to 6-5/8" One piece sill anchor	\$3.50
	3AN0253P004-GL	6-3/4" to 7-5/8" One piece sill anchor	\$3.50
	3AN0253P005-GL	7-3/4" to 8-5/8" One piece sill anchor	\$3.50
	3AN0253P006-GL	8-3/4" to 9-5/8" One piece sill anchor	\$3.50
	3812100	Double rabbet sill anchor MH and SH frames	\$3.50
	3812099	Single rabbet sill anchor MH and SH frames	\$3.50
	3AN0175A001-GL	Drywall pressure anchor	\$7.11
	3933950	Butterfly anchor 4-1/2" to 7"	\$5.75
	3832045	Adjustable wood/steel stud anchor half (6-3/4" max)	\$4.25
	3832074	4-3/4" Base anchor for sticks	\$13.40
	3832075	5-3/4" Base anchor for sticks	\$13.40
	3832076	6-3/4" Base anchor for sticks	\$13.40
	3832077	8-3/4" Base anchor for sticks	\$13.40
	3399000	Double egress sill anchor (each)	\$3.50
	3AN0081P001-GL	Double egress wood stud anchor (each)	\$5.50
	3399002	Double egress steel stud jamb anchors	\$5.50

PARTS

ANCHORS			
	Part number	Description	List each
	3399003	Double egress steel stud head anchors	\$5.50
	3AN0167P002-GL	5-3/4" Adjustable sill anchor (plate)	\$6.25
	3AN0251P001-GL	5-3/4" Adjustable sill anchor (strap)	\$6.25

GLAZING BEAD/STOP EXTENSION/MISC. ITEMS			
	Part number	Description	List each
	3909837	3/4" x 5/8" x 10' Pre-punch galvanized	\$42.00
Glazing bead			
	3934009	20 Gauge 10'0"	\$46.90
3/4" High stop extension			
	3832022	10'0" Spreader bar	\$31.00
Spreader bar			
	3980866	Z Clip	\$5.00
Clip for removable panel			
	3842021	Self-sticking door mutes	\$0.43
Self-sticking door mutes			
	3904409	Mutes	\$0.62
Mutes			
	3812101	Drywall hole plugs	\$0.61
Drywall hole plugs			

PARTS

GLAZING BEAD/STOP EXTENSION/MISC. ITEMS			
	Part number	Description	List each
	3832064	Mullion clip	\$16.50
Mullion clip			
	3832060	4-3/4" Splice channel	\$20.00
	3832061	5-3/4" Splice channel	\$20.00
	3832062	6-3/4" Splice channel	\$20.00
	3832063	8-3/4" Splice channel	\$20.00
Splice channel			
Image not available	3980677	Full length 14 gauge channel (5-9/16" x 71-11/16")	\$265.23
	3811115	4-3/4" Hospital stop kit	\$33.00
	3811116	5-3/4" Hospital stop kit	\$33.00
	3811117	6-3/4" Hospital stop kit	\$33.00
	3926423	7-3/4" Hospital stop kit	\$33.00
	3811118	8-3/4" Hospital stop kit	\$33.00
Hospital stop kit			

SCREWS			
Part number	Description	Size	List each
3980324	CH-Lock front cover plate, 2-3/4" Strike cover plate, special strikes	#8 - 32 x 1/2" U.C. FHMS (Phillips Flat head undercut machine screw zinc plated)	\$0.21
3980327	Door and frame hinge cover plates - 4-1/2" MOL lock face cover plate	#12 - 24 x 1/2" U.C. FHMS (Flat head undercut machine screw)	\$0.21
3980556	Labels	#6 x 1/2" OHDS (Oval head)	\$0.33
3831089	Aluminum and steel-stick glazing bead clips	#8 x 3/8" Type A Binding HD STS (Self-tapping screw)	\$0.21
3710000	Steel muntin bar clips, steel muntin bar sets	#8 x 3/8" Phil Type B FHSTS (Flat head self-tapping screw)	\$0.27
3911094	Astragals and UL glazing bead	#8 - 1" OH Phil Tek Z Zinc (Oval head)	\$0.33
3911093	Glazing bead	#8 x 1-1/4" Phil OH SDS (Oval head self-drilling screw)	\$0.39
3981567	Non-labeled wood stud applications with prepared openings	#20 x 5" Wood screw	\$2.95

Broken-lot charge for less-than-package quantities: 50% of package list price.

(Charge will be discounted at rate of overall order discount).

About Allegion

At Allegion (NYSE: ALLE), we design and manufacture innovative security and access solutions that help keep people safe where they live, learn, work and connect. We're pioneering safety with our strong legacy of brands like CISA®, Interflex®, LCN®, Schlage®, SimonsVoss® and Von Duprin®. Our comprehensive portfolio of hardware, software and electronic solutions is sold around the world and spans residential and commercial locks, door closer and exit devices, steel doors and frames, access control and workforce productivity systems.

For more, visit www.allegion.com

KRYPTONITE ■ LCN ■ SCHLAGE ■ STEELCRAFT ■ VON DUPRIN